Waterproofing Declaration of Performance Edition 2.04.2013 Identification no. 020707010000000081063

Version no. 01



EN 1504-5

0761

DECLARATION OF PERFORMANCE

13

Sika® Injection-201 CE

020707010000000081063

eclaration of performance

Sika® Injection-201 CE 1. Product Type Unique identification code of the product-type: 2. Type batch or serial number or any other element -201 CE allowing identification of the construction product as batch no. refer to packaging required under Article 11(4): 3. Intended use or uses of the construction product, in accordance with the Injection products for ductile filling of applicable harmonised technical specification, as Cracks according to EN 1504-5 foreseen by the manufacturer: U(D1) W(2) (1/2/3) (5/30) Sika® 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): Sika Deutschland GmbH Kornwestheimer Str. 103-107 70439 Stuttgart, Germany 5. Contact Address not relevant (see 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): 6. AVCP System or systems of assessment and verification of System 2+ constancy of performance (AVCP) of the construction product as set out in CPR, Annex V: 7. Notified body (hEN) 0761 In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: Notified factory production control certification

body No. 0761 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 0062



not relevant

8. Notified body (ETA) In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Adhesion and elongation capacity	~0,6 N/mm ² Elongation: >10%	EN 12618-2	
Watertightness	Watertight at 2 x 10 ⁵ Pa	EN 14068	
Workability Crack widths 0,1 mm – 0,2 mm – 0,3 mm	Injectability class Crack width: ≥ 0,2 mm	EN 1771	
Moisture state of cracks: Dry or not dry	Moisture state of cracks: Wet, damp and dry		EN 1504-5:2013
Durability	Lost deformation work < 20%	EN 12637-1	
Corrosion behaviour	Assumably there are no corroding effects.	EN 1504-5 Article 4	
Release of dangerous substances	Conformity with 5.4	EN 1504-5	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

fl. Pof

Junt

ppa. F+E

i.V. PI Martin Rolfes

i.V. QC Dr. Heinz Ephardt

Stuttgart, 1.Juni 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Deutschland GmbH Kornwestheimer Str. 103-107 70439 Stuttgart Telefone Fax +49 (0) 7 11 80 09-0 +49 (0) 7 11 80 09-321

www.sika.de