

Sarnafil® T Pipe Flashing

Prefabricated FPO pipe/vent flashing

Product Description	Sarnafil® T Pipe Flashing is made of synthetic roof waterproofing membrane based on premium-quality flexible polyolefins (FPO), containing stabilizers, with inlay of glass non-woven.
----------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Uses	Sarnafil® T Pipe Flashing is used as a prefabricated part for pipe/vent flashing on Sarnafil® T/TC flat roof systems.
-------------	-----------------------------------------------------------------------------------------------------------------------

Characteristics / Advantages	<ul style="list-style-type: none">■ Outstanding resistance to weathering, including UV irradiation■ Easy and safe application■ Excellent weldability■ Recyclable
-------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Tests

Approvals / Standards	<ul style="list-style-type: none">■ Quality management system EN ISO 9001/14001■ Reaction to fire according to EN 13501-1, class E
------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------

Product Data

Form

Appearance	Surface: smooth
-------------------	-----------------

Colour	Beige Grey (nearest RAL 7040) Other colours on request
---------------	------------------------------------------------------------------

Packaging	Depending on the order quantity and product size, the products are packaged on pallets or in cartons.
------------------	-------------------------------------------------------------------------------------------------------

Storage

Storage Conditions	Sarnafil® T Pipe Flashing shall be stored in dry conditions.
---------------------------	--------------------------------------------------------------

Shelf-Life	Sarnafil® T Pipe Flashing does not expire during correct storage.
-------------------	-------------------------------------------------------------------

Roofing





Art. No.	Colour	Inside diameter	Sleeve height	Flange size	Material thickness
110461	beige	82 mm	400 mm	300 x 300 mm	1.5 mm
135689	RAL 7040				
110462	beige	92 mm			
135692	RAL 7040				
110456	beige	102 mm			
135693	RAL 7040				
110457	beige	112 mm			
125517	RAL 7040				
110458	beige	127 mm			
135695	RAL 7040				
110459	beige	142 mm			
135696	RAL 7040				
110460	beige	167 mm			
135462	RAL 7040				

Other diameter on request

Technical Data

Material Basis Flexible Polyolefins (FPO)

Seam quality / type Hot plate welding / arc welding

System Information

System Structure

Ancillary products: - Cap for vent pipe in various sizes

Compatible products: - Sarnafil® TG 66-types
- Sarnafil® TG 76-types
- Sarnafil® TS 77-types
- Sarnafil® TCG-types (T Prep required)
- Sarnafil® TCS-types (T Prep required)

Application Conditions / Limits

Temperature The use of Sarnafil® T Pipe Flashing is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

Installation Instructions

Installation Method According to the valid installation instructions for Sarnafil® flat roof waterproofing membranes.

Notes on Installation / Limits

Installation works to be carried out only by Registered Sarnafil T/TC Trained Contractors.

Temperature limits for the installation of the Sarnafil® T Pipe Flashing:

Substrate temperature: -30 °C min. / +60 °C max.

Ambient temperature: -20 °C min. / +60 °C max.

Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.

Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

Roofing

Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
Ecology, Health and Safety Information	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
Protective Measures	Fresh air ventilation must be ensured, when working (welding) in closed rooms. Regulatory safety requirements must be observed.
Transportation Class	The product is not classified as hazardous good for transport.
Disposal	The material is recyclable. Any disposal must be in accordance with regulatory requirements.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and guarantee are valid.



Sika Ltd, Bankside 300, Peachman Way, Broadland Business Park,
Norwich, NR7 0WF.

Tel: 01603 709360 Fax: 01603 433436 Email: sarnafilroofing@uk.sika.com

Registered Office: Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ
Registered in England: 226822



Sarnafil®