
SikaRapid® 2

DECLARATION OF PERFORMANCE

No. 93209815

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	93209815
2	INTENDED USE/S	EN 934-2:2009 +A1:2012 Set accelerating admixture according to BS EN 934-2 (Table 6)
3	MANUFACTURER:	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 934-2:2009 +A1:2012
	Notified body:	1029

Declaration of Performance

SikaRapid® 2
93209815
2021.04 , ver. 1
1088

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	≤ 0.1% w/w	System 2+	EN 934-2:2009 +A1:2012
Alkali content	≤ 2.0% w/w	System 2+	
Setting time	At 20°C: test mix ≥ 30min. At 5°C: test mix ≤ 60% of control mix	System 2+	
Compressive strength	At 28 days: Test mix ≥ 80% of control mix. At 90 days: Test mix ≥ test mix at 28 days	System 2+	
Air content	Test mix ≤ 2% by volume above control mix	System 2+	
Corrosion behaviour	Contains the following components from EN 934-1 Annex A.2 thiocyanates	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anthony Smith
Function: Product Manager
At Sika Limited on 08 April 2021

Name : Martin Liska
Function: R&D Manager
At Sika Limited on 08 April 2021




End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaRapid® 2
93209815
2021.04 , ver. 1
1088





06

Sika Limited, Hertfordshire, United Kingdom

DoP No. 93209815

EN 934-2:2009 +A1:2012

Notified Body 1029

Set accelerating admixture according to BS EN 934-2 (Table 6)

Chloride ion content	$\leq 0.1\% \text{ w/w}$
Alkali content	$\leq 2.0\% \text{ w/w}$
Setting time	At 20°C: test mix $\geq 30\text{min}$. At 5°C: test mix $\leq 60\%$ of control mix
Compressive strength	At 28 days: Test mix $\geq 80\%$ of control mix. At 90 days: Test mix \geq test mix at 28 days
Air content	Test mix $\leq 2\%$ by volume above control mix
Corrosion behaviour	Contains the following components from EN 934-1 Annex A.2 thiocyanates

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaRapid® 2
93209815
2021.04 , ver. 1
1088

3/4

BUILDING TRUST



Sika Limited

Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom
www.sika.co.uk

Declaration of Performance

SikaRapid® 2
93209815
2021.04 , ver. 1
1088

