

PRODUCT DATA SHEET

Deco Mineralised Grit

CRUSHED SLATE

PRODUCT DESCRIPTION

Sika Liquid Plastics Deco Mineralised Grit comprises of crushed slate in various colours that can be used to provide a skid inhibiting surface or a natural mineral look finish roof when used in conjunction with a liquid applied membrane.

USES

- Mineralised grit to be used in conjunction with Sika Liquid Plastics liquid applied waterproofing membranes to provide a skid inhibiting surface to create walkways on roofs

CHARACTERISTICS / ADVANTAGES

- Can be used to create aesthetic mineral look finish roofs

APPROVALS / STANDARDS

- Offers 'Low Slip Potential' when tested according to BS 7976-2: 2002

PRODUCT INFORMATION

Packaging	20kg Bags
Appearance / Colour	Slate is a metamorphic rock. The composition consists of various combinations of minerals including quartz. Coloured Slate: Coarse Red Olive Green Coated Black NOTE: Slate is a naturally occurring material and colours are approximate. Exact matches batch to batch cannot be guaranteed.
Shelf Life	
Storage Conditions	Store in original packaging in a location away from sources of dampness and extremes of temperature. Keep protected from rain.
Maximum Grain Size	0.3mm-1.18mm

APPLICATION INFORMATION

Recommended Dosage

		Creating Walkways
Coverage Rates	Embedment Coat of chosen liquid applied membrane	0.3 l/m ²
	Deco Mineralised Grit	2.5 kg/m ²
		Create Mineral Look Finish
Coverage Rates	Embedment Coat of chosen liquid applied membrane	0.3 l/m ²
	Deco Mineralised Grit	Minimum 5kg/m ² or beach broadcast Sweep off excess (retained grit will be approx 2.5-3kg/m ²)

These figures are given for guidance purposes only

APPLICATION INSTRUCTIONS

Deco Mineralised Grit Walkways on Roofs

Mask off designated walkway to chosen roof areas, Ideally use silver tape (duck tape) to achieve a good bond strength. It is recommended to install a m2 wide walkway across the cured completed system.

Apply a coat of the chosen Sika Liquid Plastic liquid applied roofing membrane at a coverage rate of 0.3l/m² and fully broadcast the mineral grit across the walkway area. Whilst wet remove the silver tape (duck tape) and dispose of it accordingly.

NB. Non-removal of the tape before the coating has cured will result in time consuming removal and will also give a untidy edge finish. Once cured sweep away any excess mineral grit off the walkway and re-bag to use again. If the grit has become damp overnight due to inclement weather then the grit will be harder to remove and a stiff brush maybe required. Let the excess grit dry out on a dry open floor to be used again.

properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of this product, please refer to the most recent Safety Datasheet.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when

TECHNICAL ENQUIRIES

Tel: 01772 255015

Web: www.liquidplastics.co.uk

Twitter: @LiquidPlastics

SIKA LIMITED

Watchmead

Welwyn Garden City
Hertfordshire, AL7 1BQ

Tel: 01707 394444

Web: www.sika.co.uk

Twitter: @SikaLimited



DecoMineralisedGrit_en_GBLP_(03-2017)_1_1.pdf

Product Data Sheet

Deco Mineralised Grit

March 2017, Version 01.01

020816010020000002