

SikaGrind® 304

Cement Additive

Product Description SikaGrind® 304 is a liquid cement additive that has been specifically formulated to suppress the carbon staining associated with PFA blended cements.

Uses SikaGrind® 304 has been specifically formulated to: -

- Increase the cement performance in concrete
- Enhance the quality of the blended cement
- Suppress the carbon staining associated with PFA blended cements

Characteristics / Advantages SikaGrind® 304 is a very effective dispersant with the following characteristics: -

- Modifies the electrical charges on the surface of the cement particles which facilitates their separation

SikaGrind® 304 provides the following advantages in the cement production:

- Reduced re-agglomeration of the cement particles
- Less accumulation of material on grinding equipment
- Easier handling and improved flow characteristics

SikaGrind® 304 gives the following advantages to the finished cement: -

- Easier discharge of the silos
- Allows economic cement design

Product Data

Form

Appearance / Colour Brown Liquid

Packaging 1000 litre IBC and Bulk Tanker

Storage

Storage Conditions / Shelf-Life 12 months from date of production if stored in unopened and undamaged original sealed containers protected from moisture at temperatures between +5°C and +25°C.

Technical Data

Chemical Base Modified lignosulphonate

Density 1.14 kg/litre

pH Value 5.0 ± 1.0

Water Soluble Chloride Content <0.10% (chloride free)

Alkali Content <0.05%



System Information

Application Details

Consumption / Dosage	0.1 – 0.6% by weight of cement (cement clinker + additions)
Dispensing	<ul style="list-style-type: none"> ■ SikaGrind® 304 should be dispensed through suitable calibrated equipment ■ SikaGrind® 304 is to be added into the grinding mill (first or second compartment), onto the clinker feeding channel or onto the clinker (raw material) on the conveyor belt.

Application Conditions / Limitations

Compatibility	<p>Sika® Admixtures:</p> <ul style="list-style-type: none"> ■ Compatibility information available on request <p>Cements:</p> <ul style="list-style-type: none"> ■ All cement combinations
----------------------	---

Notes on Application / Limitations	Support from our Technical Department is recommended
---	--

Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
-------------------	--

Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
---------------------------	---

Health and Safety Information	For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.
--------------------------------------	---

Legal Notes	<p>The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.</p>
--------------------	---



SIKA LIMITED
 Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom
 Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · www.sika.co.uk

