according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1 Print Date 09.11.2015



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-310 PurCem (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0) 1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled. Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1

Carcinogenicity, Category 2

H317: May cause an allergic skin reaction.
H351: Suspected of causing cancer.
H325: May cause respiratory irritation

Specific target organ toxicity - single exposure, Category 3, Respiratory system
Specific target organ toxicity - repeated
H335: May cause respiratory irritation.
H373: May cause damage to organs through pro-

exposure, Category 2 longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)



Revision Date 09.11.2015			Version 1.1	Print Date 09.11.2015
_				
	Hazard statements	: H315	Causes skin irritation.	
		H317	May cause an allergic skin re	eaction.
		H319	Causes serious eye irritation.	
		H332	Harmful if inhaled.	
		H334	May cause allergy or asthma breathing difficulties if inhaled	
		H335	May cause respiratory irritation	on.
		H351	Suspected of causing cancer	- -
		H373	May cause damage to organ	s through pro-
			longed or repeated exposure).
	Precautionary statements	: Prevention:		
	•	P201	Obtain special instructions be	efore use.
		P260	Do not breathe dust/ fume/ g	
			pours/ spray.	
		P280	Wear protective gloves/ eye protection.	protection/ face
		P281	Use personal protective equiquired.	pment as re-
		Response:	1	
		P308 + P313	IF exposed or concerned: Ge vice/ attention.	et medical ad-
		P333 + P313	If skin irritation or rash occurs	s: Get medical

advice/ attention.

Hazardous components which must be listed on the label:

9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
Diphenylmethanediisocyanate, isomeres and homo-	Acute Tox.4; H332	>= 50 - <= 100
logues	Skin Irrit.2; H315	
9016-87-9	Eye Irrit.2; H319	
	Resp. Sens.1; H334	
	Skin Sens.1; H317	
	Carc.2; H351	

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)



Revision Date 09.11.2015 Version 1.1 Print Date 09.11.2015

STOT SE3; H335 STOT RE2; H373

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)



Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).


Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)





SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40

Revision Date 09.11.2015

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)





Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Diphenylmethanediisocy-	9016-87-9	urinary diamine:	Post task	GB EH40
anate, isomeres and		1µmol/mol creati-		BAT
homologues		nine		
		(Urine)		

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1



Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : clear

transparent

Odour : No data available

Odour Threshold : No data available

Flash point : > 100 °C

Ignition temperature : Not applicable

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : No data available

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,23 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Country GB 10000006207

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1



Viscosity, kinematic : > 7 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1



Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks: May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Product:

Germ cell mutagenicity- As- : No data available

sessment

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assess-

ment

: Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

Product:

Reproductive toxicity - As- : No data available

sessment

No data available

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1



Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1 Print Date 09.11.2015



SECTION 14: Transport information

ADR

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

: Banned and/or restricted (Diphenylmethanediisocyanate, isomeres and homologues)

: None of the components are listed

(=> 0.1 %).

: Not applicable

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- : The Chemicals (Hazard Information and Packaging for Sup-

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)

Revision Date 09.11.2015 Version 1.1



mental regulation/legislation specific for the substance or mixture:

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if in-
	haled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure

Full text of other abbreviations

Acute Tox.	Acute toxicity
Carc.	Carcinogenicity
Eve Irrit.	Eve irritation

Resp. Sens. Respiratory sensitisation

if inhaled.

Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route Chemical Abstracts Service

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LC50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LD50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic

according to Regulation (EC) No. 1907/2006

Sikafloor®-310 PurCem (B)



Revision Date 09.11.2015 Version 1.1 Print Date 09.11.2015

PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!