

PRODUCT DATA SHEET

EVERBUILD® PVCu Acti-Spray

An aerosol applied activator for safe use on all PVCu and plastics

PRODUCT DESCRIPTION

EVERBUILD® PVCu Acti-Spray is an aerosol applied activator for use with Everbuild® Industrial Superglue GP and HV, setting superglue in 10 seconds. Guaranteed not to stain PVCu. Acti-spray is ideal for use on all PVCu and plastics.

USES

For use on all PVCu and plastics.

CHARACTERISTICS / ADVANTAGES

- Works on all common building surfaces.
- Suitable for use with all cyanoacrylate superglues.
- Will not cause yellowing of uPVC frames and trim.

PRODUCT INFORMATION

Packaging	200 mL aerosol
Appearance / Colour	Clear
Shelf Life	12 months if stored correctly.
Storage Conditions	Store in cool dry conditions away from direct sunlight between +5 and +25 °C. Storage outside these parameters will significantly reduce shelf life. Ensure good ventilation.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

FOR PROFESSIONAL USE ONLY

- Ensure surfaces are degreased prior to bonding.
- Do not use on glass.
- Do not use in applications involving constant water immersion.
- Do not use on bitumen or tar leaching products.
- On wooden/porous surfaces, do not use any other cyanoacrylate except Superglue HV. These products are thinner and the soak in will give poor bond

strength.

- It is the user's responsibility to determine suitability for use. If in any doubt contact Technical Services for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Remove cap from canister and apply activator to one of the surfaces to be bonded. Apply cyanoacrylate adhesive to the other surface (e.g. Everbuild® Superglue HV Adhesive). Bring the parts together ensuring the joint is accurate. Joint sets hard in approximately 5 seconds. Always replace cap after use to prevent the pen drying out.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited