

## Decostik® Foaming Adhesive Applicator Cordless Application Tool

<b>Product Description</b>	Decostik® Foaming Adhesive Applicator is a battery operated tool that has been developed to provide a fast, consistent application of adhesive. Sika Liquid Plastics Decostik® Foaming Adhesive is a solvent free, two-part liquid-applied urethane adhesive, specifically formulated to bond Decotherm insulation to various existing substrates. The product is dispensed via a twin cartridge system to avoid any risk of incorrect mixing and handling of liquids.
<b>Uses</b>	<ul style="list-style-type: none"> <li>■ To be used only in conjunction with Decostik® Foaming Adhesive</li> </ul>
<b>Characteristics / Advantages</b>	<ul style="list-style-type: none"> <li>■ Cordless application tool</li> <li>■ Lightweight</li> <li>■ Quiet</li> <li>■ Easy to use</li> </ul>

**Material/Appearance / Colours**



Supplied with two batteries and a charger

**Application Conditions / Limits**

**Application**

Using a sharp knife cut the two nibs off the threaded head of a cartridge and attach the mixing nozzle. If the cartridge is equipped with a "snap off" tip, break the tip off and keep for re-use and then attach the mixing nozzle.

Attach a mixing tip to the threaded mixing head. Place the cartridge into the applicator. At the beginning of the tube, some of the material should be pumped out initially to make sure of a proper mix. Apply Decostik® Foaming Adhesive directly to the substrate, using a ribbon pattern.

Please refer to the Product Datasheet for Decostik Foaming Adhesive for more information on coverage rates etc.



<b>Value Base</b>	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
<b>Ecology, Health and Safety Information</b>	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
<b>REACH</b>	<b>European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)</b>  This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.  Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).
<b>Protective Measures</b>	Local safety regulations must be observed.
<b>Transportation Class</b>	The product is not classified as hazardous good for transport.

## General Information

<b>Specification Assistance</b>	NBS is the industry standard specification system, which allows architects, specifiers and engineers to insert clauses into specifications by manufacturer and product, making the process quicker and more efficient. We are members of NBS Plus and therefore detailed up-to-date product information is readily available to create accurate specifications.
<b>Disclaimer</b>	The information, and, in particular, the recommendations relating to the application and end- use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

<b>Contact Details</b>	For further information please contact:  Sika Liquid Plastics Sika House Miller Street Preston Lancashire PR1 1EA  Enquiry line: +44 (0)1772 259781 Fax: +44 (0)1772 255670 e-mail: <a href="mailto:liquidplastics@uk.sika.com">liquidplastics@uk.sika.com</a> Website: <a href="http://www.liquidplastics.co.uk">www.liquidplastics.co.uk</a>
------------------------	--

Registered office: Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ  
Registered in England: 226822

