

Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021	Version 8.5	Print Date 31.08.2021
Revision Date: 31.08.2021		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor-29/31 PurCem(B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

	,
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021		Version 8.5	Print Date 31.08.2021
Signal word :	Danger		
Hazard statements :	H315 H317 H319 H332 H334 H335 H351 H373	Causes skin irritation. May cause an allergic skin r Causes serious eye irritation Harmful if inhaled. May cause allergy or asthma breathing difficulties if inhale May cause respiratory irritat Suspected of causing cance May cause damage to organ longed or repeated exposure	n. a symptoms or ed. ion. er. ns through pro-
Precautionary statements :	Prevention: P201 P260 P264 P280	Obtain special instructions b Do not breathe mist or vapo Wash skin thoroughly after h Wear protective gloves/ prot eye protection/ face protectio	urs. nandling. ective clothing/
	Response: P304 + P340 + P308 + P313	P312 IF INHALED: Remove air and keep comfortable for POISON CENTER/ doctor if IF exposed or concerned: G vice/ attention.	breathing. Call a you feel unwell.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Print Date 31.08.2021

Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021	Version 8.5	
Revision Date: 31.08.2021		

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 40 - < 60

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021 Version 8.5

Print Date 31.08.2021

methylenediphenyl diisocyanate	26447-40-5	Acute Tox. 4; H332	>= 40 - < 60
neuryieneuphenyi alisooyanate	905-806-4	Skin Irrit. 2; H315	0 - 00
	01-2119457015-45-	Eye Irrit. 2; H319	
	XXXX	Resp. Sens. 1; H334	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Skin Sens. 1; H317	
		Carc. 2; H351	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
		0101 NE 2, 11373	
		specific concentration	
		limit	
		Eye Irrit. 2; H319	
		>= 5 %	
		STOT SE 3; H335	
		>= 5 %	
		Skin Irrit. 2; H315	
		>= 5 %	
		Resp. Sens. 1; H334	
		>= 0,1 %	
		STOT RE 2; H319	
		>= 5 %	
		STOT SE 3; H335	
		>= 5 %	
		Skin Irrit. 2; H315	
		>= 5 %	
		Resp. Sens. 1; H334	
		>= 0,1 %	
		0,1 /0	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021	Version 8.5	Print Date 31.08.2021
	If eye irritation persists, consult a specialist.	
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	person.
4.2 Most important symptoms and e	effects, both acute and delayed	
Symptoms :	Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information on and symptoms.	health effects
Risks :	irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breath ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged exposure.	

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021		Version 8.5	Print Date 31.08.2021
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	g apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	se i	measures	
6.1 Personal precautions, protect	ctiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sewe If the product contaminates rivers and lakes or o respective authorities.	
6.3 Methods and material for co	ntai	inment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	-
6.4 Reference to other sections			

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021		Version 8.5	Print Date 31.08.2021
Hygiene measures	:	Handle in accordance with good industrial hygi practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage, i	incl	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well- place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Sto ance with local regulations.	arefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as direct	cted.
7.3 Specific end use(s)			
Specific use(s)	:	Cleaning with aprotic polar solvents must be av Consult most current local Product Data Sheet use.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	GB EH40
	Further information	ation: Capable of ca	ausing occupation	al asthma.
		STEL	0,07 mg/m3 (NCO)	GB EH40
methylenediphenyl diisocyanate	26447-40-5	TWA	0,02 mg/m3 (NCO)	GB EH40
	asthma (also k can induce a s immunological become hyper- sometimes eve toms. These sy asthma. Not al come hyper-re those who are that can cause substances wh with pre-existin include the dis classified as as mation can be assessments of	ation: Substances t nown as asthmage tate of specific airw irritant or other me responsive, further en in tiny quantities ymptoms can range I workers who are e sponsive and it is in likely to become hy occupational asthmatich may trigger the ng airway hyper-res ease themselves. T sthmagens or respi found in the HSE p of the evidence for a rever it is reasonable	ns and respiratory ay hyper-respons chanism. Once the exposure to the s may cause respire in severity from a exposed to a sens mpossible to ident yper-responsive. na should be distin symptoms of asth ponsiveness, but the latter substance ratory sensitisers. ublication Asthma agents implicated	v sensitisers) iveness via an e airways have substance, ratory symp- a runny nose to itiser will be- ify in advance Substances nguished from ma in people which do not ces are not Further infor- igen? Critical in occupational



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021	
Revision Date: 31.08.2021	

Version 8.5

Print Date 31.08.2021

sonably p centration ment is be employee may caus consultati degree of pational a assigned asthma in bered tha pational a	equires that exposure be reduced to as low as is rea- racticable. Activities giving rise to short-term peak con- s should receive particular attention when risk manage- ing considered. Health surveillance is appropriate for all s exposed or liable to be exposed to a substance which e occupational asthma and there should be appropriate on with an occupational health professional over the risk and level of surveillance., Capable of causing occu- sthma., The 'Sen' notation in the list of WELs has been only to those substances which may cause occupational the categories shown in Table 1. It should be remem- other substances not in these tables may cause occu- sthma. HSE's asthma web pages .gov.uk/asthma) provide further information.
	STEL 0,07 mg/m3 GB EH40 (NCO)

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT
methylenediphenyl diisocyanate	26447-40-5	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment					
Eye protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.			

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

te of last issue: 31.08.2021 evision Date: 31.08.2021		Version 8.5	Print Date 31.08.2021
	Bu Co Su Vi	uitable for short time use or protection utyl rubber/nitrile rubber gloves (> 0,1 ontaminated gloves should be remove uitable for permanent exposure: ton gloves (0.4 mm), eakthrough time >30 min.	mm)
Skin and body protection	loı ar	rotective clothing (e.g. Safety shoes a ng-sleeved working clothing, long trou nd protective boots are additionaly rec nd stirring work.	users). Rubber aprons
Respiratory protection	: In Re ex in Us re se or A ² Er ex oc tic to lin	case of inadequate ventilation wear r espirator selection must be based on posure levels, the hazards of the pro- g limits of the selected respirator. se a properly fitted NIOSH approved a spirator complying with an approved a sesment indicates this is necessary. ganic vapor filter (Type A) 1: < 1000 ppm; A2: < 5000 ppm; A3: <- nsure adequate ventilation. This can be chaust extraction or by general ventilates that extraction or by general ventilates and the mixing / stirring area. In can keep the concentrations under the oc- nits then respiration protection measures and a sure adequate ventilation, especially	known or anticipated duct and the safe work- air-purifying or air-fed standard if a risk as- < 10000 ppm be achieved by local ition. (EN 689 - Meth- e). This applies in par- ise this is not sufficent ccupational exposure ires must be used.
Environmental exposure c	ontrols		
General advice		o not flush into surface water or sanita the product contaminates rivers and l	

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour	: liquid : light brown : slight
Boiling point/boiling range	: No data available
Flash point	: > 150 °C Method: closed cup
Auto-ignition temperature	: No data available
рН	: Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021	Version 8.5	Print Date 31.08.2021

Viscosity

Viscosity, dynamic	: ca. 40 - 80 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility	: insoluble
Vapour pressure	: 0,01 hPa
Density	: ca. 1,23 g/cm3 (20 °C)
Relative vapour density	: ca. 8,5

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Country GB 00000608755

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021	Version 8.5	Print Date 31.08.2021
Revision Date: 31.08.2021		

Components:

	Diphenylmethanediisocyan Acute oral toxicity	ate, :	isomeres and homologues: LD50 Oral (Rat): > 10.000 mg/kg		
	Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.		
	Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg		
	Skin corrosion/irritation Causes skin irritation.				
	Serious eye damage/eye irri	itati	on		
	Causes serious eye irritation.				
	Respiratory or skin sensitis	atio	on and a second s		
	Skin sensitisation May cause an allergic skin rea	actio	on.		
	Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.				
	Germ cell mutagenicity Not classified based on availa	able	information.		
	Carcinogenicity Suspected of causing cancer.				
	Reproductive toxicity				
	Not classified based on availa	ble	information.		
	STOT - single exposure May cause respiratory irritatio	n.			
	STOT - repeated exposure May cause damage to organs	s thr	ough prolonged or repeated exposure.		
	Aspiration toxicity Not classified based on availa	able	information.		
11.2	Information on other hazard	st			
	Endocrine disrupting prope	rtie	S		
	Product: Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to		



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021		Version 8.5	Print Date 31.08.20
	(REACH Article 57(f) or Commission Dele EU) 2017/2100 or Commission Regulatic evels of 0.1% or higher.	
SECTION 12: Ecological info	ormati	on	
12.1 Toxicity			
Components:			
Diphenylmethanediisocya	nate, is	someres and homologues:	
Toxicity to fish		_C50 (Brachydanio rerio (zebrafish)): > 1. Exposure time: 96 h	.000 mg/l
Toxicity to algae/aquatic plants	I	EC50 (Desmodesmus subspicatus (greer ng/l Exposure time: 72 h	າ algae)): > 1.640
12.2 Persistence and degradab No data available	ility		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB a	assess	ment	
<u>Product:</u> Assessment	t	This substance/mixture contains no comp o be either persistent, bioaccumulative a very persistent and very bioaccumulative 0.1% or higher	nd toxic (PBT), or
12.6 Endocrine disrupting prop	erties		
Product:			
Assessment	e (The substance/mixture does not contain of ered to have endocrine disrupting propert REACH Article 57(f) or Commission Deley EU) 2017/2100 or Commission Regulation evels of 0.1% or higher.	ties according to gated regulation
12.7 Other adverse effects			
Product:			
Additional ecological infor-	: '	There is no data available for this product	I
Country CB 00000608755			12 / 17



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021
Revision Date: 31.08.2021

Version 8.5

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 05 01* waste isocyanates
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
Country CR 00000609755		

Country GB 00000608755

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021	Version 8.5	Print Date 31.08.2021
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards Not regulated as a dangerous	s good	
14.6 Special precautions for use Not applicable	r	
14.7 Transport in bulk according Not applicable for product as	g to Annex II of Marpol and the IBC Code supplied.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 74, 56) methylenediphenyl diisocyanate (Number on list 74, 56)
International Chemical Weapons Schedules of Toxic Chemicals ar	· · · · · · · · · · · · · · · · · · ·	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea I/or gula	am suppliers, and/or ation, and/or



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021	Version 8.5	Print Date 31.08.2021
Revision Date: 31.08.2021		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	 Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMALL) and emergedments
	Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 H317 H319 H332 H334 H335 H351	: : : : : : : : : : : : : : : : : : : :	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. Suspected of causing cancer.
H373 H373	:	May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure if inhaled.
Full text of other abbreviatio	ons	
Acute Tox. Carc. Eye Irrit. Resp. Sens.	:	Acute toxicity Carcinogenicity Eye irritation Respiratory sensitisation

Country GB 00000608755



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021
Revision Date: 31.08.2021

Version 8.5

Print Date 31.08.2021

Skin Irrit.	:	Skin irritation		
Skin Sens.	:	Skin sensitisation		
STOT RE	:	Specific target organ toxicity - repeated exposure		
STOT SE	:	Specific target organ toxicity - single exposure		
GB EH40		UK. EH40 WEL - Workplace Exposure Limits		
GB EH40 BAT		UK. Biological monitoring guidance values		
GB EH40 / TWA		Long-term exposure limit (8-hour TWA reference period)		
GB EH40 / STEL	-	Short-term exposure limit (15-minute reference period)		
ADR		European Agreement concerning the International Carriage of		
//BIC	•	Dangerous Goods by Road		
CAS		Chemical Abstracts Service		
DNEL	:	Derived no-effect level		
EC50	:	Half maximal effective concentration		
GHS	:			
IATA	•	Globally Harmonized System		
IMDG	-	International Air Transport Association		
	•	International Maritime Code for Dangerous Goods		
LD50	-	Median lethal dosis (the amount of a material, given all at		
		once, which causes the death of 50% (one half) of a group of		
		test animals)		
LC50	:	Median lethal concentration (concentrations of the chemical in		
		air that kills 50% of the test animals during the observation		
		period)		
MARPOL	:	International Convention for the Prevention of Pollution from		
		Ships, 1973 as modified by the Protocol of 1978		
OEL	:	Occupational Exposure Limit		
PBT	:	Persistent, bioaccumulative and toxic		
PNEC	:	Predicted no effect concentration		
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament		
		and of the Council of 18 December 2006 concerning the Reg-		
		istration, Evaluation, Authorisation and Restriction of Chemi-		
		cals (REACH), establishing a European Chemicals Agency		
SVHC	:	Substances of Very High Concern		
vPvB	:	Very persistent and very bioaccumulative		

Further informatior Classification of th	•	Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method



Sikafloor-29/31 PurCem(B)

Date of last issue: 31.08.2021 Revision Date: 31.08.2021 Version 8.5

Print Date 31.08.2021

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN