

# PRODUCT DATA SHEET

# SikaRoof® Fastener SF-RS-6.1

#### CARBON STEEL FASTENER FOR SIKA-TROCAL ROOFING SYSTEMS

### PRODUCT DESCRIPTION

The SikaRoof® SF-RS-6.1 is a high quality fastener manafactured from SAE1022 case hardened steel, oval head form with TX25 recess

#### **USES**

Used with dedicated accessories for the attachment of Sika-Trocal® roof waterproofing systems.

# **CHARACTERISTICS / ADVANTAGES**

- Excellent pull-out performance and resistance to unwinding
- Compatible with the Sika-Trocal® range of tube washers and pressure plates
- Specially designed thread formation for use with concrete and timber substrates
- Purpose designed and precision manufactured

## PRODUCT INFORMATION

Chemical Base	Steel SAE1022 case hardened, oval head form with TX25 recess
Packaging	See current price list
Shelf Life	Will not expire under normal conditions
Storage Conditions	Must be stored between +5 °C and +30 °C in original packaging protected from direct sunlight, rain, snow and chemicals
Dimensions	Shaft diameter - 6.1mm Head diameter - 9.1mm Iengths - see current price list

# **APPLICATION**

Recommended pilot hole for concrete usually 5.0mm diameter. Pilot hole depth should be a minimum of 25mm greater than embedment depth to allow for sediment. A site pull-out test is required for all concrete deck applications.

#### **VALUE BASE**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### **Product Data Sheet**

**SikaRoof® Fastener SF-RS-6.1**November 2019, Version 01.01
020945051100000060

#### **LOCAL RESTRICTIONS**

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

# **ECOLOGY, HEALTH AND SAFETY**

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate Ballymun Dublin 11, Ireland Tel: +353 1 862 0709 Web: www.sika.ie Twitter: @SikaIreland







Product Data Sheet SikaRoof® Fastener SF-RS-6.1 November 2019, Version 01.01 020945051100000060



SikaRoofFastenerSF-RS-61-en-GB-(11-2019)-1-1.pdf