

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikadur[®]-32 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product is not intended for consumer use, Adhesive

1.3 Details of the supplier of the safety data sheet

Company	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
Telephone	:	+44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num- : +44 (0)1707 363899 (available during office hours) ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Sikadur[®]-32 (B)



Revision Date 27.06.2018		Version 3.0	Print Date 27.06.20
Hazard statements	: H314 H317 H411	May cause an allergi	burns and eye damage. ic skin reaction. with long lasting effects.
Precautionary statements	P304 + P34	Avoid release to the Wear protective glov eye protection/ face 1 + P353 IF ON SKIN (or ately all contaminate with water. 0 + P310 IF INHALED: Re air and keep comfort mediately call a POIS 1 + P338 + P310 IF IN EN with water for several	res/ protective clothing/ protection. hair): Take off immedi- ed clothing. Rinse skin emove person to fresh table for breathing. Im- SON CENTER/doctor. YES: Rinse cautiously al minutes. Remove esent and easy to do. mediately call a

Hazardous components which must be listed on the label:

- 220-666-8 3-aminomethyl-3,5,5-trimethylcyclohexylamine
- 292-588-2 Amines, polyethylenepoly-, triethylenetetramine fraction
- 202-013-9 2,4,6-tris(dimethylaminomethyl)phenol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 10 - < 20
3-aminomethyl-3,5,5-trimethylcyclohexylamine 2855-13-2 220-666-8 01-2119514687-32-XXXX	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Chronic3; H412	>= 5 - < 10



Revision Date 27.06.2018

Version 3.0

	Eye Dam.1; H318	
(1-methylethyl)-1,1'-biphenyl 25640-78-2 247-156-8 01-2119982993-17-XXXX Contains: diisopropyl-1,1'-biphenyl	Eye Irrit.2; H319 Asp. Tox.1; H304 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 5 - < 10
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 292-588-2 01-2119487919-13-XXXX Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 5 - < 10
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2 202-013-9 01-2119560597-27-XXXX Contains: bis[(dimethylamino)methyl]phenol <= 15 %	Skin Sens.1B; H317 Skin Corr.1C; H314 Eye Dam.1; H318	>= 3 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.



Revision Date 27.06.2018

Version 3.0

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	 Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Health injuries may be delayed. corrosive effects sensitising effects
	May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

•	Extinguioning moula		
	Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2	Special hazards arising from	the	e substance or mixture
	Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contam- inated fire extinguishing water must be disposed of in accord- ance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

Revision Date 27.06.2018

Version 3.0

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up :	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on	n safe handling		Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Fol- low standard hygiene measures when handling chemical products
Advice on fire and ex		:	Normal measures for preventive fire protection.
Hygiene n	neasures		Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Condition	s for safe storage, ind	clu	iding any incompatibilities
	ents for storage I containers		Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Other data	а	:	No decomposition if stored and applied as directed.
7.3 Specific e	nd use(s)		
Specific u	se(s)		Consult most current local Product Data Sheet prior to any use.



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipm	ent		
Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.		
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.		
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.		
Respiratory protection	: No special measures required.		
Environmental exposure controls			
General advice	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. 		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	 :	paste
Colour	:	brown

Version 3.0

Revision Date 27.06.2018



Odour	:	amine-like
Odour Threshold	:	No data available
Flash point	:	> 101 °C
Autoignition temperature	:	Not applicable
		No data available
Decomposition temperature	:	No data available
Lower explosion limit (Vol-%)	:	No data available
Upper explosion limit (Vol-%)	:	No data available
Flammability	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
рН	:	> 11 at 50,00 g/l
Melting point/range / Freez-	:	No data available
ing point Boiling point/boiling range	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca.1,4 g/cm3 at 20 °C
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20,5 mm2/s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

9.2 Other information

No data available

Revision Date 27.06.2018

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

<u>Components:</u> benzyl alcohol: Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg		
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
3-aminomethyl-3,5,5-trimeth Acute oral toxicity		yclohexylamine: LD50 Oral (Rat): 1.030 mg/kg		
Acute inhalation toxicity	:	LC50 (Rat): > 5,01 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg		
Amines, polyethylenepoly-, triethylenetetramine fraction: Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.465 mg/kg		

2,4,6-tris(dimethylaminomethyl)phenol:

Sikadur[®]-32 (B)



Revision Date 27.06.2018

Version 3.0

Acute oral toxicity

: LD50 Oral (Rat): 2.169 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Assessment: The product is a skin sensitiser, sub-category 1A. Result: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol :

Toxicity to fish	: LC50: > 100 mg/l, 96 h, Fish
Toxicity to daphnia and other aquatic invertebrates 3-aminomethyl-3,5,5-trimeth	: EC50: > 100 mg/l, 48 h, Daphnia magna (Water flea)
5-animometriyi-5,5,5-trimetri	yicycioliekylallille .
Toxicity to algae	\sim ErC50 > 10 - 100 mg/L 72 h Desmodesmus subspicatus

Toxicity to algae	:	ErC50: > 10 - 100 mg/l, 72 h, Desmodesmus subspicatus
		(green algae)

(1-methylethyl)-1,1'-biphenyl :



Revision Date 27.06.2018	Version 3.0	Print Date 2
Toxicity to daphnia and other aquatic invertebrates 2,4,6-tris(dimethylaminomet	: LC50: 0,167 mg/l, 48 h, Daphnia magna (' h yl)phenol :	Water flea)
Toxicity to algae	: EC50: > 10 - 100 mg/l, 72 h, Scenedesmu (fresh water algae)	us capricornutum
12.2 Persistence and degradabili	ty	
No data available		
12.3 Bioaccumulative potential		
No data available		
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB as	sessment	
Product:		
Assessment	 This substance/mixture contains no comp to be either persistent, bioaccumulative ar very persistent and very bioaccumulative 0.1% or higher. 	nd toxic (PBT), or
12.6 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be exclu unprofessional handling or disposal. Toxic to aquatic life with long lasting effec	

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Sikadur[®]-32 (B)



Revision Date 27.06.2018	Version 3.0	Print Date 27.06.2018
European Waste Catalogue	: 08 01 11* waste paint and varnish conta vents or other dangerous substances	aining organic sol-
Contaminated packaging	: 15 01 10* packaging containing residues by dangerous substances	of or contaminated

SECTION 14: Transport information

ADR 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Classification Code Labels Tunnel restriction code 14.5 Environmental hazards	 1759 CORROSIVE SOLID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-methylethyl)-1,1'-biphenyl) 8 III C10 8 (E) yes
IATA 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Labels 14.5 Environmental hazards	 1759 Corrosive solid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1- methylethyl)-1,1'-biphenyl) 8 III 8 yes
IMDG 14.1 UN number 14.2 UN proper shipping name 14.3 Class 14.4 Packing group Labels EmS Number 1 EmS Number 2 14.5 Marine pollutant IMDG Alkalis	 1759 CORROSIVE SOLID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-methylethyl)-1,1'-biphenyl) 8 III 8 F-A S-B yes

14.6 Special precautions for user

Sikadur[®]-32 (B)

Print Date 27.06.2018

Revision Date 27.06.2018

Version 3.0

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: (3)
REACH Information:	All substances contained in our Products are - preregistered or registered by our upstream suppliers, and/or - preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2	ENVIRONMENTAL HAZARDS	200 t	500 t
VOC-CH (VOCV)	: 18,54 %		
VOC-EU (solvent)	: 18,54 %		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Sikadur®-32 (B)

Revision Date 27.06.2018

Version 3.0



SECTION 16: Other information

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Skin Corr.	Skin corrosion
Skin Sens.	Skin sensitisation
ADR	European Agreement concerning the International Carriage of Danger- ous Goods by Road
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

Classification of the mixture:		Classification procedure:	
Skin Corr. 1B	H314	Calculation method	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikadur®-32 (B)



Revision Date 27.06.2018		Version 3.0	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Chronic 2	H411	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !