

Date of last issue: 28.03.2023 Version	13.2 Print Date 01.06.2023
Revision Date: 01.06.2023	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor[®]-264 N/264 N Thixo (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person	:	EHS@uk.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4H302: Harmful if swallowed.Skin corrosion, Sub-category 1BH314: Causes severe skin burns and eye damage.Serious eye damage, Category 1H318: Causes serious eye damage.Skin sensitisation, Category 1H317: May cause an allergic skin reaction.Long-term (chronic) aquatic hazard, Category 3H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	LE	
Signal word	:	Danger	•
Hazard statements	:	H302 H314 H317	Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction.



Date of last issue: 28.03.2023 Revision Date: 01.06.2023		Ve	rsion 13.2	Print Date 01.06.2023
		H412	Harmful to aquatic life with long fects.	lasting ef-
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory trac	xt.
Precautionary statements	:	Prevention:		
		P261 P273 P280	Avoid breathing mist or vapours Avoid release to the environment Wear protective gloves/ protection eye protection/ face protection.	nt.
		Response:		
		P303 + P361 + F	P353 IF ON SKIN (or hair): Tak ately all contaminated clothing. with water.	
		P304 + P340 + F	P310 IF INHALED: Remove pe air and keep comfortable for bre mediately call a POISON CENT	eathing. Im-
		P305 + P351 + F	P338 + P310 IF IN EYES: Rins with water for several minutes. I tact lenses, if present and easy tinue rinsing. Immediately call a CENTER/ doctor.	e cautiously Remove con- to do. Con-

Hazardous components which must be listed on the label:

Adduct IXA-P (epoxy amine adduct, polymer) 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 28.03.2023 Revision Date: 01.06.2023 Version 13.2

Print Date 01.06.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	>= 40 - < 60
Adduct IXA-P (epoxy amine ad- duct, polymer)	212580-83-1 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 20 - < 25
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 	>= 10 - < 20
		Acute oral toxicity: 1.030 mg/kg	



Date of last issue: 28.03.2023	
Revision Date: 01.06.2023	

Version 13.2

Print Date 01.06.2023

m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity estimate	>= 10 - < 20
		Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.



Date of last issue: 28.03.2023 Revision Date: 01.06.2023		Version 13.2	Print Date 01.06.2023
In case of eye contact	:	Small amounts splashed into eyes can ca sue damage and blindness. In the case of contact with eyes, rinse imr of water and seek medical advice. Continue rinsing eyes during transport to Remove contact lenses. Keep eye wide open while rinsing.	mediately with plenty
If swallowed	:	Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco	
4.2 Most important sympton	ns and e	effects, both acute and delayed	
Symptoms	:	Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information and symptoms.	tion on health effects
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects	
		Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.	
4.3 Indication of any immed	iate med	dical attention and special treatment nee	eded
		Treat symptomatically.	

5.1 Extinguishing media Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		



:	In the event of fire, wear self-contained breat	hing apparatus.
:	Standard procedure for chemical fires.	
se r	neasures	
ctiv	e equipment and emergency procedures	
:	Use personal protective equipment. Deny access to unprotected persons.	
:		
ntai	nment and cleaning up	
:	acid binder, universal binder, sawdust).	-
	: ser :	 se measures ctive equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary set If the product contaminates rivers and lakes or respective authorities. ntainment and cleaning up Soak up with inert absorbent material (e.g. satisfies)

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety



Date of last issue: 28.03.2023 Revision Date: 01.06.2023		Version 13.2	Print Date 01.06.2023
		practice. When using do not eat or drink. Wher smoke. Wash hands before breaks and at the	
7.2 Conditions for safe storage, in	ncl	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well- place. Containers which are opened must be c sealed and kept upright to prevent leakage. Ste ance with local regulations.	arefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as dire	cted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet use.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
Contains no substances with occupational exposure limit values					

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	E	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	2 : C P C	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	E C S	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), preakthrough time >30 min.
Skin and body protection	le a	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, ong-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection		No special measures required.



ate of last issue: 28.03.2023 evision Date: 01.06.2023		Version 13.2	Print Date 01.06.2023
Environmental exposure con	ntra	ble	
General advice	:	Do not flush into surface water or sanita If the product contaminates rivers and la respective authorities.	
SECTION 9: Physical and cher	mi	cal properties	
9.1 Information on basic physical	la	nd chemical properties	
Physical state Colour Odour	:	liquid light yellow amine-like	
Melting point/range / Freezing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or Upper explosion limit / Up- per flammability limit			
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 68 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	ca. 11 (20 °C)	
Viscosity Viscosity, dynamic	:	ca. 100 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	

: No data available

: 4,9996 hPa

Partition coefficient: n-

octanol/water

Vapour pressure



Date of last issue: 28.03.2023 Revision Date: 01.06.2023	Version 13.2	Print Date 01.06.2023
Density	: ca. 1,03 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information No data available		
SECTION 10: Stability and re	activity	
10.1 Reactivity No dangerous reaction know	under conditions of normal use.	
10.2 Chemical stability The product is chemically sta	ble.	
10.3 Possibility of hazardous re	actions	
Hazardous reactions	: Stable under recommended storage condit	ions.
10.4 Conditions to avoid		
Conditions to avoid	: No data available	
10.5 Incompatible materials		

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.	
Components:	
benzyl alcohol: Acute oral toxicity	: LD50 Oral (Rat): 1.620 mg/kg
	Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	: LC50 (Rat): > 4,178 mg/l Exposure time: 4 h



Date of last issue: 28.03.2023 Version 13.2 Print Date 01.06.2023 Revision Date: 01.06.2023 Test atmosphere: dust/mist Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method 3-aminomethyl-3,5,5-trimethylcyclohexylamine: Acute oral toxicity Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008 LD50 Oral (Rat): 1.030 mg/kg Acute inhalation toxicity LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg LD50 (Rabbit): > 2.000 - 5.000 mg/kg m-phenylenebis(methylamine): Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg Acute toxicity estimate: 930 mg/kg Method: Calculation method Acute inhalation toxicity LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract. Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method Acute dermal toxicity LD50 Dermal (Rat): > 3.100 mg/kg ÷. Hydrocarbons, C9, aromatics: Acute oral toxicity 2 LD50 Oral (Rat): > 2.000 mg/kg : LD50 Dermal (Rabbit): > 2.000 mg/kg Acute dermal toxicity 2.4.6-tris(dimethylaminomethyl)phenol: Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised

REGULATION (EC) No 1272/2008



e of last issue: 28.03.2023 ision Date: 01.06.2023	Version 13.2	Print Date 01.06.2023
Skin corrosion/irritation		
Causes severe burns.		
Components:		
Hydrocarbons, C9, aroma	tics:	
Assessment	: Repeated exposure may cause skin dr	ryness or cracking.
2,4,6-tris(dimethylaminon	nethyl)phenol:	
Species	: Rabbit	
Assessment Method	: Corrosive : OECD Test Guideline 404	
Method		
Assessment	: irritating	
Remarks	: Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Serious eye damage/eye i	rritation	
Causes serious eye damag		
Components:		
2,4,6-tris(dimethylaminon	ethyl)phenol:	
Species	: Rabbit	
Assessment	: Causes serious eye damage.	
Assessment	: irritating	
Remarks	: Annex VI - Harmonised	
	REGULATION (EC) No 1272/2008	
Respiratory or skin sensi	isation	
Skin sensitisation		
May cause an allergic skin	reaction.	

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Corrosive to the respiratory tract.



Date of last issue: 28.03.2023	
Revision Date: 01.06.2023	

Version 13.2

Print Date 01.06.2023

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:	
benzyl alcohol:	
Toxicity to fish :	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
3-aminomethyl-3,5,5-trimethyl	cyclohexylamine:
Toxicity to algae/aquatic : plants	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h
	NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h
m-phenylenebis(methylamine)	:
Toxicity to fish :	LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h
Hydrocarbons, C9, aromatics: Toxicity to algae/aquatic :	

Version 13.2

Sikafloor[®]-264 N/264 N Thixo (B)

Date of last issue: 28.03.2023

Revision Date: 01.06.2023



Print Date 01.06.2023

plants ma/l Exposure time: 72 h 2,4,6-tris(dimethylaminomethyl)phenol: Toxicity to algae/aguatic : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 plants - 100 ma/l Exposure time: 72 h 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential No data available 12.4 Mobility in soil No data available 12.5 Results of PBT and vPvB assessment Product: Assessment This substance/mixture contains no components considered : to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. 12.6 Endocrine disrupting properties Product: Assessment 2 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Product: Additional ecological infor-An environmental hazard cannot be excluded in the event of 5 mation unprofessional handling or disposal. Harmful to aquatic life with long lasting effects. **SECTION 13: Disposal considerations** 13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe



Date of last issue: 28.03.2023 Revision Date: 01.06.2023		Version 13.2	Print Date 01.06.2023
		way. Dispose of surplus and non-recyclable products waste disposal contractor. Disposal of this product, solutions and any by-p at all times comply with the requirements of env protection and waste disposal legislation and an local authority requirements. Avoid dispersal of spilled material and runoff an soil, waterways, drains and sewers.	roducts should ⁄ironmental ny regional
European Waste Catalogue	:	08 01 11* waste paint and varnish containing over the second seco	organic sol-
Contaminated packaging	:	15 01 10* packaging containing residues of or on by dangerous substances	contaminated

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1760	
	IMDG	:	UN 1760	
	ΙΑΤΑ	:	UN 1760	
14.2	2 UN proper shipping name			
	ADR	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5 phenylenebis(methyla	-trimethylcyclohexylamine, m-
	IMDG	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5 phenylenebis(methyla	-trimethylcyclohexylamine, m-
	ΙΑΤΑ	:	Corrosive liquid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))	
14.3	B Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	8	
	IMDG	:	8	
	ΙΑΤΑ	:	8	
14.4	Packing group			
	ADR Packing group	:	Ш	



Date of last issue: 28.03.2023 Revision Date: 01.06.2023	Version 13.2	Print Date 01.06.2023
Classification Code Hazard Identification Number Labels Tunnel restriction code	: C9 : 80 : 8 : (E)	
IMDG Packing group Labels EmS Code Remarks	: II : 8 : F-A, S-B : Alkalis	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 855 : Y840 : II : Corrosive	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 851 : Y840 : II : Corrosive	

14.5 Environmental hazards

ADR Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

: Not applicable



Date of last issue: 28.03.2023 Revision Date: 01.06.2023	Version ?	13.2		Print Date 01.06.2023
UK REACH Candidate list of subs concern (SVHC) for Authorisation		:	Not applicable	
The Persistent Organic Pollutants Regulations (retained : Not applicable Regulation (EU) 2019/1021 as amended for Great Brit- ain)				
International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors				
Regulation (EC) No 1005/2009 on substances that de- : Not applicable plete the ozone layer			Not applicable	
UK REACH List of substances subject to authorisation (Annex XIV)		:	Not applicable	
GB Export and import of hazardo Informed Consent (PIC) Regulation		:	Not applicable	
Control of Major Accident Hazard	s Regulations	Not	applicable	
2015 (COMAH) Volatile organic compounds :	(VOCV)		or volatile organic comp ds (VOC) content: 50,6	
	emissions (integrated	poll	4 November 2010 on ir ution prevention and co ds (VOC) content: 50,6	ontrol)
If other regulatory information app	blies that is not already	prov	vided elsewhere in the s	Safety Data

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards
	Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.



be fatal if swallowed and enters airways. es severe skin burns and eye damage. cause an allergic skin reaction. es serious eye damage. es serious eye irritation. ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
es severe skin burns and eye damage. cause an allergic skin reaction. es serious eye damage. es serious eye irritation. ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
cause an allergic skin reaction. es serious eye damage. es serious eye irritation. ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
es serious eye damage. es serious eye irritation. ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
es serious eye irritation. ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
ful if inhaled. cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
cause respiratory irritation. cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
cause drowsiness or dizziness. to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
to aquatic life with long lasting effects. ful to aquatic life with long lasting effects. e toxicity term (chronic) aquatic hazard ation hazard
ful to aquatic life with long lasting effects. e toxicity eterm (chronic) aquatic hazard ation hazard
e toxicity term (chronic) aquatic hazard ation hazard
term (chronic) aquatic hazard ation hazard
term (chronic) aquatic hazard ation hazard
ation hazard
us eye damage
ritation
mable liquids
corrosion
sensitisation
fic target organ toxicity - single exposure
bean Agreement concerning the International Carriage of
erous Goods by Road
nical Abstracts Service
ed no-effect level
naximal effective concentration
ally Harmonized System
• •
ational Air Transport Association
ational Maritime Code for Dangerous Goods
an lethal dosis (the amount of a material, given all at
which causes the death of 50% (one half) of a group of
nimals)
an lethal concentration (concentrations of the chemical in
at kills 50% of the test animals during the observation
ational Convention for the Prevention of Pollution from
, 1973 as modified by the Protocol of 1978
pational Exposure Limit
stent, bioaccumulative and toxic
cted no effect concentration
lation (EC) No 1907/2006 of the European Parliament
lation (EC) No 1907/2006 of the European Parliament
lation (EC) No 1907/2006 of the European Parliament f the Council of 18 December 2006 concerning the Reg- on, Evaluation, Authorisation and Restriction of Chemi-
lation (EC) No 1907/2006 of the European Parliament f the Council of 18 December 2006 concerning the Reg-

Further information

Classification of the mixture:

Classification procedure:



Date of last issue: 28.03.2023 Revision Date: 01.06.2023		Version 13.2	Print Date 01.06.2023
Acute Tox. 4	H302	Calculation method	
Skin Corr. 1B	H314	Calculation method	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN