

PRODUCT DATA SHEET

FOAM APPLICATOR HEAVY DUTY

P65 HEAVY DUTY METAL GUN

PRODUCT DESCRIPTION

Polyurethane foam applicator gun with universal adapter. For professional use.

USES

Suitable for various uses and heavy duty applications including;

- Qualified installation of modern windows.
- Installation of roof tiles and Monk and Nun tiles.
- Installation of exterior insulation and finish systems.
- Filling of difficult to access recessed places.
- Optimal operation with high and low expansion foams.

PRODUCT INFORMATION

Packaging	500 boxes per pallet. 1 unit per box.
Storage Conditions	Store in cool, dry conditions.
Dimensions	305 x 170 x 50 mm
Weight	0.38 kg

LIMITATIONS

- FOAM APPLICATOR HEAVY DUTY has been made for use as a gun for polyurethane foams; any other use is to be considered improper.
- Before carrying out any disassembly, cleaning or re-

CHARACTERISTICS / ADVANTAGES

- Gives the user more control to apply the foam precisely in hard to reach places, saving unnecessary wastage.
- Improves accuracy and speed of application.
- Modern and ergonomic design.
- Unique easy clean tip to clean nozzle and valve from cured foam residue.

assembly operations on the spray gun, ALWAYS release the air and foam pressures.

- Refer to the installation instructions supplied with FOAM APPLICATOR HEAVY DUTY carefully for your own safety before proceeding to the installation, use or maintenance of FOAM APPLICATOR HEAVY DUTY.
- To maintain effective use clean using Everbuild® Dual

Purpose Foam Cleaner.

OPERATING INSTRUCTIONS

Operation

For safe use and correct maintenance, FOAM APPLICATOR HEAVY DUTY should only be used by an operator who is adequately trained. After having removed the packaging, make sure the equipment is intact, checking that there are no visibly damaged parts.

1. Screw the thread of the can onto the shaft until the can is tight, being careful not to strip the threads.
2. Pull the trigger to start the flow of foam.
3. Regulate the stream of flow by adjusting the rear knob.

Cleaning

Before any cleaning operation of FOAM APPLICATOR HEAVY DUTY: At the end of the job, screw completely the regulation knob to lock the needle. This will avoid foam leakage from the nozzle.

1. If using more than one can per job, replace the empty can as soon as possible to avoid hardening of the foam in the gun.
2. A partially used can may be left on the gun. It is not necessary to clean the gun until the can is completely empty.
3. Clean the gun as soon as possible after the can is empty to avoid the foam from becoming hard inside the gun. Once the foam has become hard in the gun, solvent will not dissolve the foam's residuals.
4. Clean the gun with the Everbuild® Foam Cleaner. Any other solvent will damage the gun. NEVER USE WATER TO CLEAN THE GUN.
5. Leave the solvent in the gun for 2 minutes. Release the solvent from the gun by pressing the trigger. Repeat this process until the solvent released is completely clean with no trace of the foam.
6. Unscrew the regulation knob and remove the needle. Clean the needle with a non-abrasive product. Hardened foam will damage the needle.
7. Grease the needle before replacing it in the gun. Replace the empty can as soon as possible.

NOTE: The cleaner cannot remove residual of hardened foam even with a prolonged action.

products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
FOAM APPLICATOR
HEAVY DUTY
December 2022,
Version 01.01
020516040000000060
2 / 2



FOAMAPPLICATORHEAVYDUTY-en-GBEVER-(12-2022)-1-1.pdf

BUILDING TRUST

