Refurbishment Declaration of Performance Edition 11.2016 Identification no. 02 03 02 03 003 0 000028 Version no. 01



**JIK**a

1504-3:2005

16

0086

# **DECLARATION OF PERFORMANCE**

## SikaCem<sup>®</sup> -133GP Gunite

02 03 02 03 003 0 000028 1088

<b>1. Product Type:</b> Unique identification code of the product-type:	SikaCem <sup>®</sup>	
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	<ul> <li>133GP - Gunite (Batch No See packagin</li> <li>1-component class R4 mortar for the r of concrete structures</li> <li>Principles 3, 7 - methods 3.3, 7.1, 7.2</li> <li>Conforming to the Annex ZA Table ZA.</li> </ul>	
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:		
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	SikaCem <sup>®</sup> Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom	
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)	
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+	
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP)concerning a construction product covered by a harmonised standard:	0086 Notified factory production control certibody No. 0086 performed the initial inspite manufacturing plant and of factory point control and the continuous surveillance assessment and evaluation of factory point control and issued the certificate of control the factory production control (FPC) 54	

1/3

Refurbishment Declaration of Performance Edition 11.2016 Identification no. 02 03 02 03 003 0 000028 Version no. 01

8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (see 7)
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------

### 9. Declared performance

R

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Compressive strength	Class R4	EN 12190	
Chloride ion content	≤ 0.05%	EN 1015-7	
Adhesive bond	≥ 2.0 MPa	EN 1542	-
Restrained shrinkage / expansion	NPD*	EN 1261704	_
Carbonation resistance	Passed	EN 13295	EN 1504-3: 2005
Elastic modulus	≥ 20GPa	EN 13412	
Coefficient of thermal expansion	~ 10 x 10 <sup>-6</sup> m/m °C	EN 1770	
Capillary absorption	≤ 0.5 kg/m²/h <sup>0.5</sup>	EN 13057	-
Reaction to fire	Class A1	EN 13501-1	
Dangerous Substances	Complies with 5.4	Complies with 5.4	

\*Not required for repair method 3.3

Refurbishment Declaration of Performance Edition 11.2016 Identification no. 02 03 02 03 003 0 000028 Version no. 01

#### **10. Declaration**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

R&D Manager

Technical Manager

11, 2016

### Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

#### Legal note:

(R)

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



SIKA LIMITED Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · www.sika.co.uk 3 /3