

Date of last issue: 05.01.2023	Version 3.7	Print Date 29.02.2024
Revision Date: 11.12.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Parex Tec

[:] Parex Tecgrip V Summer Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Grouting mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 1, hearing organs	H372: Causes damage to organs through pro- longed or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.



Date of last issue: 05.01.2023 Revision Date: 11.12.2023		Version 3.7	Print Date 29.02.2024
2.2 Label elements			
Labelling (REGULATION (EC	C) No 1272/2008)		
Hazard pictograms			
Signal word	: Danger	• •	
Hazard statements	: H226 H304 H315 H319 H335 H361d H372 H412	Flammable liquid and vapou May be fatal if swallowed an Causes skin irritation. Causes serious eye irritatior May cause respiratory irritat Suspected of damaging the Causes damage to organs (through prolonged or repeat Harmful to aquatic life with le fects.	nd enters airways. n. ion. unborn child. hearing organs) red exposure.
Precautionary statements	 Prevention: P210 P260 P280 	Keep away from heat, hot su open flames and other igniti smoking. Do not breathe dust/ fume/ g pours/ spray. Wear protective gloves/ prot eye protection/ face protecti	on sources. No gas/ mist/ va- rective clothing/
	Response: P301 + P310	IF SWALLOWED: Immediat	elv call a

P301 + P310
P301 + P310
P301 + P310
P331
P370 + P378
P370 +

Hazardous components which must be listed on the label:

styrene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 05.01.2023 Revision Date: 11.12.2023 Version 3.7

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		(70 00/00)
styrene	100-42-5 202-851-5 01-2119457861-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation tox- icity (vapour): 11,8 mg/l	>= 25 - < 40

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.



ate of last issue: 05.01.2023 evision Date: 11.12.2023	Version 3.7	Print Date 29.02.202
If swallowed	 Do not induce vomiting without medical adv Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconstruction 	
I.2 Most important symptoms ar	d effects, both acute and delayed	
Symptoms	 Aspiration may cause pulmonary oedema a Cough Respiratory disorder Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information and symptoms. 	
Risks	: Risk of serious damage to the lungs (by as irritant effects	piration).
	May be fatal if swallowed and enters airway Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unborn child.	yS.
	Causes damage to organs through prolong exposure.	ed or repeated
I.3 Indication of any immediate i Treatment	Causes damage to organs through prolong	
•	Causes damage to organs through prolong exposure. nedical attention and special treatment need : Treat symptomatically.	
Treatment	Causes damage to organs through prolong exposure. nedical attention and special treatment need : Treat symptomatically.	
Treatment	Causes damage to organs through prolong exposure. nedical attention and special treatment need : Treat symptomatically.	
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media	Causes damage to organs through prolong exposure. medical attention and special treatment need : Treat symptomatically. sures : Alcohol-resistant foam Carbon dioxide (CO2)	
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing	Causes damage to organs through prolong exposure. medical attention and special treatment need : Treat symptomatically. sures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water	
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from	Causes damage to organs through prolong exposure. medical attention and special treatment need : Treat symptomatically. sures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water	led
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod-	Causes damage to organs through prolong exposure. medical attention and special treatment need : Treat symptomatically. sures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water the substance or mixture	led



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024
Further information :	Use water spray to cool unopened containers.	
SECTION 6: Accidental release	measures	
6.1 Personal precautions, protectiv	e equipment and emergency procedures	
Personal precautions :	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explo tions. Vapours can accumulate in low areas.	sive concentra-
6.2 Environmental precautions		
Environmental precautions :	Prevent product from entering drains. If the product contaminates rivers and lakes or respective authorities.	drains inform
6.3 Methods and material for conta	inment and cleaning up	
Methods for cleaning up :	Contain spillage, and then collect with non-con sorbent material, (e.g. sand, earth, diatomaced miculite) and place in container for disposal ac / national regulations (see section 13).	ous earth, ver-

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024
	measures against electrostatic discharges.	
Hygiene measures	Handle in accordance with good industrial hyperactice. When using do not eat or drink. When smoke. Wash hands before breaks and at the	en using do not
7.2 Conditions for safe storage, in	cluding any incompatibilities	
Requirements for storage areas and containers	Keep container tightly closed in a dry and wel place. Containers which are opened must be sealed and kept upright to prevent leakage. S ance with local regulations.	carefully re-
Further information on stor- age stability	No decomposition if stored and applied as dir	ected.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
styrene	100-42-5	TWA	100 ppm 430 mg/m3	GB EH40
		STEL	250 ppm 1.080 mg/m3	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024
	long-sleeved working clothing, long tro and protective boots are additionaly re and stirring work.	
Respiratory protection	 In case of inadequate ventilation wear Respirator selection must be based or exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: Ensure adequate ventilation. This can exhaust extraction or by general ventil ods for determining inhalation exposur ticular to the mixing / stirring area. In c to keep the concentrations under the c limits then respiration protection meas 	 < 10000 ppm be achieved by local lation. (EN 689 - Meth- re). This applies in par- case this is not sufficent boccupational exposure
Environmental exposure co	ntrols	
General advice	: Prevent product from entering drains. If the product contaminates rivers and respective authorities.	lakes or drains inform

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid No data available
Odour	:	aromatic
Melting point/range / Freezing point	:	No data available
Initial boiling point and boiling range	:	> 145 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	Upper flammability limit 6,1 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 1,1 %(V)



Date of last issue: 05.01.2023 Revision Date: 11.12.2023		Version 3.7	Print Date 29.02.2024
Flash point	:	ca. 31 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	No data available	
Viscosity Viscosity, kinematic	:	No data available	
Solubility(ies) Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	5,9995 hPa	
Density	:	ca. 1 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024
	Vapours may form explosive mixture	with air.
10.4 Conditions to avoid		
Conditions to avoid	: Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositio	n products	
No decomposition if stored	and applied as directed.	
SECTION 11: Toxicological	information	
11.1 Information on hazard cla	sses as defined in Regulation (EC) No 127	72/2008

Acute toxicity

Not classified based on available information.

Components:

styrene:

Acute inhalation toxicity	:	LC50 (Rat): 11,8 mg/l Exposure time: 4 h Test atmosphere: vapour	

Acute toxicity estimate: 11,8 mg/l Test atmosphere: vapour Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



Date of last issue: 05.01.2023	
Revision Date: 11.12.2023	

Version 3.7

Print Date 29.02.2024

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.



Date of last issue: 05.01.2023 Revision Date: 11.12.2023 Version 3.7

Print Date 29.02.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

:	wherever possible. Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed
	waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental
	protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with
	soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1866	
	IMDG	:	UN 1866	
	ΙΑΤΑ	:	UN 1866	
14.2	UN proper shipping name			
	ADR	:	RESIN SOLUTION (styrene)	
	IMDG	:	RESIN SOLUTION (styrene)	
	ΙΑΤΑ	:	Resin solution (styrene)	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADR Packing group Classification Code	:	III F1	



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024
Hazard Identification Number Labels Tunnel restriction code	: 30 : 3 : (D/E)	
IMDG Packing group Labels EmS Code	: III : 3 : F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	 366 Y344 III Flammable Liquids 	
ger aircraft) Packing instruction (LQ) Packing group Labels	 355 Y344 III Flammable Liquids 	
14.5 Environmental hazards ADR		
Environmentally hazardous	: no	
Marine pollutant	: no	
IATA (Passenger) Environmentally hazardous	: no	
IATA (Cargo) Environmentally hazardous	: no	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors



Date of last issue: 05.01.2023 Revision Date: 11.12.2023	Version 3.7	Print Date 29.02.2024				
Regulation (EC) No 1005/2009 on substances that de- : Not applicable plete the ozone layer						
Volatile organic compounds :	Law on the incentive tax for volatile organic con (VOCV) Volatile organic compounds (VOC) content: < 0 no VOC duties Directive 2010/75/EU of 24 November 2010 on emissions (integrated pollution prevention and o Volatile organic compounds (VOC) content: < 0	% w/w industrial control)				
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.						
Health, safety and environ- : mental regulation/legislation specific for the substance or mixture:	Environmental Protection Act 1990 & Subsidiar Health and Safety at Work Act 1974 & Subsidia Control of Substances Hazardous to Health Rey (COSHH) May be subject to the Control of Major Accident Regulations (COMAH), and amendments.	ry Regulations gulations				

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 H304 H315 H319 H332 H335 H361d H372 H412	:	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.			
Full text of other abbreviations					
Acute Tox. Aquatic Chronic Asp. Tox. Eye Irrit. Flam. Liq. Repr. Skin Irrit.		Acute toxicity Long-term (chronic) aquatic hazard Aspiration hazard Eye irritation Flammable liquids Reproductive toxicity Skin irritation			



Date of last issue: 05.01.2023
Revision Date: 11.12.2023

Version 3.7

Print Date 29.02.2024

STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation period)
MARPOL		International Convention for the Prevention of Pollution from
MART OF	•	Ships, 1973 as modified by the Protocol of 1978
OEL		Occupational Exposure Limit
PBT		Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH		Regulation (EC) No 1907/2006 of the European Parliament
	-	and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
		• • •

Further information

Classification of the m	ixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 2	H361d	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 1	H372	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Date of last issue: 05.01.2023 Revision Date: 11.12.2023 Version 3.7

Print Date 29.02.2024

Changes as compared to previous version !

GB / EN