

Sika[®] Stixall[®] Clear

DECLARATION OF PERFORMANCE

No. 13666060

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	13666060
2	INTENDED USE/S	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	4
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	N/A

Sika[®] Stixall[®] Clear 13666060 2024/08 , ver. 06 1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD		
Loss of volume	≤45 %		
Resistance to flow	≤5 mm		
Elongation	≥ 25 %		
			EN 15651- 1:2012
		-	1.2012
·			

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas

Function: Technical Product


Coordinator

At Leeds on 27 August 2024

Name: Alex West

Function: Product Manager At Leeds on 05 September 2024

End of information as required by Regulation (EU) No 305/2011





		14
	Sika Ser	vices AG, Zurich, Switzerland
	Sind Sci	DoP No. 13666060
		EN 15651-1:2012
		Notified Body N/A
Sea	lant for non-structural use in joints in build	dings and pedestrian walkways Part 1: Sealants for Façade elemen
	,	, ,
	Reaction to fire	
	Reaction to fire	NPD
	Loss of volume	NPD ≤45 %
	-	
	Loss of volume	≤45 %
	Loss of volume Resistance to flow	≤45 % ≤5 mm
	Loss of volume Resistance to flow	≤45 % ≤5 mm
	Loss of volume Resistance to flow	≤45 % ≤5 mm
	Loss of volume Resistance to flow	≤45 % ≤5 mm

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika[®] Stixall[®] Clear 13666060 2024/08, ver. 08 1213



1213

