

# SikaRapid® 1

# **DECLARATION OF CONFORMITY**

# No. 58254344

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	58254344
2	INTENDED USE/S	EN 934-2:2009 +A1:2012 Hardening accelerating admixture according to BS EN 934- 2 (Table 7)
3	MANUFACTURER:	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 934-2:2009 +A1:2012
	Approved body:	0120

SikaRapid® 1 58254344 2021.04, ver. 1 1088

### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification	
Chloride ion content	≤ 0.1% by weight	System 2+		
Alkali content	≤ 10.0% by weight	System 2+	<del></del>	
Compressive strength	At 20° C and 24 h: test mix ≥ 120 % of control mix; at 20° C and 28 days: test mix ≥ 90 % of control mix; at 5° C and 48 h: test mix ≥ 130 % of control mix	System 2+		
Air content in fresh concrete	Test mix ≤ 2 % by volume above control mix	System 2+	EN 934-2:2009 +A1:2012	
Corrosion behaviour	Contains the following components from EN 934-1 Annex A.2: Thiocyanates, nitrates	System 2+	_	
Dangerous substances	NPD	System 2+	<u> </u>	

### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anthony Smith Function: Product Manager At Sika Limited on 08 April 2021 Name: Martin Liska Function: R&D Manager At Sika Limited on 08 April 2021

End of information as required by UKCA





21

Sika Limited, Hertfordshire, United Kingdom

DoP No. 58254344

EN 934-2:2009 +A1:2012

Approved Body 0120

Hardening accelerating admixture according to BS EN 934-2 (Table 7)

Chloride ion content  $\leq 0.1\%$  by weight Alkali content  $\leq 10.0\%$  by weight

At 20° C and 24 h: test mix  $\geq$  120 % of control mix; Compressive strength at 20° C and 28 days: test mix  $\geq$  90 % of control mix;

at 5° C and 48 h: test mix ≥ 130 % of control mix

Air content in fresh concrete Test mix ≤ 2 % by volume above control mix

Contains the following components from EN 934-1

Annex A.2: Thiocyanates, nitrates

http://dop.sika.com

#### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### **LEGAL NOTE**

Corrosion behaviour

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



### Sika Limited

Watchmead Welwyn Garden City Hertfordshire United Kingdom www.sika.co.uk

**Declaration of Conformity** 

SikaRapid® 1 58254344 2021.04, ver. 1 1088

