

THE COMPLETE FAÇADE SOLUTION FIRE RATED SEALANT



FIRE RESISTANT SILICONE SEALANT FOR LINEAR SEALS IN WALLS AND FLOORS

Easy to use one component silicone the weather sealant for fireproof facades. It is also suitable in other industrial applications where good UV, thermal and fire resistance are required.

Features and Benefits

- Up to 4 hours fire resistance according to EN 1366-4
- Meeting relevant industry standards such as: ETA acc. EAD-350141-00-1106, EN 1366-4, EN 13501-2, BS 476-20, UL EU, UL 2079, Certifire, EN 10140-2, EN 15651-1, -4, ISO 11600 F 25 LM, ASTM C 920 class 25
- Excellent UV resistance
- Movement capability of ± 35% (ASTM C 719)
- Easy to smooth and very good workability
- Good adhesion to many different substrates
- Neutral curing



Sikasil®-670 Fire

Designed for fire rated movement and connection joints on porous and non-porous substrates



What can Sika UK offer?

- Local supply
- Technical support
- Independently tested
- Readily Available
- Colours Available in black and grey

MORE INFORMATION

Contact: Ali Aydogan | Mobile: : 07786 933402

Email: aydogan.ali@uk.sika.com www.sika.co.uk/facades

Connect with Ali on LinkedIn:

linkedin.com/in/ali-aydoğan-b567b91b8

Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.







SIKA LIMITED

Head Office Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ United Kingdom

Contact

Phone +441707394444 E-Mail enquiries@uk.sika.com www.sika.co.uk

SikaLimited



INDISCIPLATED SEALANT - SIKASII - 670 FIDE MAY 2022