

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaRoof® Primer-600 UK

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |   |
|--|---|
| Flammable liquids, Category 2  | H225: Highly flammable liquid and vapour.                   |
| Skin irritation, Category 2  | H315: Causes skin irritation.                               |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.                    |
| Short-term (acute) aquatic hazard, Category 1  | H400: Very toxic to aquatic life.                           |
| Long-term (chronic) aquatic hazard, Category 1                                       | H410: Very toxic to aquatic life with long lasting effects. |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758






## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

|                          |   |   |
|--------------------------|---|---|
| Hazard pictograms        | : |     |
| Signal word              | : | Danger  |
| Hazard statements        | : | H225 Highly flammable liquid and vapour.<br>H315 Causes skin irritation.<br>H336 May cause drowsiness or dizziness.<br>H410 Very toxic to aquatic life with long lasting effects.   |
| Precautionary statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P233 Keep container tightly closed.<br>P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.<br>P273 Avoid release to the environment.<br><b>Response:</b><br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.<br>P391 Collect spillage. |

### Hazardous components which must be listed on the label:

cyclohexane

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name   | CAS-No.<br>EC-No.<br>Registration number           | Classification  | Concentration<br>(% w/w) |
|---|--|---|--------------------------|
| cyclohexane   | 110-82-7<br>203-806-2<br>01-2119463273-41-XXXX     | Flam. Liq. 2; H225<br>Asp. Tox. 1; H304<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410   | >= 60 - < 80             |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Not Assigned<br>921-024-6<br>01-2119475514-35-XXXX | Flam. Liq. 2; H225<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411   | >= 25 - < 40             |
| ethyl acetate   | 141-78-6<br>205-500-4<br>01-2119475103-46-XXXX     | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>(Central nervous system)<br>EUH066   | >= 5 - < 10              |
| n-hexane  | 110-54-3<br>203-777-6<br>01-2119480412-44-XXXX     | Flam. Liq. 2; H225<br>Repr. 2; H361f<br>Asp. Tox. 1; H304<br>STOT RE 2; H373<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Aquatic Chronic 2;<br>H411<br><br>specific concentration limit<br>STOT RE 2; H373<br>>= 5 % | >= 0,25 - < 1            |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

|                                 |  |  |                   |
|---------------------------------|--|--|-------------------|
| zinc bis(dibenzylthiocarbamate) | 14726-36-4<br>238-778-0<br>01-2119543708-31-XXXX | Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><hr/> M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1 | $\geq 0,25 - < 1$ |
|---------------------------------|--|--|-------------------|

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Erythema  
Dermatitis  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
  
Causes skin irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components    | CAS-No.  | Value type (Form of exposure)   | Control parameters *               | Basis *     |
|---------------|----------|---|------------------------------------|-------------|
| cyclohexane   | 110-82-7 | TWA   | 200 ppm<br>700 mg/m <sup>3</sup>   | 2006/15/EC  |
|               |          | Further information: Indicative   |                                    |             |
|               |          | TWA   | 100 ppm<br>350 mg/m <sup>3</sup>   | GB EH40     |
|               |          | STEL  | 300 ppm<br>1.050 mg/m <sup>3</sup> | GB EH40     |
| ethyl acetate | 141-78-6 | STEL  | 400 ppm<br>1.468 mg/m <sup>3</sup> | 2017/164/EU |
|               |          | Further information: Indicative   |                                    |             |
|               |          | TWA   | 200 ppm<br>734 mg/m <sup>3</sup>   | 2017/164/EU |
|               |          | TWA   | 200 ppm<br>734 mg/m <sup>3</sup>   | GB EH40     |
|               |          | STEL  | 400 ppm<br>1.468 mg/m <sup>3</sup> | GB EH40     |
| n-hexane      | 110-54-3 | TWA   | 20 ppm<br>72 mg/m <sup>3</sup>     | 2006/15/EC  |
|               |          | Further information: Indicative   |                                    |             |
|               |          | TWA   | 20 ppm<br>72 mg/m <sup>3</sup>     | GB EH40     |
|               |          | Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. |                                    |             |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Colour : coloured
- Odour : characteristic
- Melting point/range / Freezing point : No data available
- Initial boiling point and boiling range : 62 - 100 °C
- Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : 7,4 %(V)



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

---

|   |   |                                    |
|---|---|------------------------------------|
| Lower explosion limit /<br>Lower flammability limit | : | 1,1 %(V)                           |
| Flash point   | : | ca. -35 °C<br>Method: closed cup   |
| Auto-ignition temperature                           | : | 427 °C                             |
| Decomposition temperature                           | : | No data available                  |
| pH  | : | No data available                  |
| <b>Viscosity</b>                                    |   |                                    |
| Viscosity, kinematic                                | : | > 20,5 mm <sup>2</sup> /s (40 °C)  |
| <b>Solubility(ies)</b>                              |   |                                    |
| Water solubility                                    | : | No data available                  |
| Partition coefficient: n-<br>octanol/water          | : | No data available                  |
| Vapour pressure                                     | : | 103,9912 hPa                       |
| Density   | : | ca. 0,84 g/cm <sup>3</sup> (20 °C) |
| Relative vapour density                             | : | No data available                  |
| Particle characteristics                            | : | No data available                  |

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

---

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l  
Exposure time: 96 h

#### **zinc bis(dibenzylthiocarbamate):**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1133  
IMDG : UN 1133  
IATA : UN 1133

### 14.2 UN proper shipping name

ADR : ADHESIVES  
IMDG : ADHESIVES  
IATA : Adhesives

### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

|             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADR</b>  | : 3   |                  |
| <b>IMDG</b> | : 3   |                  |
| <b>IATA</b> | : 3   |                  |

### 14.4 Packing group

|  |                     |  |
|--|---------------------|--|
| <b>ADR</b>                               |                     |  |
| Packing group                            | : II                |  |
| Classification Code                      | : F1                |  |
| Hazard Identification Number             | : 33                |  |
| Labels                                   | : 3                 |  |
| Tunnel restriction code                  | : (D/E)             |  |
| <b>IMDG</b>                              |                     |  |
| Packing group                            | : II                |  |
| Labels                                   | : 3                 |  |
| EmS Code                                 | : F-E, S-D          |  |
| <b>IATA (Cargo)</b>                      |                     |  |
| Packing instruction (cargo aircraft)     | : 364               |  |
| Packing instruction (LQ)                 | : Y341              |  |
| Packing group                            | : II                |  |
| Labels                                   | : Flammable Liquids |  |
| <b>IATA (Passenger)</b>                  |                     |  |
| Packing instruction (passenger aircraft) | : 353               |  |
| Packing instruction (LQ)                 | : Y341              |  |
| Packing group                            | : II                |  |
| Labels                                   | : Flammable Liquids |  |

### 14.5 Environmental hazards

|                           |       |  |
|---------------------------|-------|--|
| <b>ADR</b>                |       |  |
| Environmentally hazardous | : yes |  |
| <b>IMDG</b>               |       |  |
| Marine pollutant          | : yes |  |
| <b>IATA (Passenger)</b>   |       |  |
| Environmentally hazardous | : yes |  |
| <b>IATA (Cargo)</b>       |       |  |
| Environmentally hazardous | : yes |  |

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 99,5% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 99,5% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

|       |   |  |
|-------|---|--|
| H225  | : | Highly flammable liquid and vapour.                                |
| H304  | : | May be fatal if swallowed and enters airways.                      |
| H315  | : | Causes skin irritation.  |
| H319  | : | Causes serious eye irritation.                                     |
| H336  | : | May cause drowsiness or dizziness.                                 |
| H361f | : | Suspected of damaging fertility.                                   |
| H373  | : | May cause damage to organs through prolonged or repeated exposure. |
| H400  | : | Very toxic to aquatic life.  |
| H410  | : | Very toxic to aquatic life with long lasting effects.              |
| H411  | : | Toxic to aquatic life with long lasting effects.                   |

### Full text of other abbreviations

|                    |   |   |
|--------------------|---|---|
| Aquatic Acute      | : | Short-term (acute) aquatic hazard   |
| Aquatic Chronic    | : | Long-term (chronic) aquatic hazard  |
| Asp. Tox.          | : | Aspiration hazard   |
| Eye Irrit.         | : | Eye irritation  |
| Flam. Liq.         | : | Flammable liquids   |
| Repr.              | : | Reproductive toxicity   |
| Skin Irrit.        | : | Skin irritation   |
| STOT RE            | : | Specific target organ toxicity - repeated exposure  |
| STOT SE            | : | Specific target organ toxicity - single exposure  |
| 2006/15/EC         | : | Europe. Indicative occupational exposure limit values   |
| 2017/164/EU        | : | Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values                  |
| GB EH40            | : | UK. EH40 WEL - Workplace Exposure Limits  |
| 2006/15/EC / TWA   | : | Limit Value - eight hours   |
| 2017/164/EU / STEL | : | Short term exposure limit   |
| 2017/164/EU / TWA  | : | Limit Value - eight hours   |
| GB EH40 / TWA      | : | Long-term exposure limit (8-hour TWA reference period)  |
| GB EH40 / STEL     | : | Short-term exposure limit (15-minute reference period)  |
| ADR                | : | European Agreement concerning the International Carriage of Dangerous Goods by Road   |
| CAS                | : | Chemical Abstracts Service  |
| DNEL               | : | Derived no-effect level   |
| EC50               | : | Half maximal effective concentration  |
| GHS                | : | Globally Harmonized System  |
| IATA               | : | International Air Transport Association   |
| IMDG               | : | International Maritime Code for Dangerous Goods   |
| LD50               | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50               | : | Median lethal concentration (concentrations of the chemical in  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaRoof® Primer-600 UK

Date of last issue: 01.12.2023  
Revision Date: 21.12.2023

Version 3.0

Print Date 29.02.2024

|        |  |
|--------|--|
|        | air that kills 50% of the test animals during the observation period)  |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL    | : Occupational Exposure Limit  |
| PBT    | : Persistent, bioaccumulative and toxic  |
| PNEC   | : Predicted no effect concentration  |
| REACH  | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC   | : Substances of Very High Concern  |
| vPvB   | : Very persistent and very bioaccumulative   |

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 2      | H225 |
| Skin Irrit. 2     | H315 |
| STOT SE 3         | H336 |
| Aquatic Acute 1   | H400 |
| Aquatic Chronic 1 | H410 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

GB / EN