

# Everbuild Tecnic<sup>®</sup> Fire Sealant 400

## DECLARATION OF PERFORMANCE

### No. 89270107

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	89270107
2	<b>INTENDED USE/S</b>	Sealants for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for facade elements
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	Not applicable
5	<b>SYSTEM/S OF AVCP:</b>	3
6a	<b>HARMONISED STANDARD:</b>	EN 15651-1:2012
	Notified body/ies:	0074

#### Declaration of Performance

Everbuild Tecnic<sup>®</sup> Fire Sealant 400

89270107

2023/07, ver. 03

1213

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E		
Water tightness and air tightness		3	
Resistance to flow	≤ 3 mm	3	
Loss of volume	≤ 10 %	3	
Tensile properties – at maintained extension after water immersion	NF at 100 %	3	
Tensil properties – for non-structural low modulus sealants used in joints in cold climate areas (-30 °C)	≤ 0.9 N/mm <sup>2</sup>	3	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): - for non-structural sealants used in joints in cold climate areas (-30 °C)	NF at 100 %	3	
Durability	Pass	3	
Release of dangerous chemicals	See sds		

## 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas  
Function: Technical Product  
Coordinator  
At Leeds on 29 June 2023

Name : Alex West  
Function: Product Manager  
At Leeds on 08 February 2024



End of information as required by Regulation (EU) No 305/2011

### Declaration of Performance

Everbuild Tecnic® Fire Sealant 400  
89270107  
2023/07 , ver. 03  
1213



14

Sika Services AG, Zurich, Switzerland

DoC No. 89270107

EN 15651-1:2012

Notified Body 0074

Sealants for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for facade elements

Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	$\leq 3$ mm
Loss of volume	$\leq 10$ %
Tensile properties – at maintained extension after water immersion	NF at 100 %
Tensile properties – for non-structural low modulus sealants used in joints in cold climate areas (-30 °C)	$\leq 0.9$ N/mm <sup>2</sup>
Tensile properties (i.e. at maintained extension): - for non-structural sealants used in joints in cold climate areas (-30 °C)	NF at 100 %
Durability	Pass
Release of dangerous chemicals	See sds

[Declarations of Performance Downloads | Sika Limited](#)

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Everbuild Tecnic® Fire Sealant 400

89270107

2023/07, ver. 03

1213

**Declaration of Performance**

Everbuild Tecnic® Fire Sealant 400

89270107

2023/07 , ver. 03

1213

**4/4**

**BUILDING TRUST**

