

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaPower®-1200 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Hazard statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P261 P264 P273 P280	Avoid breathing mist or vapours. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
		Response: P333 + P313 P391	If skin irritation or rash occurs: Get medical advice/ attention. Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxy)phenyl]propane
Aliphatic Polyurethane Prepolymer, blocked
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
bis-[4-(2,3-epoxypropoxy)phenyl]methane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 40 - < 60
Aliphatic Polyurethane Prepolymer, blocked	1613260-86-8 Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 M-Factor (Chronic aquatic toxicity): 1	>= 25 - < 40
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	68413-24-1 500-210-7	Skin Sens. 1; H317	>= 5 - < 10
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Contains: methanol <= 0,2 %	2530-83-8 219-784-2 01-2119513212-58-XXXX	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	< 1
bis-[4-(2,3-epoxypropoxy)phenyl]methane	Not Assigned 701-263-0 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,025 - < 0,25

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area.

Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
------------	---------	-------------------------------	----------------------	---------

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m ³	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
		TWA	200 ppm 266 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	250 ppm 333 mg/m ³	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Appearance : paste
Colour : yellow
- Odour : characteristic
- Melting point/range / Freezing point : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,15 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Aliphatic Polyurethane Prepolymer, blocked:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Acute oral toxicity : LD50 Oral (Rat): 7.010 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal (Rabbit): 4.248 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxypropoxy)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates Exposure time: 48 h

Aliphatic Polyurethane Prepolymer, blocked:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Scenedesmus capricornutum (fresh water algae)): 11
plants mg/l
Exposure time: 72 h

M-Factor (Chronic aquatic : 1
toxicity)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l
Exposure time: 96 h

bis-[4-(2,3-epoxypropoxy)phenyl]methane:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 2,55 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (algae): 1,8 mg/l
plants Exposure time: 72 h

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3077

IMDG : UN 3077

IATA : UN 3077

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(epoxy resin)

IATA : Environmentally hazardous substance, solid, n.o.s., Environmentally hazardous substance, solid, n.o.s.
(epoxy resin)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 9	
IMDG	: 9	
IATA	: 9	

14.4 Packing group

ADR
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)
Packing instruction (cargo aircraft) : 956

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

International Chemical Weapons Convention (CWC)
Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

Control of Major Accident Hazards Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
2006/15/EC : Europe. Indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2006/15/EC / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-1200 Part A

Date of last issue: 04.01.2023
Revision Date: 11.12.2023

Version 4.0

Print Date 29.02.2024

EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GB / EN