

BUILDING TRUST

Sikadur Combiflex[®] CF Adhesive Normal DECLARATION OF PERFORMANCE No. 72789209

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	72789209	
2	INTENDED USE/S	EN 1504-4:2004 Structural bonding products for bonded mortar or concrete for use in buildings and civil engineering works	
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich	
4	AUTHORISED REPRESENTATIVE:		
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire	
6a	HARMONISED STANDARD:	EN 1504-4:2004	
	Notified body/ies:	0921, 0767	

Declaration of Performance Sikadur Combiflex® CF Adhesive Normal 72789209 2018.04 , ver. 2 1001 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bond/adhesion strength (concrete failure)	Pass	System 2+	
Shear adhesion	≥ 6 N/mm ²	System 2+	
Compressive strength	≥ 30 N/mm ²	System 2+	
Shrinkage/expansion	≤ 0.1 %	System 2+	
Workability	110 min at 23 °C	System 2+	 EN 1504-
Sensitivity to water	Pass	System 2+	4:2004
Modulus of elasticity	≥ 2000 N/mm ²	System 2+	
Coefficient of thermal expansion	≤ 100 × 10 ⁻⁶ per K	System 2+	
Glass transition temperature	≥ 40 °C	System 2+	
Reaction to fire	Class E	System 3	
Durability	Pass	System 2+	
Dangerous Substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tom Forsyth Function: TM Manager – Concrete and Waterproofing At Welwyn Garden City on 25 June 2018 Name : Alex Burman Function: Product Manager - Waterproofing At Welwyn Garden City on 25 June 2018

T.A.Forsyth

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikadur Combiflex [®] CF Adhesive Normal	EN 1504-4:2004	020703020030000021001

Declaration of Performance

Sikadur Combiflex[®] CF Adhesive Normal 72789209 2018.04 , ver. 2 1001



CE

Sika Services AG, Zurich, Switzerland

DoP No. 72789209

EN 1504-4:2004

Notified Body 0921, 0767

Structural bonding products for bonded mortar or concrete for use in buildings and civil engineering works

Bond/adhesion strength (concrete failure)	Pass
Shear adhesion	≥ 6 N/mm2
Compressive strength	≥ 30 N/mm2
Shrinkage/expansion	≤ 0.1 %
Workability	110 min at 23 °C
Sensitivity to water	Pass
Modulus of elasticity	≥ 2000 N/mm2
Coefficient of thermal expansion	≤ 100 × 10–6 per K
Glass transition temperature	≥ 40 °C
Reaction to fire	Class E
Durability	Pass
Dangerous Substances NPD	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikadur Combiflex® CF Adhesive Normal 72789209 2018.04 , ver. 2 1001



BUILDING TRUST

Sika Ltd Watchmead AL7 1BQ United Kingdom www.sika.co.uk

Declaration of Performance

Sikadur Combiflex® CF Adhesive Normal 72789209 2018.04 , ver. 2 1001



BUILDING TRUST