
# Safety Data Sheet





### **IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF** 1. THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikafloor®-305 W Part A

**Use of the substance/preparation**: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444 Fax no. : 01707 329129 e-mail address of person

responsible for this SDS

: EHS@uk.sika.com

**Emergency telephone number** : +44 (0)1707 363899 (available during office hours).

#### 2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

See section 11 for more detailed information on health effects and symptoms.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Aqueous acrylate dispersion

Characteristics

#### 4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention if symptoms occur.

: Do not induce vomiting unless directed to do so by medical personnel. Maintain an Ingestion

open airway. Seek immediate medical attention.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower Eye contact

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

: No specific treatment. Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

#### 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

: In a fire or if heated, a pressure increase will occur and the container may burst. Special exposure hazards

: 27.11.2009. Date of issue **MSDS no.** : 604278 1/5 Sikafloor®-305 W Part A 27.11.2009 2/5

# 5. FIRE-FIGHTING MEASURES

Hazardous combustion products

 Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8).

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

### 7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

**Storage** 

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**Packaging materials** 

**Recommended**: Use original container.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure limit values**

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

### **Exposure controls**

**Date of issue** : **27.11.2009**. **MSDS no.** : 604278 **2/5** 

Sikafloor®-305 W Part A 27.11.2009 3/5

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

Hand protection

No special measures required.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates

this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

**Eye protection** Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists,

gases or dusts.

**Skin protection**: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before

handling this product. Recommended: Use barrier skin cream.

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### **General information**

**Appearance** 

Form : Liquid.

Colour : Pale colour.

Odour : Characteristic.

Important health, safety and environmental information

**pH** : 8 to 9

**Density** :  $\sim 1.05 \text{ g/cm}^3 [20^{\circ}\text{C } (68^{\circ}\text{F})]$ 

# 10. STABILITY AND REACTIVITY

Stability: The product is stable.Conditions to avoid: No specific data.Materials to avoid: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# 11. TOXICOLOGICAL INFORMATION

### Potential acute health effects

**Inhalation** : May cause irritation.

**Ingestion** : Can cause gastrointestinal disturbances.

**Skin contact** : May cause skin irritation. **Eye contact** : May cause eye irritation.

**Chronic effects**: No known significant effects or critical hazards.

Date of issue : 27.11.2009. MSDS no. : 604278 3/5

Sikafloor®-305 W Part A 27.11.2009 4/5

### 12. ECOLOGICAL INFORMATION

**Environmental effects** 

: Avoid contact of spilt material and runoff with soil and surface waterways. Do not empty into drains; dispose of this material and its container in a safe way.

# 13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC)

: 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Packaging** 

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and

regulations.

### 14. TRANSPORT INFORMATION

### **International transport regulations**

**ADR** 

Not regulated.

**IMDG** 

Not regulated.

Marine pollutant : №

**IATA** 

Not regulated.

# 15. REGULATORY INFORMATION

### **EU** regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

**Classification**: This product is not classified according to EU legislation.

**VOC content (EU)** : VOC (w/w): 5.24%

National regulations

**Regulatory information**: Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

3)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

Date of issue : 27.11.2009. MSDS no. : 604278 4/5

Sikafloor®-305 W Part A 27.11.2009 5/5

# 15. REGULATORY INFORMATION

# 16. OTHER INFORMATION

### **History**

Date of printing : 27.11.2009.

Date of issue : 27.11.2009.

Date of previous issue : 11.11.2009.

Indicates information that has changed from previously issued version.

### **Notice to reader**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

**Date of issue** : **27.11.2009**. **MSDS no**. : 604278 **5/5** 

# **Safety Data Sheet**



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikafloor 305W Part B

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444 : 01707 329129 Fax no. e-mail address of person

responsible for this SDS

: EHS@uk.sika.com

**Emergency telephone number** 

: +44 (0)1707 363899 (available during office hours).

#### 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R43

R52/53

**Human health hazards** : May cause sensitisation by skin contact.

**Environmental hazards** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient name	CAS number	%	EC number	Classification	
hexamethylenediisocyanate homopolymer	28182-81-2	>=90		R43 R52/53	[1]
Poly(oxy-1,2-ethanediyl), .alphatridecylomegahydroxy-, phosphate	9046-01-9	2.5-5		Xi; R41, R38 N; R51/53	[1]
hexamethylene-di-isocyanate	822-06-0	<0.5	212-485-8	T; R23 Xi; R36/37/38 R42/43	[1] [2]
See section 16 for the full text of the R-phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

: 27.11.2009. Date of issue **MSDS no.** : 604186 1/6 Sikafloor 305W Part B 27.11.2009 2/6

# 4. FIRST AID MEASURES

### First-aid measures

**Inhalation**: Get medical attention if adverse health effects persist or are severe.

**Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

evelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

# 5. FIRE-FIGHTING MEASURES

### **Extinguishing media**

**Suitable**: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

carbon dioxide

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions**: Keep unnecessary and unprotected personnel from entering. Do not touch or walk

through spilt material. Put on appropriate personal protective equipment (see section

8).

**Environmental precautions**: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air). Water polluting material.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers,

water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth

and place in container for disposal according to local regulations (see section 13).

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert

material and place in an appropriate waste disposal container.

# 7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Date of issue : 27.11.2009. MSDS no. : 604186 2/6

Sikafloor 305W Part B 27.11.2009 3/6

## 7. HANDLING AND STORAGE

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**Packaging materials** 

**Recommended**: Use original container.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure limit values**

hexamethylenediisocyanate homopolymer

EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitiser.

STEL: 0.07 mg/m³, (as NCO) 15 minute(s).
TWA: 0.02 mg/m³, (as NCO) 8 hour(s).

EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitiser.

Notes: as NCO
STEL: 0.07 mg/m³, (as NCO) 15 minute(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

TWA: 0.02 mg/m³, (as NCO) 8 hour(s).

### **Exposure controls**

Occupational exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapour filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

**Environmental exposure controls** 

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue : 27.11.2009. MSDS no. : 604186 3/6

Sikafloor 305W Part B 27.11.2009 4/6

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### **General information**

**Appearance** 

Form : Liquid.

**Colour** : Colourless to light yellow.

Odour : Odourless.

Important health, safety and environmental information

**Boiling point** :  $>150^{\circ}$ C ( $>302^{\circ}$ F)

Flash point : Closed cup: >93.3°C (>199.9°F)

Density : ~1.13 g/cm³ [25°C (77°F)]

## 10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# 11. TOXICOLOGICAL INFORMATION

### Potential acute health effects

**Inhalation** : May cause irritation.

Ingestion: Can cause gastrointestinal disturbances.Skin contact: May cause sensitisation by skin contact.

**Eye contact** : May cause eye irritation.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

regulations.

### 12. ECOLOGICAL INFORMATION

**Environmental effects** 

 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue

(EWC)

: 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Packaging** 

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and

Date of issue : 27.11.2009. MSDS no. : 604186 4/6

Sikafloor 305W Part B 27.11.2009 5/6

# 13. DISPOSAL CONSIDERATIONS

15 01 10\* packaging containing residues of or contaminated by dangerous substances

### 14. TRANSPORT INFORMATION

### **International transport regulations**

<u>ADR</u>

Not regulated.

Proper shipping name

-- -

<u>IMDG</u>

Not regulated.

Marine pollutant : No

<u>IATA</u>

Not regulated.

# 15. REGULATORY INFORMATION

### **EU regulations**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi

Irritant

Contains : hexamethylenediisocyanate homopolymer Risk phrases : R43- May cause sensitisation by skin contact.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S37- Wear suitable gloves.

Additional warning phrases

: Contains isocyanates. See information supplied by the manufacturer.

VOC content (EU) : VOC (w/w): 0%

**National regulations** 

**Regulatory information**: Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

3)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Workplace Exposure Limits, HSE (as updated).

HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

Date of issue : 27.11.2009. MSDS no. : 604186 5/6

Sikafloor 305W Part B 27.11.2009 6/6

# 16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R23- Toxic by inhalation.

R41- Risk of serious damage to eyes.

R38- Irritating to skin.

R36/37/38- Irritating to eyes, respiratory system and skin.

R43- May cause sensitisation by skin contact.

R42/43- May cause sensitisation by inhalation and skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: T - Toxic Xi - Irritant

N - Dangerous for the environment

### **History**

Date of printing : 27.11.2009.

Date of issue : 27.11.2009.

Date of previous issue : No previous validation.

 ${f {\Bbb Z}}$  Indicates information that has changed from previously issued version.

### **Notice to reader**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 27.11.2009. MSDS no. : 604186 6/6