

Sikacrete[®]-301 Premium

DECLARATION OF PERFORMANCE No. 61362

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	61362
2	INTENDED USE/S	For uses in buildings and civil engineering works- Structural and non-structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete. For uses subject to reaction to fire regulations.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	SYSTEM/S OF AVCP:	System 2+ System 3
6a	HARMONISED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1180

INTERNAL

Declaration of Performance
Sikacrete[®]-301 Premium
61362
2024, ver. 1
212254

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive strength	≥ 45 MPa	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0,05 %	System 2+	
Adhesive bond	≥ 2,0 MPa	System 2+	
Carbonation resistance	Pass	System 2+	
Elastic modulus	≥ 20 GPa	System 2+	
Coefficient of thermal expansion	~ 8 x 10 ⁻⁶ m/m °C	System 2+	
Capillary absorption	≤ 0,5 kg·m ⁻² ·h ^{-0,5}	System 2+	
Reaction to fire	Class F	System 3	
Release of dangerous substances	NPD	System 2+	
Restrained shrinkage/expansion	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Rob Doherty
Function: Senior Product Manager
At Welwyn Garden City on 19
December 2024

Name: Martin Liska
Function: Head of R&D: Concrete and
Cementitious Systems
At Welwyn Garden City
on 19 December 2024

R. Doherty

Martin Liska

End of information as required by Regulation (EU) No 305/2011

INTERNAL

Declaration of Performance
Sikacrete®-301 Premium
61362
2024, ver. 1
212254



24

Sika Services AG, Zurich, Switzerland

61362

Compressive strength	$\geq 45 \text{ MPa}$
Chloride ion content	$\leq 0,05 \%$
Adhesive bond	$\geq 2,0 \text{ MPa}$
Carbonation resistance	Pass
Elastic modulus	$\geq 20 \text{ GPa}$
Capillary absorption	$\leq 0,5 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0,5}$
Reaction to fire	Class F
Coefficient of thermal expansion	$\sim 8 \times 10^{-6} \text{ m/m } ^\circ\text{C}$

EN 1504-3:2005

1180

For uses in buildings and civil engineering works- Structural and non-structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete.

For uses subject to reaction to fire regulations.

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

INTERNAL

Declaration of Performance

Sikacrete®-301 Premium

61362

2024, ver. 1

212254

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

INTERNAL

Declaration of Performance
Sikacrete®-301 Premium
61362
2024, ver. 1
212254

