

Version 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

Trade name

: SCHÖNOX<sup>®</sup> HS 10

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Gypsum product, Floor levelling compound

# 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

# 1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	72/2008)
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.

### 2.2 Label elements

Labelling (REGULATION ( Hazard pictograms	( <b>EC)</b> :	No 1272/2008)	
Signal word	:	Danger	
Hazard statements	:	H315 H318	Causes skin irritation. Causes serious eye damage.
Precautionary statements	:	P101 P102 P103	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.



Revision Date 15.02.2019

Version 1.0

Prevention: P264

P280

Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

• Cement (chromium reduced)

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

# 3.2 Mixtures

# Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Cement (chromium reduced)	65997-15-1 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 10 - < 20
Substances with a workplace expo	sure limit :		
Quartz (SiO2)	14808-60-7 238-878-4		>= 25 - < 40
Limestone Contains: Quartz (SiO2) <5µm >= 0,1 %	1317-65-3 215-279-6		>= 5 - < 10

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.	
Augusta CD 40000047000			



Revision Date 15.02.2019		Version 1.0	Print Date 15.02
In case of skin contact	:	Take off contaminated clothing and shoes im Wash off with soap and plenty of water. If symptoms persist, call a physician.	mediately.
In case of eye contact	:	Small amounts splashed into eyes can cause sue damage and blindness. In the case of contact with eyes, rinse immed of water and seek medical advice. Continue rinsing eyes during transport to hos Remove contact lenses.	iately with plenty
If swallowed	:	Keep eye wide open while rinsing. Do not induce vomiting without medical advic Rinse mouth with water.	e.
		Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsci	ous person.
4.2 Most important symptoms a	nd	effects, both acute and delayed	
Symptoms	:	Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information and symptoms.	on health effects
Risks	:	irritant effects	
		Causes skin irritation. Causes serious eye damage.	
4.3 Indication of any immediate	me	dical attention and special treatment needed	d
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	asur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water je ide/sand/foam/alcohol resistant foam/chemica extinction.	
5.2 Special hazards arising from	n the	e substance or mixture	
Hazardous combustion prod- ucts	- :	No hazardous combustion products are know	'n
5.3 Advice for firefighters			
Special protective equipment for firefighters	t :	In the event of fire, wear self-contained breat	hing apparatus.
Further information	:	Standard procedure for chemical fires.	
Country GB 100000017328			3 / 14



\_\_\_\_\_

Revision Date 15.02.2019

Version 1.0

<b>SECTION 6: Accidental releas</b>	se measures
6.1 Personal precautions, protect	ctive equipment and emergency procedures
Personal precautions	: Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions	: Try to prevent the material from entering drains or water courses.
6.3 Methods and material for co	ntainment and cleaning up
Methods for cleaning up	: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	
For personal protection see s	ection 8.
SECTION 7: Handling and sto	orage
7.1 Precautions for safe handlin	g
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see

	Advice on safe handling :	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, incl	uding any incompatibilities
	Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- : age stability	Keep in a dry place. No decomposition if stored and applied as directed.



Version 1.0

# 7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
Further information	Carcinogens or	mutagens		
	Ť	TWA (Respirable dust)	0,1 mg/m3 (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory material are given in MDHS14/3, Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Cement (chromium reduced)	65997-15-1	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable are inhalable dust, The COSHH definition of a substance hazardous to hea includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8 hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' a		nen sampling is MDHS14/3 of respirable and zardous to health n in air equal to or 4 mg.m-3 8- rill be subject to e dusts have st comply with les of a wide particular parti- body response e. HSE distin-	



Revision Date 15.02.2019	Version 1.0	Print Date 15.02.2019
	'respirable'., Inhalable dust approxim rial that enters the nose and mouth d available for deposition in the respira mates to the fraction that penetrates lung. Fuller definitions and explanato Where dusts contain components that the relevant limits should be complied exposure limit is listed, a figure three should be used	luring breathing and is therefore tory tract. Respirable dust approxi- to the gas exchange region of the ory material are given in MDHS14/3., at have their own assigned WEL, all d with., Where no specific short-term
	TWA (Respirable dust)	4 mg/m3 GB EH40
Further information	For the purposes of these limits, resp those fractions of airborne dust which undertaken in accordance with the m General methods for sampling and g inhalable dust, The COSHH definition includes dust of any kind when prese or greater than 10 mg.m-3 8-hour TV hour TWA of respirable dust. This me COSHH if people are exposed above been assigned specific WELs and ex the appropriate limit., Most industrial range of sizes. The behaviour, depos cle after entry into the human respira that it elicits, depend on the nature a	n will be collected when sampling is nethods described in MDHS14/3 ravimetric analysis of respirable and n of a substance hazardous to health ent at a concentration in air equal to VA of inhalable dust or 4 mg.m-3 8- eans that any dust will be subject to the these levels. Some dusts have coosure to these must comply with dusts contain particles of a wide sition and fate of any particular parti- tory system and the body response nd size of the particle. HSE distin- titing purposes termed 'inhalable' and ates to the fraction of airborne mate- luring breathing and is therefore tory tract. Respirable dust approxi- to the gas exchange region of the my material are given in MDHS14/3., at have their own assigned WEL, all d with., Where no specific short-term
Limestone	1317-65-3 TWA (inhalable dust)	10 mg/m3 GB EH40
Further information	For the purposes of these limits, resp those fractions of airborne dust which undertaken in accordance with the m General methods for sampling and g inhalable dust, The COSHH definition includes dust of any kind when prese or greater than 10 mg.m-3 8-hour TV hour TWA of respirable dust. This me COSHH if people are exposed above been assigned specific WELs and ex the appropriate limit., Most industrial range of sizes. The behaviour, depos cle after entry into the human respira that it elicits, depend on the nature a	n will be collected when sampling is nethods described in MDHS14/3 ravimetric analysis of respirable and n of a substance hazardous to health ent at a concentration in air equal to VA of inhalable dust or 4 mg.m-3 8- eans that any dust will be subject to the these levels. Some dusts have coosure to these must comply with dusts contain particles of a wide sition and fate of any particular parti- tory system and the body response nd size of the particle. HSE distin- titing purposes termed 'inhalable' and ates to the fraction of airborne mate- luring breathing and is therefore tory tract. Respirable dust approxi- to the gas exchange region of the my material are given in MDHS14/3., at have their own assigned WEL, all d with., Where no specific short-term



Revision Date 15.02.2019

Version 1.0

	should be used			
		TWA (Respirable dust)	4 mg/m3	GB EH40
*The choice montioned values are in co	those fractions of undertaken in ac General method inhalable dust, T includes dust of or greater than 1 hour TWA of res COSHH if people been assigned s the appropriate I range of sizes. T cle after entry int that it elicits, dep guishes two size 'respirable'., Inha rial that enters th available for dep mates to the frac lung. Fuller defin Where dusts cor the relevant limit exposure limit is should be used	s of these limits, respi f airborne dust which cordance with the me s for sampling and gr he COSHH definition any kind when preser 0 mg.m-3 8-hour TW pirable dust. This me e are exposed above pecific WELs and exp imit., Most industrial of he behaviour, deposi to the human respirat bend on the nature an fractions for limit-set alable dust approxima to not a proxima to not a proximation osition in the respirat tions and explanator itain components that s should be complied listed, a figure three	will be collected wh ethods described in avimetric analysis of of a substance haz nt at a concentration A of inhalable dust of ans that any dust wi these levels. Some bosure to these mus dusts contain particle tition and fate of any ory system and the ad size of the particle ting purposes terme ates to the fraction of uring breathing and ory tract. Respirable o the gas exchange y material are given t have their own assist with., Where no sp times the long-term	en sampling is MDHS14/3 f respirable and ardous to health in air equal to or 4 mg.m-3 8- ill be subject to dusts have it comply with es of a wide particular parti- body response e. HSE distin- ed 'inhalable' and f airborne mate- is therefore e dust approxi- region of the in MDHS14/3., igned WEL, all ecific short-term exposure

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

# general dust value

Form of exposure	Value type	Control parameters	Basis	
Inhalable	TWA	10 mg/m3	GB EH40	
Respirable	TWA	4 mg/m3	GB EH40	

# 8.2 Exposure controls

# Personal protective equipment

Eye protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.
Skin and body protection	Dust impervious protective suit Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.

Revision Date 15.02.2019



Respiratory protection	<ul> <li>Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. particulate filter P</li> <li>P1: Inert material; P2, P3: hazardous substances</li> <li>Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.</li> </ul>
Environmental exposure of	controls
General advice	: Try to prevent the material from entering drains or water courses.

Version 1.0

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance	:	powder
Colour	:	white
Odour	:	odourless
Odour Threshold	:	No data available
рН	:	not determined
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available



Revision Date 15.02.2019		Version 1.0	Print Date 15.02.201
Density	:	ca. 1,13 g/cm3 (20 °C)	
Solubility(ies) Water solubility	:	No data available	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	Not applicable	
Explosive properties	:	No data available	
Oxidizing properties	:	No data available	

# 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

# 10.4 Conditions to avoid

### 10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Version 1.0

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### Acute toxicity

Not classified based on available information.

# Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Causes serious eye damage.

# Respiratory or skin sensitisation

### Skin sensitisation

Not classified based on available information.

# Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

# STOT - repeated exposure

Not classified based on available information.

# Aspiration toxicity

Not classified based on available information.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

No data available

# 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available



# Revision Date 15.02.2019 Version 1.0 Print Date 15.02.2 12.5 Results of PBT and vPvB assessment Product: Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. 12.6 Other adverse effects Product: Additional ecological information : There is no data available for this product.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

# **SECTION 14: Transport information**

# 14.1 UN number

Not regulated as a dangerous good

# 14.2 UN proper shipping name

Not regulated as a dangerous good

# 14.3 Transport hazard class(es)

Not regulated as a dangerous good

# 14.4 Packing group

Not regulated as a dangerous good

# 14.5 Environmental hazards

Not regulated as a dangerous good

Country GB 100000017328



Version 1.0

# 14.6 Special precautions for user

Not applicable

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

<b>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b> International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors								
REACH - Candidate List of Su Concern for Authorisation (Art			None of the components are listed (=> 0.1 %).					
REACH - List of substances s (Annex XIV)	ubject to authorisation	:	Not applicable					
Regulation (EC) No 1005/2009 plete the ozone layer	on substances that de-	:	Not applicable					
Regulation (EC) No 850/2004 lutants	on persistent organic pol-	:	Not applicable					
Regulation (EC) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals								
REACH - Restrictions on the r the market and use of certain preparations and articles (Ann	dangerous substances,		Conditions of restriction for the fol- lowing entries should be considered: Cement (chromium reduced) (Number on list 47)					
REACH Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.								
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable								
Volatile organic compounds	Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0,01 % no VOC duties							
Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content:								



Revision Date 15.02.2019

Version 1.0

< 0,01 %, 0 g/l VOC content excluding water

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:  Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)
 May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

# Other regulations:

This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

# 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

Full text of H-Statements		
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H335	:	May cause respiratory irritation.
Full text of other abbreviation	ons	
Eye Dam.	:	Serious eye damage
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers
		from the risks related to exposure to carcinogens or mutagens
		at work
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2004/37/EC / TWA	:	Long term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	-	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in



Revision Date 15.02.2019		Version 1.0	Print Date 15.02
	air that kills period)	50% of the test animals duri	ng the observation
MARPOL		al Convention for the Prevent as modified by the Protocol	
OEL		al Exposure Limit	
PBT	: Persistent,	bioaccumulative and toxic	
PNEC	: Predicted n	o effect concentration	
REACH	and of the ( istration, Ev	(EC) No 1907/2006 of the Eu Council of 18 December 2006 valuation, Authorisation and F H), establishing a European	o concerning the Reg- Restriction of Chemi-
SVHC		s of Very High Concern	
vPvB	: Very persis	tent and very bioaccumulativ	е
Further information			
Classification of the mixtu	re:	Classification	procedure:
Skin Irrit. 2	H315	Calculation met	thod
Eye Dam. 1	H318	Calculation met	thod

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN