

PRODUCT DATA SHEET

EVERBUILD® FINE SURFACE FILLER

A ready mixed filler for filling small holes and surface imperfections

PRODUCT DESCRIPTION

EVERBUILD® FINE SURFACE FILLER is an easy to use ready mixed filler for filling small holes and surface imperfections in most porous surfaces such as plaster and wood. Dries to a very smooth finish that can be painted or papered.

USES

Minor indoor or outdoor repairs to plaster, plaster-board, brick, render, wood, stone and most other building materials.

CHARACTERISTICS / ADVANTAGES

- Interior or exterior use
- Ready mixed formula – apply straight from tub
- Overpaintable with most solvent based and emulsion paints
- Overstainable

Movement Accommodation Low – Dries hard

Maximum Fill 4mm depth in one coat

Maximum Width 25mm

Application Temperature 5°C to 30°C.

pH 8.5-9.9

PRODUCT INFORMATION

Packaging	600g Plastic Tub
Appearance / Colour	White / Off White Paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store at 5°C - 25°C. Protect from frost.
Density	1.9 g/cm ³ (approx)
Solid Content	85 -90% w/w

APPLICATION INFORMATION

Drying time 30mins - 4 hours depending on depth and temperature

APPLICATION INSTRUCTIONS**SUBSTRATE QUALITY / PRE-TREATMENT**

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

APPLICATION

Stir well before use and apply direct from tub. Press the filler into the repair with a spreader or knife up to a maximum depth of 4mm. Once dry, sand to a smooth finish. When used outdoors, seal the repair with an oil based paint once dry.

CLEANING OF TOOLS

All tools should be cleaned immediately after use with warm water.

LIMITATIONS

- For fine surface holes only. Do not apply more than 4mm deep.
- Not suitable for repairs to permanently wet areas. Do not use to repair plastics or metals.
- Do not apply or allow to dry below 5°C.
- Drying time will be approximately 30 mins to 1 hour at 20°C. This will increase substantially with increased depth, lower temperatures or when used externally.
- As the manufacturer cannot know all the uses their products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited