

Date of last issue: 01.12.2023	Version 6.3	Print Date 29.02.2024
Revision Date: 18.12.2023		

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sarnafil T Clean

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cleaning agent, For professional users only.

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone Telefax E mail address of person	:	+44 (0)1707 394444 +44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	١	/ersion 6.3	Print Date 29.02.2024
Long-term (chronic) aquatic ha egory 3	zard, Cat- H41 fect	12: Harmful to aquatic life with s.	long lasting ef-
2.2 Label elements			
Labelling (REGULATION (EC	) No 1272/2008)		
Hazard pictograms :			
Signal word :	Danger		
Hazard statements :	H226 H304 H312 + H332 H315 H319 H335 H373 H412	Flammable liquid and vapou May be fatal if swallowed an Harmful in contact with skin Causes skin irritation. Causes serious eye irritation May cause respiratory irritat May cause damage to organ longed or repeated exposur Harmful to aquatic life with li- fects.	nd enters airways. or if inhaled. n. ion. ns through pro- e if inhaled.
Precautionary statements :	Prevention:		
	P210 P260 P264	Keep away from heat, hot so open flames and other igniti smoking. Do not breathe mist or vapo Wash skin thoroughly after l	on sources. No urs.
	Response:		······································
	P301 + P310	IF SWALLOWED: Immediat	ely call a
	P331 P370 + P378	POISON CENTER/ doctor. Do NOT induce vomiting. In case of fire: Use dry sand alcohol-resistant foam to ex	

## Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene

#### **Additional Labelling**

The data sheet for medical personnel is available at the here provided emergency address.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 01.12.2023	Version 6.3	Print Date 29.02.2024
Revision Date: 18.12.2023		

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

## Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>=80
1-methoxy-2-propanol	107-98-2	Flam. Liq. 3; H226	>= 10 - < 20
Contains:	203-539-1	STOT SE 3; H336	
2-methoxypropanol <= 0,3 %	01-2119457435-35- XXXX	(Central nervous system)	

For explanation of abbreviations see section 16.

:

according to Detergents Regulation EC 648/2004 : 30 % and more: Aromatic hydrocarbons

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.



te of last issue: 01.12.2023 vision Date: 18.12.2023		Version 6.3	Print Date 29.02.202
If inhaled		Move to fresh air. Consult a physician after significant expo	osure.
In case of skin contact	1	Take off contaminated clothing and shoe Wash off with soap and plenty of water. f symptoms persist, call a physician.	es immediately.
In case of eye contact		mmediately flush eye(s) with plenty of w Remove contact lenses. Keep eye wide open while rinsing. f eye irritation persists, consult a specia	
If swallowed		Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unc	
2 Most important symptoms Symptoms	: /	<b>ects, both acute and delayed</b> Aspiration may cause pulmonary oedem Cough Respiratory disorder Excessive lachrymation	na and pneumonitis.
		Erythema Headache Dermatitis Skin disorders See Section 11 for more detailed informa and symptoms.	ation on health effects
Risks	:   ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	Erythema Headache Dermatitis Skin disorders See Section 11 for more detailed informa	aspiration). ways.

## **SECTION 5: Firefighting measures**

5.1	Extin	guishing	media
-----	-------	----------	-------

Suitable extinguishing media :

Alcohol-resistant foam Carbon dioxide (CO2)



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	Print Date 29.02.2024
	Dry chemical	
Unsuitable extinguishing : media	Water High volume water jet	
5.2 Special hazards arising from th	e substance or mixture	
Specific hazards during fire- : fighting	Do not use a solid water stream as it may scatt fire.	er and spread
Hazardous combustion prod- : ucts	No hazardous combustion products are known	
5.3 Advice for firefighters		
Special protective equipment : for firefighters	In the event of fire, wear self-contained breathin	ng apparatus.
Further information :	Use water spray to cool unopened containers.	
SECTION 6: Accidental release	measures	
6.1 Personal precautions, protectiv	e equipment and emergency procedures	
Personal precautions :	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explos tions. Vapours can accumulate in low areas.	sive concentra-
6.2 Environmental precautions		
Environmental precautions :	Prevent product from entering drains.	

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling



Date of last issue: 01.12.2023 Revision Date: 18.12.2023		Version 6.3	Print Date 29.02.2024
Advice on safe handling	:	Avoid exceeding the given occupational exp section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prof plication area. Take precautionary measures against static Provide sufficient air exchange and/or exhat Open drum carefully as content may be und Take necessary action to avoid static electric (which might cause ignition of organic vapou Follow standard hygiene measures when ha products	nibited in the ap- discharge. ust in work rooms. er pressure. city discharge urs).
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away open flames/ hot surfaces. No smoking. Tak measures against electrostatic discharges.	
Hygiene measures	:	Handle in accordance with good industrial hy practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the	nen using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and we place. Containers which are opened must be sealed and kept upright to prevent leakage. ance with local regulations.	e carefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as d	irected.
7.3 Specific end use(s) Specific use(s)	:	Consult most current local Product Data She use.	eet prior to any

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further informative through the ski	ation: Identifies the in, Indicative	possibility of signi	ficant uptake
		STEL	100 ppm 442 mg/m3	2000/39/EC



Date of last issue: 01.12.2023	Version 6.3	Print Date 29.02.2024
Revision Date: 18.12.2023		

		TWA	50 ppm 220 mg/m3	GB EH40		
			bsorbed through the			
	signed substa	signed substances are those for which there are concerns that				
	dermal absor	dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm 441 mg/m3	GB EH40		
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
		STEL	150 ppm 568 mg/m3	2000/39/EC		
		TWA	100 ppm 375 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The as-					
	signed substances are those for which there are concerns that					
	dermal absor	dermal absorption will lead to systemic toxicity.				
		STEL	150 ppm 560 mg/m3	GB EH40		

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### **Biological occupational exposure limits**

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	methyl hippuric acid: 650 Millimo- les per mole cre- atinine (Urine)	After shift	GB EH40 BAT

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	<ul> <li>Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.</li> <li>Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (&gt; 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm),</li> </ul>
	breakthrough time >30 min.



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	Print Date 29.02.2024
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. long-sleeved working clothing, long trouser and protective boots are additionaly recom and stirring work.	rs). Rubber aprons
Respiratory protection :	In case of inadequate ventilation wear resp Respirator selection must be based on kno exposure levels, the hazards of the produc- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10 Ensure adequate ventilation. This can be a exhaust extraction or by general ventilation ods for determining inhalation exposure). T ticular to the mixing / stirring area. In case to keep the concentrations under the occup limits then respiration protection measures Ensure adequate ventilation, especially in o	own or anticipated and the safe work- 0000 ppm achieved by local h. (EN 689 - Meth- This applies in par- this is not sufficent pational exposure must be used.
Environmental exposure cont	ols	

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid translucent		
Odour	:	solvent-like		
Melting point/range / Freezing point	:	No data available		
Boiling point/boiling range	:	ca. 140 °C		
Flammability (solid, gas)	:	No data available		
Upper/lower flammability or explosive limits				

Upper explosion limit / Up-	:	Upper flammability limit
per flammability limit		7,0 %(V)



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	Print Date 29.02.2024
Lower explosion limit / Lower flammability limit	Lower flammability limit 1,1 %(V)	
Flash point	29 °C Method: closed cup	
Auto-ignition temperature	270 °C	
Decomposition temperature	No data available	
рН	Not applicable substance/mixture is non-so	bluble (in water)
Viscosity Viscosity, kinematic	< 20,5 mm2/s (40 °C)	
<b>Solubility(ies)</b> Water solubility	insoluble	
Partition coefficient: n- octanol/water	No data available	
Vapour pressure	ca. 12 hPa (20 °C)	
Density	ca. 0,9 g/cm3 (20 °C)	
Relative vapour density	No data available	
Particle characteristics	No data available	
9.2 Other information		

## No data available

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.



evision Date: 18.12.2023		Version 6.3	Print Date 29.02.2024
<b>10.2 Chemical stability</b> The product is chemically st	table.		
10.3 Possibility of hazardous r		ons	
Hazardous reactions	:	Stable under recommended storage conditions.	
		Vapours may form explosive mixture with air.	
10.4 Conditions to avoid			
Conditions to avoid	:	Heat, flames and sparks.	
10.5 Incompatible materials			
Materials to avoid	:	No data available	
<b>10.6 Hazardous decomposition</b> No decomposition if stored a	-		
SECTION 11: Toxicological			
I1.1 Information on hazard cla Acute toxicity Harmful in contact with skin	sses	as defined in Regulation (EC) No 1272/2008	
I1.1 Information on hazard cla Acute toxicity Harmful in contact with skin <u>Components:</u>	or if i	as defined in Regulation (EC) No 1272/2008	
I1.1 Information on hazard cla Acute toxicity Harmful in contact with skin	or if i	as defined in Regulation (EC) No 1272/2008 nhaled. and xylene:	
I1.1 Information on hazard cla Acute toxicity Harmful in contact with skin <u>Components:</u> reaction mass of ethylben	or if i	as defined in Regulation (EC) No 1272/2008 nhaled. and xylene:	
I1.1 Information on hazard cla Acute toxicity Harmful in contact with skin <u>Components:</u> reaction mass of ethylben Acute oral toxicity	or if i	as defined in Regulation (EC) No 1272/2008 nhaled. and xylene:	
11.1 Information on hazard cla Acute toxicity Harmful in contact with skin <u>Components:</u> reaction mass of ethylben Acute oral toxicity 1-methoxy-2-propanol:	or if i	<b>as defined in Regulation (EC) No 1272/2008</b> nhaled. <b>and xylene:</b> LD50 Oral (Rat): 3.523 mg/kg	
<ul> <li>I1.1 Information on hazard cla</li> <li>Acute toxicity</li> <li>Harmful in contact with skin</li> <li><u>Components:</u></li> <li>reaction mass of ethylben</li> <li>Acute oral toxicity</li> <li>1-methoxy-2-propanol:</li> <li>Acute oral toxicity</li> </ul>	or if i	as defined in Regulation (EC) No 1272/2008 nhaled. and xylene: LD50 Oral (Rat): 3.523 mg/kg LD50 Oral (Rat): > 5.000 mg/kg LC50: 7,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
<ul> <li>I1.1 Information on hazard clane</li> <li>Acute toxicity</li> <li>Harmful in contact with skin</li> <li>Components:</li> <li>reaction mass of ethylben</li> <li>Acute oral toxicity</li> <li>1-methoxy-2-propanol:</li> <li>Acute oral toxicity</li> <li>Acute oral toxicity</li> </ul>	or if i or if i zene : :	as defined in Regulation (EC) No 1272/2008 nhaled. and xylene: LD50 Oral (Rat): 3.523 mg/kg LD50 Oral (Rat): > 5.000 mg/kg LC50: 7,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist	



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	Print Date 29.02.2024

#### Respiratory or skin sensitisation

## Skin sensitisation

Not classified based on available information.

### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)



# Sarnafil T Clean

Date of last issue: 01.12.2023 Revision Date: 18.12.2023		Version 6.3	Print Date 29.02.202
1-methoxy-2-propanol:			
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and othe aquatic invertebrates	r:	EC50 (Daphnia (water flea)): > 100 mg/ Exposure time: 48 h	1
12.2 Persistence and degradab	ility		
This product does not contai tion (EU/648/2004) (>0,2%).	n an	y tensides according to the definition in the	ne EU Detergents Regula-
<b>12.3 Bioaccumulative potential</b> No data available			
<b>12.4 Mobility in soil</b> No data available			
12.5 Results of PBT and vPvB a	isse	ssment	
Product:			
Assessment	:	This substance/mixture contains no con to be either persistent, bioaccumulative very persistent and very bioaccumulativ 0.1% or higher	and toxic (PBT), or
12.6 Endocrine disrupting prop	ertie	s	
Product:			
Assessment	:	The substance/mixture does not contain ered to have endocrine disrupting prope REACH Article 57(f) or Commission De (EU) 2017/2100 or Commission Regula levels of 0.1% or higher.	erties according to legated regulation
12.7 Other adverse effects			
Product:			
Additional ecological infor-	:	An environmental hazard cannot be exc unprofessional handling or disposal.	cluded in the event of

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product

: The generation of waste should be avoided or minimized wherever possible.



Date of last issue: 01.12.2023 Revision Date: 18.12.2023		Version 6.3	Print Date 29.02.2024
		Empty containers or liners may retain som This material and its container must be dis way. Dispose of surplus and non-recyclable pro- waste disposal contractor. Disposal of this product, solutions and any at all times comply with the requirements of protection and waste disposal legislation a local authority requirements. Avoid dispersal of spilled material and run soil, waterways, drains and sewers.	sposed of in a safe oducts via a licensed / by-products should of environmental and any regional
European Waste Catalogue	:	07 07 04* other organic solvents, washing liquors	g liquids and mother
Contaminated packaging	:	15 01 10* packaging containing residues of by dangerous substances	of or contaminated

## **SECTION 14: Transport information**

14.1 UN number or ID number			
ADR	:	UN 1993	
IMDG	:	UN 1993	
ΙΑΤΑ	:	UN 1993	
14.2 UN proper shipping name			
ADR	:	FLAMMABLE LIQUII (1-methoxy-2-propar	
IMDG	:	FLAMMABLE LIQUII (1-methoxy-2-propar	
ΙΑΤΑ	:	Flammable liquid, n.o (1-methoxy-2-propar	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR			
Packing group	:		
Classification Code	:	F1	

## Country GB 000000122027



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	B Print Date 29.02.2024
Hazard Identification Number Labels Tunnel restriction code	30 3 (D/E)	
<b>IMDG</b> Packing group Labels EmS Code	III 3 F-E, S-E	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	366 Y344 III Flammable Liquids	
<b>IATA (Passenger)</b> Packing group Labels	III Flammable Liquids	
14.5 Environmental hazards		
<b>ADR</b> Environmentally hazardous	no	
<b>IMDG</b> Marine pollutant	no	
IATA (Passenger) Environmentally hazardous	no	
IATA (Cargo) Environmentally hazardous	no	

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable



\_

Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3		Print Date 29.02.2024
The Persistent Organic Pollutan Regulation (EU) 2019/1021 as a ain)		Not applicable	
International Chemical Weapons Schedules of Toxic Chemicals a		Not applicable	
Regulation (EC) No 1005/2009 opposed plete the ozone layer	on substances that de- :	Not applicable	
UK REACH List of substances s (Annex XIV)	subject to authorisation :	Not applicable	
GB Export and import of hazard Informed Consent (PIC) Regula		Not applicable	
Control of Major Accident Hazar 2015 (COMAH)	-		e un de
Volatile organic compounds :	Law on the incentive tax for (VOCV) Volatile organic compound		
	Directive 2010/75/EU of 2 emissions (integrated poll Volatile organic compound	ution prevention and co	ntrol)
If other regulatory information ap Sheet, then it is described in this		ided elsewhere in the S	Safety Data
Health, safety and environ-	: Environmental Protection		

mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

## Other regulations:

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



Date of last issue: 01.12.2023 Revision Date: 18.12.2023 Version 6.3

Print Date 29.02.2024

## **SECTION 16: Other information**

Full text of H-Statements		
H226	:	Flammable liquid and vapour.
H304	÷	May be fatal if swallowed and enters airways.
H312		Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause drowsiness of dizziness. May cause damage to organs through prolonged or repeated
H373	·	
4440		exposure if inhaled.
H412	•	Harmful to aquatic life with long lasting effects.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	•	International Convention for the Prevention of Pollution from
	•	Ships, 1973 as modified by the Protocol of 1978
OEL		Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
	•	



Date of last issue: 01.12.2023 Revision Date: 18.12.2023	Version 6.3	Print Date 29.02.2024
PNEC REACH	<ul> <li>Predicted no effect concentration</li> <li>Regulation (EC) No 1907/2006 of the Europ and of the Council of 18 December 2006 co istration, Evaluation, Authorisation and Res cals (REACH), establishing a European Ch</li> </ul>	oncerning the Reg- striction of Chemi-
SVHC	: Substances of Very High Concern	
vPvB	: Very persistent and very bioaccumulative	
Further information		
Classification of the mixture:	Classification pro	ocedure:

Classification	of the mixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Acute Tox. 4	H312	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chroni	c 3 H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN