Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sika Water Repel

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

 Telephone no.
 : 01707 394444

 Fax no.
 : 01707 329129

 e-mail address of person
 : EHS@uk.sika.com

responsible for this SDS

Emergency telephone number : -

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10

Xn; R65 R66, R67 N; R51/53

Physical/chemical hazards : Flammable.

Human health hazards : Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin

dryness or cracking. Vapours may cause drowsiness and dizziness.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Reactive siloxane, containing solvent

Characteristics

Ingredient name	CAS number	%	EC number	Classification	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	>=90	265-185-4	R10 Xn; R65 R66, R67 N; R51/53	[1]
Polydimethylsiloxane		2.5-25		F; R11 N; R51/53	[1]
See section 16 for the full text of the R-phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

Date of issue : 03.08.2009. MSDS no. : 603759 1/6

Sika Water Repel 03.08.2009 2/6

4. FIRST AID MEASURES

First-aid measures

Inhalation : If it is suspected that fumes are still present, the rescuer should wear an appropriate

mask or self-contained breathing apparatus. Get medical attention if adverse health

effects persist or are severe. Get medical attention if symptoms appear.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce

vomiting. Maintain an open airway. Seek immediate medical attention.

Skin contact: Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Obtain medical attention if symptoms occur.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Flammable liquid. In a fire or if heated, a pressure increase will occur and the

container may burst, with the risk of a subsequent explosion. Runoff to sewer may

create fire or explosion hazard.

Hazardous combustion

products

6.

Special protective equipment for fire-fighters

: No specific data.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

ACCIDENTAL RELEASE MEASURES

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment (see section 8). Evacuate surrounding areas.

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE

Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapour or mist. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a

Date of issue : 03.08.2009. MSDS no. : 603759 2/6

Sika Water Repel 03.08.2009 3/6

7. HANDLING AND STORAGE

compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous.

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection Hand protection

No special measures required.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue : 03.08.2009. MSDS no. : 603759 3/6

Sika Water Repel 03.08.2009 4/6

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.

Colour : Colourless.

Odour : Hydrocarbon.

Important health, safety and environmental information

Boiling point : ▶135°C (>275°F)

Flash point : Closed cup: >30°C (>86°F)

Explosion limits : Lower: 1.1%

Upper: 6.5%

Vapour pressure : ▶fighest known value: 0.4 kPa (3 mm Hg) (Naphtha (petroleum), hydrodesulfurized

heavy)

Density : **▶**0.79 g/cm³

Solubility : Insoluble in the following materials: water

Viscosity : Kinematic (40°C (104°F)): <0.069 cm²/s (<6.9 cSt)

10. STABILITY AND REACTIVITY

Stability: The product is stable.

Conditions to avoid : Kvoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid release to the environment. Refer to special instructions/safety data sheet. Do not

swallow.

Materials to avoid : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation: Vapours may cause drowsiness and dizziness.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Eye contact: May cause eye irritation.

Chronic effects : Prolonged or repeated contact can defat the skin and lead to irritation, cracking

and/or dermatitis.

12. ECOLOGICAL INFORMATION

Environmental effects : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue : 03.08.2009. MSDS no. : 603759 4/6

Sika Water Repel 03.08.2009 5/6

13. DISPOSAL CONSIDERATIONS

European waste catalogue (EWC)

: 07 07 04* other organic solvents, washing liquids and mother liquors

Packaging

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous

substances

14. TRANSPORT INFORMATION

International transport regulations

<u>ADR</u>

UN number : UN1993

ADR Class : 3
Classification code : F1
Packing group : III

Proper shipping name: Flammable liquid, n.o.s

Contains : Turpentine substitute (White Spirit)

Label No. : 3

<u>IMDG</u>

UN number : UN1993

IMDG Class : 3
Packing group : III

Proper shipping name : Flammable liquid, n.o.s

Contains : Turpentine substitute (White Spirit)

Emergency schedules

(EmS)

: F-E, S-E

Marine pollutant : P Label no. : 3

IATA

UN number : UN1993

IATA Class : 3
Packing group : III

Proper shipping name : Flammable liquid, n.o.s

Contains: Turpentine substitute (White Spirit)

Label no. : 3

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : ▼n, N

Harmful, Dangerous for the environment

Date of issue : 03.08.2009. MSDS no. : 603759 5/6

Sika Water Repel 03.08.2009 6/6

15. REGULATORY INFORMATION

Risk phrases : R10- Flammable.

R65- Harmful: may cause lung damage if swallowed.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

: VOC (w/w): 95.25%

Safety phrases : S2- Keep out of the reach of children.

S29- Do not empty into drains.

S46- If swallowed, seek medical advice immediately and show this container or label.

VOC content (EU)

Regulatory information

National regulations

: Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

3)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR)

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R11- Highly flammable.

R10- Flammable.

R65- Harmful: may cause lung damage if swallowed.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: F - Highly flammable

ions 2 and Xn - Harmful

N - Dangerous for the environment

History

3

Date of printing : 03.08.2009.

Date of issue : 03.08.2009.

Date of previous issue : 16.03.2009.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.

Date of issue : 03.08.2009. MSDS no. : 603759 6/6