

SikaPlast® 100 MR (GB)

DECLARATION OF PERFORMANCE

No. 73352079

1 UNIQUE IDENTIFICATION CODE OF THE PRODUCT-

TYPE:

73352079

2 INTENDED USE/S EN 934-2

Water reducing concrete admixture according to EN934-2

(table 3.2)

3 MANUFACTURER: Sika Limited

Watchmead

Welwyn Garden City

Hertfordshire AL7 1BQ

United Kingdom

4 AUTHORISED REPRESENTATIVE:

5 SYSTEM/S OF AVCP:

System 2+

6a HARMONISED STANDARD:

EN 934-2

Notified body/ies:

1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Water soluble chloride	< 0.1%	System 2+	EN 934-2
Alkali content	< 0.25%	System 2+	
Increase in consistence	Increase in slump >/= 120mm from initial (30+/- 10)mm (fulfilled)	System 2+	
Retention of consistence	30 mins after the addition the consistence of the test mix shall not fall below the value of the initial consistence of the control mix (fulfilled)	System 2+	
Compressive strength	At 28 days: test mix >/= 90% of control mix (fulfilled)	System 2+	
Air content in fresh concrete	Test Mix > 2% by volume (fulfilled)	System 2+	
Dangerous substances	NPD	System 2+	
Corrosion behaviour	No corrosion promoting effects on steel embedded in concrete	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anthony Smith Function: Product Manager At Sika Limited on 26 March 2021

Name: Martin Liska Function: R&D Manager

At Sika Limited on 26 March 2021

End of information as required by Regulation (EU) No 305/2011





18

Sika Limited, Hertfordshire, United Kingdom

DoP No. 73352079

EN 934-2

Notified Body 1029

Water reducing concrete admixture according to EN934-2

(table 3.2)

Water soluble chloride < 0.1%
Alkali content < 0.25%

Increase in slump >/= 120mm from initial (30+/-

10)mm (fulfilled)

30 mins after the addition the consistence of the Retention of consistence test mix shall not fall below the value of the initial

consistence of the control mix (fulfilled)

Compressive strength At 28 days: test mix >/= 90% of control mix

(fulfilled)

Air content in fresh concrete Test Mix > 2% by volume (fulfilled)

Corrosion behaviour No corrosion promoting effects on steel embedded

in concrete

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaPlast® 100 MR (GB) 73352079 2021.03 , ver. 2 1088



Sika Limited

Watchmead Welwyn Garden City United Kingdom www.sika.co.uk

Declaration of Performance

SikaPlast® 100 MR (GB) 73352079 2021.03 , ver. 2 1088

