
according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)



Sika®

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikadur®-330 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product is not intended for consumer use, Adhesive

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)



Revision Date 14.06.2017 Version 3.0 Print Date 14.06.2017

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Im-

mediately call a POISON CENTER/doctor.

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Hazardous components which must be listed on the label:

• 247-063-2 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Registration number		
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine 25513-64-8 247-063-2 01-2119560598-25-XXXX	Acute Tox.4; H302 Skin Corr.1A; H314 Eye Dam.1; H318 Skin Sens.1A; H317	>= 50 - <= 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

Sikadur®-330 (B)





SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects sensitising effects

Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)





SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see

Country GB 000000041124

4 / 12

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017



section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017 Version 3.0 Print Date 14.06.2017



Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste Colour : grey

Odour : amine-like

Odour Threshold : No data available

Flash point : > 102 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : ca. 11

at 500,00 g/l

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : ca.0,02 hPa

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017 Version 3.0

: ca.1,3 g/cm3 at 20 °C Density

: No data available

: insoluble Water solubility

Partition coefficient: n-

octanol/water

Viscosity, dynamic : No data available

Viscosity, kinematic > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

: No data available Evaporation rate

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017 Version 3.0 Print Date 14.06.2017



Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae : EC50: 29,5 mg/l, 72 h, Scenedesmus capricornutum (fresh

water algae)

Toxicity to fish (Chronic tox- : LC50: 174 mg/l, 48 h, Leuciscus idus (Golden orfe)

city)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential


No data available

12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)



Sika ®

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1760

14.2 Description of the goods : CORROSIVE LIQUID, N.O.S.

(trimethylhexane-1,6-diamine)

14.3 Class: 814.4 Packing group: IIIClassification Code: C9Labels: 8

Country GB 000000041124

9 / 12

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017 Version 3.0 Print Date 14.06.2017

Tunnel restriction code : (E) **14.5 Environmentally hazard-** : no

ous

IATA

14.1 UN number : 1760

14.2 Description of the goods : Corrosive liquid, n.o.s.

(trimethylhexane-1,6-diamine)

 14.3 Class
 : 8

 14.4 Packing group
 : III

 Labels
 : 8

 14.5 Environmentally hazard : no

ous

IMDG

14.1 UN number : 1760

14.2 Description of the goods : CORROSIVE LIQUID, N.O.S.

(trimethylhexane-1,6-diamine)

 14.3 Class
 : 8

 14.4 Packing group
 : III

 Labels
 : 8

 EmS Number 1
 : F-A

 EmS Number 2
 : S-B

 14.5 Marine pollutant
 : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/orexcluded from the regulation, and/or

- exempted from the registration.

REACH Information:

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)





Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Full text of other abbreviations

Acute Tox. Acute toxicity
Eye Dam. Serious eye damage
Skin Corr. Skin corrosion
Skin Sens. Skin sensitisation

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

according to Regulation (EC) No. 1907/2006

Sikadur®-330 (B)

Revision Date 14.06.2017



Version 3.0

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!