



EN 1504-2: 2004  
EN 13813: 2002

09

0620

## DECLARATION OF PERFORMANCE

### Sikafloor®-330

02	08	01	04	040	0	000001	1041
----	----	----	----	-----	---	--------	------

#### EN 13813:2002

<b>1. Product Type:</b> Unique identification code of the product-type:	Sikafloor®-
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	330 (Batch No. see packaging)
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	two part, solvent free, very low VOC emission certified, elastic, self-smoothing PUR resin <b>Principles 1.3, 2.2, 8.2, 5.1, 6.1 of EN 1504-2 and EN 13813 SR-B1,5-AR1-IR 4</b>
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikafloor®, Descol sports surfaces Duurstedeweg 7 NL – 7418 CK Deventer Netherlands
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4

Declaration of Performance



<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Not relevant for system 4
<b>8. Notified body (ETA):</b> In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)

## 9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Fire Classification:	E <sub>fl</sub>	EN 13501-1	EN 13813: 2002
Release of corrosive substances (Synthetic Resin Screed):	SR	EN 13813	
Abrasion Resistance:	AR 1 <sup>1)</sup>	EN 13892-4	
Bond strength:	B 1,5	EN 13892-8	
Impact Resistance:	IR 4	EN ISO 6272	
Sound insulation:	NPD	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Thermal resistance:	NPD	EN 12664	

<sup>1)</sup> Not broadcast with sand



For Further Information:  
Insert Local address  
Street  
City & Post Code  
Country

Phone      Insert number  
Telefax      Insert number  
[www.sika.com](http://www.sika.com)



## EN 1504-2:2004

<b>1. Product Type:</b> Unique identification code of the product-type:	Sikafloor®-
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	330 (Batch No. see packaging)
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	two part, solvent free, very low VOC emission certified, elastic, self-smoothing PUR resin <b>Principles 1.3, 2.2, 8.2, 5.1, 6.1 of EN 1504-2 and EN 13813 SR-B1,5-AR1-IR 4</b>
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikafloor®, Descol sports surfaces Duurstedeweg 7 NL – 7418 CK Deventer Netherlands
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	0620 Notified factory production control certification body No. 0620 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 1041.
<b>8. Notified body (ETA):</b> In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)



For Further Information:  
Insert Local address  
Street  
City & Post Code  
Country

Phone      Insert number  
Telefax    Insert number  
[www.sika.com](http://www.sika.com)

## 9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Abrasion resistance	< 3000 mg	EN ISO 5470-1	EN 1504-2: 2004
Permeability to CO <sub>2</sub> :	S <sub>D</sub> > 50 m	EN 1062-6	
Permeability to water vapour:	Class II	EN 1062-6	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/[m}^2 \times \text{h}^{0.5}]$	EN ISO 7783-2	
Resistance to severe chemical attack:	Class II	EN 13529	
Impact resistance	Class II	EN ISO 6272-1	
Adhesion strength by pull-off test	$\geq 0.8 \text{ N/mm}^2$	EN 1542	
Fire Classification:	E <sub>fl</sub>	EN 13501-1	

Not broadcast with sand



For Further Information:  
 Insert Local address  
 Street  
 City & Post Code  
 Country

Phone      Insert number  
 Telefax      Insert number  
[www.sika.com](http://www.sika.com)

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Remo van der Wilt  
General Manager

Marcel Ras  
Manager Operations



Deventer, July 1<sup>st</sup>, 2013

## Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For Further Information:  
Insert Local address  
Street  
City & Post Code  
Country

Phone      Insert number  
Telefax    Insert number  
[www.sika.com](http://www.sika.com)

