

## PRODUCT DATA SHEET

# Leadax Flashing Easy FA

Leadax Flashing Easy FA - Fully adhesive Leadax lead-free flashing

### PRODUCT DESCRIPTION

The fully self-adhesive lead replacement made from recycled polyvinyl butyral (r-PVB).

### USES

For sealing around dormers, windows, chimneys, abutments, valleys and ridges.

### CHARACTERISTICS / ADVANTAGES

- Lightweight
- Malleable - similar to lead
- Strong

### PRODUCT INFORMATION

<b>Packaging</b>	Individually wrapped in polythene sleeve with paper product label.		
<b>Colour</b>	Grey		
<b>Shelf Life</b>	25 years		
<b>Storage Conditions</b>	Leadax Easy FA should be stored in a ventilated area, away from frost, humidity and at temperatures - 5 to + 30 °C. However, prior to use, the product must acclimatise to processing temperature of + 5 °C.		
<b>Dimensions</b>	Characteristic	Units	Value
	Length	m	5
	Width	mm	150, 250, 300, 450
<b>Overall Thickness</b>	1.8 mm		

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable condi-

tions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

Ensure the surface is dry and free of dust and grease.

### APPLICATION

Use Leadax scissors to cut to size and a Leadax roller to mould the product. The temperature needs to be above + 5 °C. Release the liner after pre-shaping by hand and roller.

Any overlap should be 80 mm making sure the area of Leadax Easy FA to be covered is free from dust and grease. Connections should be sealed with Leadax sealant. Remove the protective foil within 30 days.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



**Product Data Sheet**  
Leadax Flashing Easy FA  
March 2026, Version 02.01  
020945201000245829

LeadaxFlashingEasyFA-en-GB-(03-2026)-2-1.pdf