

Date of last issue: 25.11.2022	Version 1.1	Print Date 29.02.2024
Revision Date: 04.12.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Parex Cembond

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cement / Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone Telefax E-mail address of person	:	+44 (0)1707 394444 +44 (0)1707 329129 EHS@uk.sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)							
Skin irritation, Category 2	H315: Causes skin irritation.						
Serious eye damage, Category 1	H318: Causes serious eye damage.						
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.						

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		!
Signal word	:	Danger	
Hazard statements	:	H315	Causes skin irritation.



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	V	Print Date 29.02.2024	
	H318 H335	Causes serious eye damage. May cause respiratory irritation.	
Precautionary statements :	Prevention:		
	P261	Avoid breathing dust/ fume/ gas	/ mist/ va-
	P264	pours/ spray. Wash skin thoroughly after hand	dlina.
	P280	Wear protective gloves/ eye pro protection.	
	Response:		
	P304 + P340 + I	P312 IF INHALED: Remove pe air and keep comfortable for bre POISON CENTER/ doctor if you	eathing. Call a
	P305 + P351 + I		e cautiously Remove con- to do. Con-
	Storage:		
	P403 + P233	Store in a well-ventilated place. tainer tightly closed.	Keep con-

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006. The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 60 - < 80
	266-043-4	Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory system)	



Date of last issue: 25.11.2022	Version 1.1	Print Date 29.02.2024
Revision Date: 04.12.2023		

Substances with a workplace exposure limit : calcium carbonate>= 1 - < 2,5							
		>= 1 - < 2,3					
	207-439-9						
	01-2119486795-18-						
	XXXX						
kaolin	1332-58-7	>= 1 - < 2,5					
	310-194-1						

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General advice : Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled ÷ Move to fresh air. Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. 2 Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact Small amounts splashed into eyes can cause irreversible tis-: sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. : Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Cough **Symptoms** : Respiratory disorder **Excessive lachrymation** Erythema

Dermatitis

Risks



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.	
4.3 Indication of any immediate n	edical attention and special treatment r	needed
Treatment	: Treat symptomatically.	
SECTION 5: Firefighting meas	ures	
5.1 Extinguishing media		
Suitable extinguishing media	 In case of fire, use water/water spray/w ide/sand/foam/alcohol resistant foam/c extinction. 	
5.2 Special hazards arising from	he substance or mixture	
Hazardous combustion prod- ucts	: No hazardous combustion products are	e known
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-contained	l breathing apparatus.
Further information	: Standard procedure for chemical fires.	
SECTION 6: Accidental releas	emeasures	
6.1 Personal precautions, protect	ve equipment and emergency procedu	res
Personal precautions	: Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.	
6.2 Environmental precautions		
Environmental precautions	 Try to prevent the material from enterin courses. No special environmental precautions r 	-
6.3 Methods and material for con	ainment and cleaning up	
Methods for cleaning up	Pick up and arrange disposal without c Keep in suitable, closed containers for	
6.4 Reference to other sections		
For personal protection see se	tion 8.	



Date of last issue: 25.11.2022 Revision Date: 04.12.2023 Version 1.1

Print Date 29.02.2024

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	Do not breathe vapours/dust. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Further information on stor- age stability	:	Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
Cement (chromium reduced)	65997-15-1	TWA (inhalable dust)	10 mg/m3	GB EH40	
		TWA (Respirable dust)	4 mg/m3	GB EH40	
calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m3	GB EH40	
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sam-				

Date of last issue: 25.11.2022 Revision Date: 04.12.2023

4

	aerosols., The health includes in air equal to o dust or 4 mg.m any dust will be above these le WELs and exp limits., Most ind sizes. The beh after entry into sponse that it e HSE distinguis termed 'inhalat the fraction of a during breathin respiratory trac penetrates to t tions and expla dusts contain o the relevant lim short-term exp	metric analysis or re COSHH definition of s dust of any kind wi or greater than 10 m and 8-hour TWA of re e subject to COSHH vels. Some dusts has osure to these mus dustrial dusts contain aviour, deposition at the human respirate elicits, depend on the hes two size fraction oble' and 'respirable'. airborne material that og and is therefore at the gas exchange re anatory material are components that has hits should be comp- osure limit is listed, limit should be use	of a substance has hen present at a c ng.m-3 8-hour TW espirable dust. The dif people are exp ave been assigne t comply with the in particles of a wi and fate of any par ory system, and the e nature and size ns for limit-setting , Inhalable dust ap at enters the nose available for depose approximates to the given in MDHS14 ve their own assig lied with., Where a figure three time	zardous to concentration A of inhalable is means that posed to dust d specific appropriate de range of ticular particle ne body re- of the particle. purposes oproximates to and mouth sition in the le fraction that Fuller defini- 4/4., Where ined WEL, all no specific
		TWA (Respirable dust)	4 mg/m3	GB EH40
kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m3	GB EH40
	dust and inhala will be collecte the methods de pling and gravi aerosols., The health includes in air equal to o dust or 4 mg.m any dust will be above these le WELs and exp limits., Most ind sizes. The beh after entry into sponse that it e HSE distinguis termed 'inhalat the fraction of a during breathin respiratory trac penetrates to the	ation: For the purpo able dust are those d when sampling is escribed in MDHS1 metric analysis or re COSHH definition of s dust of any kind wi or greater than 10 m n-3 8-hour TWA of re e subject to COSHH vels. Some dusts has osure to these mus dustrial dusts contal aviour, deposition a the human respirate elicits, depend on th hes two size fractio obe' and 'respirable'. airborne material that ag and is therefore a ct. Respirable dust a he gas exchange re anatory material are components that has	fractions of airbor undertaken in acc 4/4 General metho espirable, thoracio of a substance has hen present at a c ng.m-3 8-hour TW espirable dust. The ave been assigne t comply with the ave been assigne t comply with the in particles of a wi and fate of any par ory system, and the e nature and size ns for limit-setting , Inhalable dust ap at enters the nose available for depose approximates to the egion of the lung. F	ne dust which cordance with ods for sam- c and inhalable ardous to concentration A of inhalable is means that oosed to dust d specific appropriate de range of ticular particle ne body re- of the particle. purposes oproximates to and mouth sition in the ne fraction that Fuller defini- 4/4., Where





Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
		mplied with., Where no specific ed, a figure three times the long- ised.
	TWA (Respirable dust)	e 0,1 mg/m3 2004/37/EC
	Further information: Carcinoge	ns or mutagens

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

general dust value

Form of exposure	Value type	Control parameters	Basis
Inhalable	TWA	10 mg/m3	GB EH40
Respirable fraction	TWA	4 mg/m3	GB EH40

8.2 Exposure controls

Personal protective equipmen	t
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.
Skin and body protection :	Dust impervious protective suit Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. particulate filter P P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General	advice
---------	--------

: Try to prevent the material from entering drains or water



Date of last issue: 25.11.2022	
Revision Date: 04.12.2023	

Version 1.1

Print Date 29.02.2024

courses. No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical Physical state	an :	solid
Appearance Colour	:	powder grey
Odour	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility	:	soluble



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: No data available	
Density	: ca. 1 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: 25.11.2022 Revision Date: 04.12.2023 Version 1.1

Print Date 29.02.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential No data available



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB a	assessment	
Product:		
Assessment	 This substance/mixture contains no co to be either persistent, bioaccumulative very persistent and very bioaccumulation 0.1% or higher 	e and toxic (PBT), or
12.6 Endocrine disrupting prop No data available	perties	
12.7 Other adverse effects		
12.7 Other adverse enects		

13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
ΙΑΤΑ	: Not regulated as a dangerous good

14.2 UN proper shipping name



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class	s(es)	
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards Not regulated as a dange		
14.6 Special precautions for Not applicable	r user	
14.7 Maritime transport in b Not applicable for produc	ulk according to IMO instruments ct as supplied.	

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high
concern (SVHC) for Authorisation: Not applicableThe Persistent Organic Pollutants Regulations (retained
Regulation (EU) 2019/1021 as amended for Great Brit-
ain): Not applicableInternational Chemical Weapons Convention (CWC)
Schedules of Toxic Chemicals and Precursors: Not applicableRegulation (EC) No 1005/2009 on substances that de-
plete the ozone layer: Not applicable



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024		
UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)				
Volatile organic compounds :	Law on the incentive tax for volatile organic co (VOCV) Volatile organic compounds (VOC) content: < no VOC duties Directive 2010/75/EU of 24 November 2010 o emissions (integrated pollution prevention and Volatile organic compounds (VOC) content: <	0% w/w n industrial I control)		
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.				
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	Environmental Protection Act 1990 & Subsidia Health and Safety at Work Act 1974 & Subsidia Control of Substances Hazardous to Health R (COSHH) May be subject to the Control of Major Accider Regulations (COMAH), and amendments.	iary Regulations egulations		

Other regulations:

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements				
H315 H318 H335	 Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. 			
Full text of other abbreviations				
Eye Dam. Skin Irrit. STOT SE 2004/37/EC	 Serious eye damage Skin irritation Specific target organ toxicity - single exposure Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work 			
GB EH40 2004/37/EC / TWA GB EH40 / TWA ADR CAS	 UK. EH40 WEL - Workplace Exposure Limits Long term exposure limit Long-term exposure limit (8-hour TWA reference period) European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service 			



Date of last issue: 25.11.2022 Revision Date: 04.12.2023	Version 1.1	Print Date 29.02.2024
DNEL :	Derived no-effect level	
EC50 :	Half maximal effective concentration	
GHS :	Globally Harmonized System	
IATA :	International Air Transport Association	
IMDG :	International Maritime Code for Dangerous Goo	ds
LD50 :	: Median lethal dosis (the amount of a material, given all at	
	once, which causes the death of 50% (one half)	of a group of
	test animals)	2 .
LC50 :	Median lethal concentration (concentrations of t	he chemical in
	air that kills 50% of the test animals during the c	observation
	period)	
MARPOL :	International Convention for the Prevention of P	ollution from
	Ships, 1973 as modified by the Protocol of 1978	3
OEL :	Occupational Exposure Limit	
PBT :	Persistent, bioaccumulative and toxic	
PNEC :	Predicted no effect concentration	
REACH :	Regulation (EC) No 1907/2006 of the European	Parliament
	and of the Council of 18 December 2006 concer	rning the Reg-
	istration, Evaluation, Authorisation and Restriction	on of Chemi-
	cals (REACH), establishing a European Chemic	als Agency
SVHC :	Substances of Very High Concern	
vPvB :	Very persistent and very bioaccumulative	

Further information

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN