Version 6.0



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Trade name : SikaGard<sup>®</sup> -831(B)

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Fire protection system, For professional users only.

## 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		!
Signal word	:	Danger	•
Hazard statements	:	H302 + H332 H314 H317 H412	Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting ef-

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



			fects.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory tract.
Precautionary statements	:	Prevention:	
		P261	Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P303 + P361 + F	P353 IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water.
		P304 + P340 + F	P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Im- mediately call a POISON CENTER/ doctor.
		P305 + P351 + F	•

## Hazardous components which must be listed on the label:


3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) Polyoxypropylenediamine (polymer)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version 6.0



## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Eye Dam. 1; H318	>= 25 - < 40
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 20 - < 25
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 20 - < 25
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 10 - < 20
Polyoxypropylenediamine (poly- mer)	9046-10-0 618-561-0	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Aquatic Chronic 3; H412 Eye Dam. 1; H318	>= 10 - < 20
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	< 1

For explanation of abbreviations see section 16.

:

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

Date of last issue: 03.12.2020 Revision Date: 07.05.2021

Version 6.0



If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.</li> </ul>
In case of eye contact	<ul> <li>Small amounts splashed into eyes can cause irreversible tissue damage and blindness.</li> <li>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>Continue rinsing eyes during transport to hospital.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	<ul> <li>Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.</li> </ul>
Risks	: Health injuries may be delayed. corrosive effects sensitising effects
	Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.
4.3 Indication of any immediate Treatment	e medical attention and special treatment needed : Treat symptomatically.
SECTION 5: Firefighting me	asures
5.1 Extinguishing media Suitable extinguishing media	a : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for



Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0

extinction.

o.z opeciai nazarus arising non	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.
SECTION 6: Accidental releases 6.1 Personal precautions, protect		measures e equipment and emergency procedures
Personal precautions		Use personal protective equipment.
		Deny access to unprotected persons.
6.2 Environmental precautions		Deny access to unprotected persons.
<b>6.2 Environmental precautions</b> Environmental precautions	:	

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling	<ul> <li>Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8).</li> </ul>
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Provide sufficient air exchange and/or exhaust in work rooms.



Date of last issue: 03 Revision Date: 07.05		Version 6.0	Print Date 24.05.2022
		Follow standard hygiene measures when hand products	ing chemical
Advice on prote fire and explos	ection against : ion	Normal measures for preventive fire protection.	
Hygiene meas	ures :	Handle in accordance with good industrial hygic practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for	safe storage, inc	luding any incompatibilities	
Requirements areas and cont		Keep container tightly closed in a dry and well- place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Sto ance with local regulations.	arefully re-
Further informa age stability	ation on stor- :	No decomposition if stored and applied as direc	sted.
7.3 Specific end us	se(s)		

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

Contains no substances with occupational exposure limit values.

## 8.2 Exposure controls

Personal protective equipment	
Eye protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

#### **Environmental exposure controls**

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Colour Odour Odour Threshold	:	liquid yellow amine-like No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0,07 hPa
Relative vapour density	:	No data available
Density	:	ca. 1,00 g/cm3 (20 °C)
Solubility(ies) Water solubility Solubility in other solvents	-	insoluble No data available

Country GB 000000129843

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



Partition coefficient: n- octanol/water Auto-ignition temperature		No data available
		No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	ca. 100 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

## 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

## 10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Harmful if swallowed or if inhaled.

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



## Components:

<b>3-aminomethyl-3,5,5-trimet</b> Acute oral toxicity	hylc :	· · · · · · · · · · · · · · · · · · ·
Acute inhalation toxicity	:	LC50 (Rat): > 5,01 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
m-phenylenebis(methylam	ine):	
Acute oral toxicity	:	
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3.100 mg/kg
2,4,6-tris(dimethylaminome	ethy	l)phenol:
Acute oral toxicity	:	LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008
salicylic acid:		
Acute oral toxicity	:	LD50 Oral (Rat): 891 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg
Skin corrosion/irritation Causes severe burns.		
Components:		
2,4,6-tris(dimethylaminome	ethy	l)phenol:
Species	:	Rabbit
Assessment Method	:	Corrosive OECD Test Guideline 404
	•	
Assessment	:	irritating
untry GB 000000129843		

Country GB 000000129843

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



Remarks

: Annex VI - Harmonised REGULATION (EC) No 1272/2008

## Serious eye damage/eye irritation

Causes serious eye damage.

#### **Components:**

#### 2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	:	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

#### Respiratory or skin sensitisation

## Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

Corrosive to the respiratory tract.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

:

## 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



## **SECTION 12: Ecological information**

## 12.1 Toxicity

<u>Components:</u>				
3-aminomethyl-3,5,5-trimethylcyclohexylamine:				
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h			
benzyl alcohol:				
Toxicity to fish	: LC50 (Fish): > 100 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h			
m-phenylenebis(methylamin	e):			
Toxicity to fish	<ul> <li>LC50 (Oryzias latipes (Japanese medaka)): &gt; 10 - 100 mg/l</li> <li>Exposure time: 96 h</li> </ul>			
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h			
2,4,6-tris(dimethylaminomethyl)phenol:				
Toxicity to algae/aquatic plants	<ul> <li>EC50 (Scenedesmus capricornutum (fresh water algae)): &gt; 10</li> <li>- 100 mg/l</li> <li>Exposure time: 72 h</li> </ul>			
<b>12.2 Persistence and degradabili</b> No data available	ty			
<b>12.3 Bioaccumulative potential</b> No data available				
<b>12.4 Mobility in soil</b> No data available				
12.5 Results of PBT and vPvB assessment				
Product:				
Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher			
12.6 Endocrine disrupting properties				

## Product:



Date of last issue: 03.12.2020 Revision Date: 07.05.2021	Version 6.0	Print Date 24.05.202
Assessment	<ul> <li>The substance/mixture does not conta ered to have endocrine disrupting prop REACH Article 57(f) or Commission D (EU) 2017/2100 or Commission Regu- levels of 0.1% or higher.</li> </ul>	perties according to Delegated regulation
12.7 Other adverse effects		
Product: Additional ecological infor- mation	: An environmental hazard cannot be en unprofessional handling or disposal. Harmful to aquatic life with long lasting	

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product	<ul> <li>The generation of waste should be avoided or minimized wherever possible.</li> <li>Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.</li> <li>Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.</li> <li>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.</li> <li>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.</li> </ul>
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

14.1 UN number			
ADR	:	UN 2735	
IMDG	:	UN 2735	
ΙΑΤΑ	:	UN 2735	
14.2 UN proper shipping name			
ADR	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))	
IMDG	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-	
0 1 00 00000100010			10/

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

# SikaGard<sup>®</sup> -831(B)

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



Revision Date: 07.05.2021			1 mil Balo 2 1.00.2021
		phenylenebis(methylamine))	
ΙΑΤΑ	:	Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, phenylenebis(methylamine))	m-
14.3 Transport hazard class(es)			
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
<b>ADR</b> Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	80 8	
<b>IMDG</b> Packing group Labels EmS Code	:	III 8 F-A, S-B	
<b>IATA (Cargo)</b> Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels		Y841 III	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	852	
14.5 Environmental hazards			
<b>ADR</b> Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
<b>IATA (Passenger)</b> Environmentally hazardous	:	no	
<b>IATA (Cargo)</b> Environmentally hazardous	:	no	
14.6 Special precautions for use	r		

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 SilcaCard® 921(P)

# SikaGard<sup>®</sup> -831(B)

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)			:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)			:	Not applicable
	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer			Not applicable
	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			:	Not applicable
REACH Information: All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg		trea /or gula	tion, and/or	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma jor-accident hazards involving dangerous substances. Not applicable				

Volatile organic compounds	: Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 22,58 %
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 22,58 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations	
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations	
specific for the substance or	Control of Substances Hazardous to Health Regulations	

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



mixture:

(COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

#### Full text of H-Statements H302 : Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects. Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Chronic Long-term (chronic) aquatic hazard Eye Dam. Serious eye damage Eye Irrit. Eye irritation Reproductive toxicity Repr. Skin Corr. Skin corrosion Skin sensitisation Skin Sens. European Agreement concerning the International Carriage of ADR Dangerous Goods by Road Chemical Abstracts Service CAS Derived no-effect level DNEL Half maximal effective concentration EC50 GHS **Globally Harmonized System**

International Air Transport Association IATA International Maritime Code for Dangerous Goods IMDG LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration REACH Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Date of last issue: 03.12.2020 Revision Date: 07.05.2021 Version 6.0



SVHC:Substances of Very High ConcernvPvB:Very persistent and very bioaccumulation	ve
---	----

Further information		
Classification of the m	ixture:	Classification procedure:
Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN