

Sikacrete[®]-920 UHP

Declaration of Performance No 27251475

1	Unique identification code of the product-type:	27251475
2	Intended use/es:	<p>For uses in buildings and civil engineering works — Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete</p> <p>For uses subject to reaction to fire regulations — Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete</p>
3	Manufacturer:	<p>Sika Services AG Tüffenwies 16 8064 Zürich Switzerland</p>
5	System/s of AVCP:	<p>System 2+ (For uses in buildings and civil engineering works) System 4 (For uses subject to reaction to fire regulations)</p>
6a	Harmonised standard:	EN 1504-3:2005
	Notified body/ies:	1139

Declaration of Performance

Sikacrete[®]-920 UHP

27251475

12/09/2024 1

1029

1 / 3

7 Declared performance/s:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive strength	Class R4	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive Bond	≥ 2.0 MPa	System 2+	
Restrained shrinkage / expansion (dimensional stability)	NPD	System 2+	
Elastic Modulus	≥ 20 GPa	System 2+	
Thermal Compatibility (For durability)	Freeze-thaw ≥ 2.0 MPa	System 2+	
Skid resistance	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Capillary Absorption	≤ 0.5 kg/m ² /h ^{1/2}	System 2+	
Reaction to fire	Class A1	System 4	
Dangerous substances	NPD	System 2+	
Carbonation Resistance (For durability of corrosion protection or inhibition)	Pass	System 2+	


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski

Function: Corporate Product Certification Manager

At Warsaw on 2024-09-12



Name: Wiktor Karpala

Function: Data Processing Specialist CTD

At Warsaw on 2024-09-12



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikacrete®-920 UHP

27251475

12/09/2024 1

1029

2 / 3

BUILDING TRUST



CE

24

Sika Services AG, Zürich, Switzerland

27251475

Compressive strength	Class R4
Chloride ion content	≤ 0.05 %
Adhesive Bond	≥ 2.0 MPa
Elastic Modulus	≥ 20 GPa
Thermal Compatibility (For durability)	Freeze-thaw ≥ 2.0 MPa
Capillary Absorption	≤ 0.5 kg/m ² /h ^½
Reaction to fire	Class A1

EN 1504-3:2005

1139

For uses in buildings and civil engineering works — Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete

For uses subject to reaction to fire regulations — Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikacrete®-920 UHP

27251475

12/09/2024 1

1029

3 / 3

BUILDING TRUST

