

BUILDING TRUST

Sikadur[®]-52 Injection Normal

DECLARATION OF PERFORMANCE No. 36748706

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	36748706
2	INTENDED USE/S	EN 1504-5:2004 Construction products: Concrete injection for force transmitting filling of cracks, voids and interstices (F). Intended use: In buildings and civil engineering works. U(F1)W(3)(1)(8/30)(0)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-5:2004
	Notified body/ies:	0921

Declaration of Performance Sikadur®-52 Injection Normal 36748706 2019.10, ver. 2 1001 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Adhesion by tensile bond strength	Cohesive failure in the substrate	System 2+	
Adhesion by slant shear strength	NPD	System 2+	
Shrinkage: Volumetric shrinkage	NPD	System 2+	
Glass transition temperature	> 40 °C	System 2+	
Workability: Injectability into dry medium	0.3 mm	System 2+	
Workability: Injectability into non dry medium	0.3 mm	System 2+	EN 1504- 5:2004
Chloride content	NPD	System 2+	
Durability	Cohesive failure in the substrate	System 2+	
Corrosion behavior	Deemed to have no corrosive effect	System 2+	
Release of dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Chris Mossman-Monk Function: Product Manager At Sika Limited on 26 January 2022

.

Name : Martin Liska Function: R&D Manager At Sika Limited on 26 January 2022

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance Sikadur®-52 Injection Normal 84588089 2019.10, ver. 2 1001



BUILDING TRUST

	E
	17
Sika Services A	G, Zurich, Switzerland
31	6748706
EN 1	504-5:2004
Notifie	ed Body 0921
Intended use: In buildin	ce transmitting filling of cracks, voids and interstices (F). gs and civil engineering works. (3)(1)(8/30)(0)
Adhesion by tensile bond strength	Cohesive failure in the substrate
Glass transition temperature	> 40 °C
Workability: Injectability into dry medium	0.3 mm
Workability: Injectability into non dry medium	0.3 mm
Durability	Cohesive failure in the substrate
	Deemed to have no corrosive effect

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance Sikadur®-52 Injection Normal 84588089 2019.10, ver. 2 1001

BUILDING TRUST

Sika Limited

Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom www.sika.co.uk

Declaration of Performance

Sikadur®-52 Injection Normal 84588089 2019.10, ver. 2 1001



BUILDING TRUST