

## PRODUCT DATA SHEET

# P28 Filter Fluid

A powerful chemical that enhances the performance of in-line magnetic filters

### PRODUCT DESCRIPTION

Everbuild P28 Filter Fluid has been specifically developed to penetrate, release and lift magnetite deposits and contaminants, and deliver the debris directly to the in-line filter for fast and safe removal. Everbuild P28 Filter Fluid is a neutral product that is compatible with all metals and materials commonly used in central heating systems.

### USES

- Suitable for systems already treated with inhibitor
- Increases the capture rate of circulating solids, not just suspended black iron oxide sludge by in-line filters
- Suitable for use with all types of filters
- Suitable for use in all types of water

### PRODUCT INFORMATION

<b>Packaging</b>	500 ml bottle
<b>Shelf Life</b>	36 months from the date of manufacture
<b>Storage Conditions</b>	Store in tightly closed original container and keep in a dry, cool and well ventilated place. Keep away from freezing conditions. Store at temperatures above 5 °C

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

### CHARACTERISTICS / ADVANTAGES

- Powerful additive that safely dislodges and circulates magnetite to the filter
- Increases the efficiency and lifespan of filters
- Suitable for use with all filter types
- Concentrated formula - one bottle treats 100 L/ up to 12 radiators
- BS 7593: 2019 Part L Compliant

### APPLICATION INSTRUCTIONS

- Everbuild P28 Filter Fluid should be dosed at 0.5 % of system volume (0.5 litres per 100 L of system water)
- Leave in system and MUST be used in conjunction with a Protector/Inhibitor chemical. We recommend the use of Everbuild P30 Protector.
- For open vented systems, add via the feed and expansion tank
- For sealed systems, add via towel rail or the in-line system filter

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

P28 Filter Fluid  
November 2021,  
Version 01.01  
020516020000000070

2 / 2



P28FilterFluid-en-GBEVER-(11-2021)-1-1.pdf

BUILDING TRUST

