Sikafloor®-1590/2650 Part A substrate

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-1590/2650 Part A substrate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Danger

Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.

	H360F	May damage fertility.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P201	Obtain special instructions before use.
P261	Avoid breathing mist or vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Reaction mass of isomers of epoxy resin BFDGE
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 --- specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 25 - < 40
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 603-103-00-4 01-2119485289-22-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 5 - < 10
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48-XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.

If symptoms persist, call a physician.

In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. irritant effects sensitising effects toxic effects for reproduction

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.
Further information on storage stability	:	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mix-

ing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	viscous liquid
Colour	:	colourless
Odour	:	epoxy-like
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic	:	ca. 3.470 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,49 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity
Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity	:	LD50 Oral (Rat): > 3.900 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,64 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): > 4.500 mg/kg

Skin corrosion/irritation
Causes skin irritation.

Serious eye damage/eye irritation
Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation
May cause an allergic skin reaction.

Respiratory sensitisation
Not classified due to lack of data.

Germ cell mutagenicity
Not classified due to lack of data.

Carcinogenicity
Not classified due to lack of data.

Reproductive toxicity
May damage fertility.

STOT - single exposure
Not classified due to lack of data.

STOT - repeated exposure
Not classified due to lack of data.

Aspiration hazard
Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties
Not classified due to lack of data.

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h

Reaction mass of isomers of epoxy resin BFDGE:

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h

12.2 Persistence and degradability
No data available

12.3 Bioaccumulative potential
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

Components:

bis(isopropyl)naphthalene:

Assessment : vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

14.2 UN proper shipping name

ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
IATA	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
IATA	:	9	

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)

IMDG

Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F

IATA (Cargo)

Packing instruction (cargo	:	964

aircraft)
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)
Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR
Environmentally hazardous : yes

IMDG
Marine pollutant : yes

IATA (Passenger)
Environmentally hazardous : yes

IATA (Cargo)
Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds	:	Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) Volatile organic compounds (VOC) content: 1,3% w/w no VOC duties Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 1,3% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:	:	Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.
Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.

H319	:	Causes serious eye irritation.
H360F	:	May damage fertility.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

Sikafloor®-1590/2650 Part A substrate

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN