

DECLARATION OF PERFORMANCE

Nr: 844008-0001

1. Identification Code : **SikaShield®P65 MG SA 4 mm 1,00/8m2**

2. Intended use:

| | |
|---------------------|--|
| EN13707:2009 | Reinforced flexible bitumen sheets for roof waterproofing |
|---------------------|--|

3. Manufacturer: **INDEX S.p.A. Via G.Rossini, 22 37060 Castel d'Azzano (Verona) Italia**

4. Authorised represent **NA**

5. System or systems of assesment and verification of constancy of performance of the construction product as set out in annex V:

| | |
|---------------------|----------------|
| EN13707:2009 | AVCP 2+ |
|---------------------|----------------|

6. Identification number of the notified body and related harmonised standard:

Concerning AVCP system 2+, the following notified body performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control:

BUREAU VERITAS (n° 1370 - FPC n° 1370-CPR-0040)


7. Declared performances:

| Standard: | Test | Standard | Performance |
|--------------|--|---------------------|---|
| EN13707:2009 | External Fire Performance | UNI EN 13501-5 | Froof |
| | Reaction To Fire | UNI EN 13501-1 | E |
| | Watertightness | UNI EN 1928 (B) | 60 kPa >= |
| | Tensile properties | UNI EN 12311-1 | L/T 850/700 N/5cm - 20 % (50-15)%/(50 -15)% |
| | Resistance to root penetration | UNI EN 13948 | NPD |
| | Resistance to static loading Meth A | UNI EN 12730 Met A | 20 kg >= |
| | Resistance to impact | UNI EN 12691 | NPD mm |
| | Resistance to tearing (nail shank) | UNI EN 12310-1 | L/T 200/200 N - 30 % |
| | Peel resistance of joints | UNI EN 12316-1 | 50 N/5cm -30 |
| | Shear resistance of joints | UNI EN 12317-1 | L/T 750/600 N/5cm -20% or out |
| | Flexibility at low temperature after ageing | EN 1296 e EN 1109 | NPD |
| | Flow resistance at elevated temperature after ageing | EN 1296 e EN 1110 | NPD |
| | Artificial ageing by long term exposure to UV ray | EN 1297 e EN 1850-1 | Si |
| | Flexibility at low temperature | UNI EN 1109 | -20 °C <= |
| | Flow resistance at elevated temperature | UNI EN 1110 | NPD |
| | Adhesion of granules | UNI EN 12039 | NPD |
| | Dangerous Substances | Sostanze pericolose | NPD |

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Salvatore Schirinzi (GM)



Castel d'Azzano 30/01/2025