According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-18 Pronto

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Acrylate coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Hazard statements H225 Highly flammable liquid and vapour. Causes skin irritation. H315 May cause an allergic skin reaction. H317 H335 May cause respiratory irritation. Precautionary statements Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P233 Keep container tightly closed. P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P370 + P378 In case of fire: Use dry sand, dry chemical or

Hazardous components which must be listed on the label:

methyl methacrylate 2-ethylhexyl acrylate tetramethylene dimethacrylate 2-(N-methyl-p-toluidino)ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

alcohol-resistant foam to extinguish.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
methyl methacrylate	80-62-6 201-297-1 01-2119452498-28- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 40 - < 60
2-ethylhexyl acrylate	103-11-7 203-080-7 01-2119453158-37- XXXX	Skin Irrit. 2; H315 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412	>= 5 - < 10
tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30- XXXX	Skin Sens. 1B; H317	>= 1 - < 2,5
2-(N-methyl-p-toluidino)ethanol	2842-44-6 220-638-5 01-2120827830-56- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Cough

Respiratory disorder Allergic reactions

Erythema **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Water

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod: :

ucts

Carbon dioxide (CO2) Carbon monoxide

No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition.

Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Revision Date: 13.09.2023

Advice on protection against :

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat,

ignition and direct sunlight.

Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store

in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further information: Indicative			
		STEL	100 ppm	2009/161/EU
		STEL	100 ppm	GB EH40
			416 mg/m3	
		TWA	50 ppm	GB EH40
			208 mg/m3	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid Colour : various

Odour : unpleasant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Melting point/range / Freezing : No data available

point

Boiling point/boiling range ca. 100 °C

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : Upper flammability limit

per flammability limit

12,5 %(V)

Lower explosion limit /

: Lower flammability limit

Lower flammability limit

0,8 %(V)

Flash point

: ca. 10 °C

Method: closed cup

Auto-ignition temperature

: ca. 245 °C

Decomposition temperature

: No data available

pН

Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic

: ca. 250 mPa.s (20 °C)

Viscosity, kinematic

 $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$

Solubility(ies)

Water solubility

insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure

: ca. 38,7 hPa

Density

: ca. 0,98 g/cm3 (20 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

methyl methacrylate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29,8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Country GB 000000124430

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

2-ethylhexyl acrylate:

Acute oral toxicity : LD50 Oral (Rat): 4.435 mg/kg

2-(N-methyl-p-toluidino)ethanol:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish : NOEC (Danio rerio (zebra fish)): 9,4 mg/l

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 69 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC: 37 mg/l Exposure time: 21 d

Method: OECD Test Guideline 202

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 37 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

2-ethylhexyl acrylate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,81 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,3 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: ErC50 (Desmodesmus subspicatus (green algae)): 1,71 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 1247

 IMDG
 : UN 1247

 IATA
 : UN 1247

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

14.2 UN proper shipping name

ADR : METHYL METHACRYLATE MONOMER, STABILIZED

IMDG : METHYL METHACRYLATE, MONOMER, STABILIZED

IATA : Methyl methacrylate monomer, stabilized

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 339
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 353

ger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

: Not applicable

Control of Major Accident Hazards Regulations P5c FLAMMABLE LIQUIDS

2015 (COMAH)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412

Full text of other abbreviations

Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

STOT SE Specific target organ toxicity - single exposure

Europe. COMMISSION DIRECTIVE 2009/161/EU establishing 2009/161/EU

a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

UK. EH40 WEL - Workplace Exposure Limits GB EH40

2009/161/EU / TWA Limit Value - eight hours 2009/161/EU / STEL Short term exposure limit

GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period) GB EH40 / STEL Short-term exposure limit (15-minute reference period) ADR

European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS Derived no-effect level DNEL

Half maximal effective concentration EC50

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikafloor®-18 Pronto

Date of last issue: 05.06.2023 Version 8.0 Print Date 29.02.2024

Revision Date: 13.09.2023

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method

Skin Sens. 1 H317 Calculation method STOT SE 3 H335 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN