

Date of last issue: 01.12.2023	Version 3.4	Print Date 29.02.2024
Revision Date: 19.12.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard[®]-63 N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1C	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341: Suspected of causing genetic defects.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikagard[®]-63 N Part A

-

Date of last issue: 01.12.2023 Revision Date: 19.12.2023	Ver	sion 3.4	Print Date 29.02.2024
Hazard pictograms :			
Signal word :	Danger		
Hazard statements :	H317 H341 H360F	Causes severe skin burns and ey May cause an allergic skin reaction Suspected of causing genetic def May damage fertility. Toxic to aquatic life with long last	on. fects.
Precautionary statements :	P273 P280	Obtain special instructions before Avoid release to the environment Wear protective gloves/ protective eye protection/ face protection.	
	P304 + P340 + P3 P305 + P351 + P3 P308 + P313	ately all contaminated clothing. R with water. 310 IF INHALED: Remove pers air and keep comfortable for brea mediately call a POISON CENTE 338 + P310 IF IN EYES: Rinse with water for several minutes. Re tact lenses, if present and easy to tinue rinsing. Immediately call a F CENTER/ doctor. IF exposed or concerned: Get me	inse skin son to fresh athing. Im- R/ doctor. cautiously emove con- o do. Con- POISON
		vice/ attention. Collect spillage.	

Hazardous components which must be listed on the label:

epoxy phenol novolac resin Trimethylolpropane triglycidylether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 01.12.2023	
Revision Date: 19.12.2023	

Version 3.4

Print Date 29.02.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
epoxy phenol novolac resin	28064-14-4 Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 40 - < 60
Trimethylolpropane triglycidylether	Not Assigned 701-135-4 01-2120078341-60- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 Repr. 1B; H360F Aquatic Chronic 2; H411	>= 10 - < 20
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	>= 5 - < 10
Substances with a workplace expos			
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 1 - < 2,5

For explanation of abbreviations see section 16.



Date of last issue: 01.12.2023 Revision Date: 19.12.2023 Version 3.4

Print Date 29.02.2024

SECTION 4: First aid measures

4.1 Description of first aid measures							
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.						
If inhaled	: Move to fresh air. Consult a physician after significant exposure.						
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.						
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. 						
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 						
4.2 Most important symptoms a	nd effects, both acute and delayed						
Symptoms	 Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. 						
Risks	: Health injuries may be delayed. corrosive effects sensitising effects toxic effects for reproduction						
	May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. May damage fertility. Causes severe burns.						



Date of last issue: 01.12.2023 Revision Date: 19.12.2023		Version 3.4	Print Date 29.02.202
4.3 Indication of any immediate n Treatment	neo	lical attention and special treatment needed	I
rreatment	•	Treat symptomatically.	
SECTION 5: Firefighting meas	ur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water je ide/sand/foam/alcohol resistant foam/chemica extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter of courses.	drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	n
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ning apparatus.
Further information	:	Collect contaminated fire extinguishing water	separately. This
		must not be discharged into drains. Fire residues and contaminated fire extinguish be disposed of in accordance with local regula	
SECTION 6: Accidental releas	e I	neasures	
6.1 Personal precautions, protect	tiv	e equipment and emergency procedures	
		Use personal protective equipment.	
		Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sev	
		If the product contaminates rivers and lakes o	r drains inform

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

respective authorities.

6.4 Reference to other sections

For personal protection see section 8.



Date of last issue: 01.12.2023 Revision Date: 19.12.2023 Version 3.4

Print Date 29.02.2024

SECTION 7: Handling and storage

7.1	Precautions for safe handling	9	
	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	incl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
------------	---------	----------------------------------	---------------------------	---------



Date of last issue: 01.12.2023Version 3.4Revision Date: 19.12.2023		3.4	Print Da	te 29.02.2024	
Titanium dioxide (> 10 μm)		13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
			TWA (Respirable dust)	4 mg/m3	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipme	nt
Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	 In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
	 Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure

Environmental exposure controls

	-
General	advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform



Print Date 29.02.2024

Sikagard[®]-63 N Part A

Date of last issue: 01.12.2023

Revision Date: 19.12.2023

		respective authorities.
SECTION 9: Physical and chei	mic	al properties
9.1 Information on basic physical	l an	d chemical properties
Physical state Colour	:	liquid various
Odour	:	epoxy-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	plosive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	ca. 115 °C Method: closed cup
Auto-ignition temperature	:	No data available
		No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble

Version 3.4

SAFETY DATA SHEET According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH

Regulations SI 2019/758



Sikagard[®]-63 N Part A

Date of last issue: 01.12.2023 Revision Date: 19.12.2023	Version 3.4	Print Date 29.02.2024
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,07 hPa	
	0,07 hPa	
Density	: ca. 1,52 g/cm3 (20 °C)	

Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: 01.12.2023
Revision Date: 19.12.2023

Version 3.4

Print Date 29.02.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

epoxy phenol novolac resin	:	
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

Trimethylolpropane triglycidylether:

Acute oral toxicity	:	LD50 Oral (Rat): 3.398 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Not classified based on available information.



Sikagard®-63 N Part A

Date of last issue: 01.12.2023 Revision Date: 19.12.2023	Version 3.4	Print Date 29.02.2024
Reproductive toxicity May damage fertility.		
STOT - single exposure Not classified based on available inform	nation.	
STOT - repeated exposure Not classified based on available inform	nation.	
Aspiration toxicity		

Not classified based on available information.

2

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Trimethylolpropane triglycidylether: Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l plants Exposure time: 72 h Toxicity to daphnia and other : EC50: 3,7 mg/l aquatic invertebrates (Chron-Exposure time: 48 d ic toxicity) Species: Daphnia magna (Water flea) benzyl alcohol: Toxicity to fish : LC50 (Fish): > 100 mg/l Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h aquatic invertebrates 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential No data available



Date of last issue: 01.12.2023 Revision Date: 19.12.2023		Version 3.4	Print Date 29.02.2024
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB a	assessmen	t	
Product:			
Assessment	to be very p	substance/mixture contains no con either persistent, bioaccumulative persistent and very bioaccumulative or higher	e and toxic (PBT), or
12.6 Endocrine disrupting prop	erties		
<u>Product:</u> Assessment	ered t REAC (EU) 2	ubstance/mixture does not contai o have endocrine disrupting prop CH Article 57(f) or Commission De 2017/2100 or Commission Regula of 0.1% or higher.	erties according to elegated regulation
12.7 Other adverse effects			
Product:			
Additional ecological infor- mation	unpro	vironmental hazard cannot be ex fessional handling or disposal. to aquatic life with long lasting ef	

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	 15 01 10* packaging containing residues of or contaminated by dangerous substances
Country GB 100000016524	12 / 17

Version 3.4



Print Date 29.02.2024

Sikagard[®]-63 N Part A

Date of last issue: 01.12.2023

Revision Date: 19.12.2023			Version 3.4	Finit Date 23.0
(CVSION Date: 13.12.2025				
SECTION 14: Transport infor	ma	tion		
14.1 UN number or ID number				
ADR	:	UN 1760		
IMDG	:	UN 1760		
ΙΑΤΑ	:	UN 1760		
14.2 UN proper shipping name				
ADR	:		LIQUID, N.O.S. opane triglycidylether)	
IMDG	:		LIQUID, N.O.S. opane triglycidylether)	
ΙΑΤΑ	:	Corrosive liqu (Trimethylolpr	id, n.o.s. opane triglycidylether)	
14.3 Transport hazard class(es)				
		Class	Subsidiary risks	
ADR	:	8		
IMDG	:	8		
ΙΑΤΑ	:	8		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III C9 80 8 (E)		
IMDG Packing group Labels EmS Code Remarks	: : :	III 8 F-A, S-B Alkalis		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	856 Y841 III Corrosive		

IATA (Passenger)



Date of last issue: 01.12.2023 Revision Date: 19.12.2023			Version 3.4	Print Date 29.02.2024
Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	852 Y841 III Corrosive		
14.5 Environmental hazards				
ADR Environmentally hazardous	:	yes		
IMDG Marine pollutant	:	yes		
IATA (Passenger) Environmentally hazardous	:	yes		
IATA (Cargo) Environmentally hazardous	:	yes		
14.6 Special precautions for use	r			

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	: Not applicable
Control of Major Accident Hazards Regulations E2 2015 (COMAH)	ENVIRONMENTAL HAZARDS
Volatile organic compounds : Law on the incentive t (VOCV)	ax for volatile organic compounds



Date of last issue: 01.12.2023 Revision Date: 19.12.2023	Version 3.4	Print Date 29.02.2024			
	Volatile organic compounds (VOC) content: 6,5% w/w				
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 6,5% w/w				
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.					
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	ation/legislation Health and Safety at Work Act 1974 & Subsidiary Regulations				
Other regulations:					

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 H314 H315 H317 H318 H319 H332 H341 H360F H411		Harmful if swallowed. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Suspected of causing genetic defects. May damage fertility. Toxic to aquatic life with long lasting effects.			
Full text of other abbreviations					
Acute Tox. Aquatic Chronic Eye Dam. Eye Irrit. Muta. Repr. Skin Corr. Skin Corr. Skin Irrit. Skin Sens. GB EH40 GB EH40 / TWA ADR		Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Germ cell mutagenicity Reproductive toxicity Skin corrosion Skin irritation Skin sensitisation UK. EH40 WEL - Workplace Exposure Limits Long-term exposure limit (8-hour TWA reference period) European Agreement concerning the International Carriage of			



Date of last issue: 01.12.2023 Revision Date: 19.12.2023		Version 3.4		Print Date 29.02.2024
CAS DNEL EC50 GHS IATA IMDG LD50 LC50	:	Dangerous Goods by Ro Chemical Abstracts Serv Derived no-effect level Half maximal effective co Globally Harmonized Sys International Air Transpo International Maritime Co Median lethal dosis (the a once, which causes the o test animals) Median lethal concentrati air that kills 50% of the te	ice Incentration Incentration Int Association Inde for Dangerous Goo Inde for Dangerous Goo Indeath of 50% (one half Indeath of 50% (one half	given all at) of a group of the chemical in
MARPOL	:	period) International Convention Ships, 1973 as modified		
OEL	:	Occupational Exposure Limit		
PBT PNEC	:	Persistent, bioaccumulati Predicted no effect conce		
REACH	:	Regulation (EC) No 1907 and of the Council of 18 l istration, Evaluation, Auth cals (REACH), establishi	7/2006 of the European December 2006 conce norisation and Restrict	erning the Reg- ion of Chemi-
SVHC	:	Substances of Very High		ould rigorioy
vPvB	:	Very persistent and very		
Further information				
Classification of the mixture	e:		Classification proce	dure:
Skin Corr. 1C	H314		Calculation method	
Eye Dam. 1	H3	18	Calculation method	
Skin Sens. 1	H317		Calculation method	
Muta. 2	H341		Calculation method	
Repr. 1B	H3	60F	Calculation method	
Aquatic Chronic 2	H4	11	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN

SAFETY DATA SHEET According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Sikagard[®]-63 N Part A

Date of last issue: 01.12.2023 Revision Date: 19.12.2023 Version 3.4

Print Date 29.02.2024

