

Date of last issue: 12.12.2023	Version 9.0	Print Date 10.09.2024
Revision Date: 17.01.2024		

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikasil<sup>®</sup> IG-25 HM Plus Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Catalyst for 2 Comp. sealants/adhesives., Sealing system

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	72/2008)
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through pro- longed or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)



Print Date 10.09.2024

# Sikasil<sup>®</sup> IG-25 HM Plus Part B

Date of last issue: 12.12.2023 Revision Date: 17.01.2024 Version 9.0

Hazard pictograms Signal word Danger ÷ Harmful if swallowed. Hazard statements H302 Causes skin irritation. H315 May cause an allergic skin reaction. H317 Causes serious eve damage. H318 Causes damage to organs through prolonged H372 or repeated exposure if inhaled. Harmful to aquatic life with long lasting ef-H412 fects. **Prevention:** Precautionary statements P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. **Response:** P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Get medical advice/ attention if you feel un-P314 well.

### Hazardous components which must be listed on the label:

4,4,7,7-tetraethoxy-3,8-dioxa-4,7-disiladecane N-[3-(triethoxysilyl)propyl]ethylenediamine

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 12.12.2023 Revision Date: 17.01.2024 Version 9.0

Print Date 10.09.2024

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
4,4,7,7-tetraethoxy-3,8-dioxa-4,7- disiladecane	16068-37-4 240-212-2 01-2120764364-51- XXXX	Acute Tox. 3; H301 Acute Tox. 4; H312 STOT RE 1; H372 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute oral toxicity: 161 mg/kg Acute dermal toxicity: 1.971 mg/kg	>= 20 - < 25
N-[3- (triethoxysi- lyl)propyl]ethylenediamine Contains: N,N'-bis[3- (triethoxysi- lyl)propyl]ethylenediamine >= 15 - <= 20 % di- aminoethylaminopropyltetraethox- ydisiloxane >= 3 - <= 5 %	5089-72-5 225-806-1 01-2120767929-30- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 10 - < 20
tetraethyl silicate	78-10-4 201-083-8 01-2119496195-28- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 10 - < 20
1,2-Bis(triethoxysilyl)ethene	87061-56-1 Not Assigned	Acute Tox. 3; H301 Acute Tox. 4; H312 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 161 mg/kg Acute dermal toxicity: 1.971 mg/kg	>= 2,5 - < 5



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	0	Print Date 10.09.2024
bis(ethyl acetoacetato- O1',O3)bis(2-methylpropan-1- olato)titanium Contains: 2-methylpropan-1-ol <= 2 %	83877-91-2 281-161-6 01-2119968551-31- XXXX	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) STOT SE 3; H336 (Central nervous system)	>= 1 - < 2,5
Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane	93925-42-9 300-344-4 01-2119560586-30- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Chronic 3; H412	>= 0,25 - < 0,3
		specific concentration limit Repr. 1B; H360FD >= 0,6 % Muta. 2; H341 >= 2 % STOT SE 1; H370 >= 20 % STOT SE 2; H371 >= 2 % STOT RE 1; H372 >= 20 %	
For explonation of obbrouistions a	as sostion 16	STOT RE 2; H373 >= 2 % Acute toxicity esti- mate Acute oral toxicity: 1.000 mg/kg	

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice

: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.



e of last issue: 12.12.2023 ision Date: 17.01.2024		Version 9.0	Print Date 10.09.2
If inhaled		ve to fresh air. Isult a physician after significant expo	sure.
In case of skin contact	Wa	e off contaminated clothing and shoe sh off with soap and plenty of water. /mptoms persist, call a physician.	s immediately.
In case of eye contact	sue In ti of v Cor Rer	all amounts splashed into eyes can ca damage and blindness. The case of contact with eyes, rinse im vater and seek medical advice. Thinue rinsing eyes during transport to nove contact lenses. The eye wide open while rinsing.	mediately with plenty
If swallowed	Rin Do	not induce vomiting without medical a se mouth with water. not give milk or alcoholic beverages. rer give anything by mouth to an unco	
Most important symptoms	and effect	s, both acute and delayed	
Symptoms	Alle	strointestinal discomfort rgic reactions essive lachrymation	
	Ery Der See	matitis Section 11 for more detailed informa symptoms.	ation on health effects
Risks	Ery Der See and : irrita	matitis Section 11 for more detailed informa	ation on health effects
Risks	Ery Der See and : irrita sen Har Cau May Cau	matitis Section 11 for more detailed informa symptoms. ant effects	
	Ery Der See and : irrita sen Har Cau May Cau Cau exp	matitis e Section 11 for more detailed informa symptoms. ant effects sitising effects mful if swallowed. uses skin irritation. / cause an allergic skin reaction. uses serious eye damage. uses damage to organs through prolou	nged or repeated

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for



	Version 9.0	Print Date 10.09.2024
	extinction.	
the	e substance or mixture	
:	No hazardous combustion products are known	
:	In the event of fire, wear self-contained breathing	apparatus.
:	Standard procedure for chemical fires.	
se r	neasures	
	:	extinction.  the substance or mixture  No hazardous combustion products are known  In the event of fire, wear self-contained breathing

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

#### **6.2 Environmental precautions**

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform
		respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel,
	acid binder, universal binder, sawdust).
	Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
		Do not get in eyes, on skin, or on clothing.
		For personal protection see section 8.
		Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
		Smoking, eating and drinking should be prohibited in the application area.



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024
	Follow standard hygiene measures products	when handling chemical
Advice on protection against : fire and explosion	Normal measures for preventive fire	protection.
Hygiene measures :	Handle in accordance with good ind practice. When using do not eat or c smoke. Wash hands before breaks a	drink. When using do not
7.2 Conditions for safe storage, in	luding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dr place. Store in accordance with loca	
Further information on stor- : age stability	No decomposition if stored and appl	lied as directed.
7.3 Specific end use(s)		
Specific use(s)	Consult most current local Product I use.	Data Sheet prior to any

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
tetraethyl silicate	78-10-4	TWA	5 ppm 44 mg/m3	2017/164/EU
	Further infor	mation: Indicative		
		TWA	5 ppm 44 mg/m3	GB EH40
	Further information: Where no specific short-term expose listed, a figure three times the long-term exposure limit sused.			

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
ethanol	64-17-5	TWA	1.000 ppm	GB EH40
			1.920 mg/m3	
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

\*The above mentioned values are in accordance with the legislation in effect at the date of the re-



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024

lease of this safety data sheet.

# 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipmen	t
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure contr	ols
General advice	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024
Physical state Appearance Colour	: solid : paste : dark grey, black	
Odour	: very faint	
Melting point/range / Freezing point	: No data available	
Boiling point/boiling range	: No data available	
Flammability (solid, gas)	: No data available	
Upper/lower flammability or	explosive limits	
Upper explosion limit / Up- per flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: Not applicable	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 8 - 10 Concentration: 100 %	
Viscosity		
Viscosity, dynamic	: ca. 500.000 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: No data available	
Partition coefficient: n- octanol/water	: No data available	



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,08 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
<b>9.2 Other information</b> Flammable solids Burning rate	: > 120 s Method: UN-Test N1	

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

# 10.5 Incompatible materials

Materials to avoid : No data available

### **10.6 Hazardous decomposition products**

Hazardous decomposition : ethanol products

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Harmful if swallowed.



sion Date: 17.01.2024	Version 9.0	Print Date 10.09
Components:		
4,4,7,7-tetraethoxy-3,8-dio	(a-4,7-disiladecane:	
Acute oral toxicity	: LD50 Oral (Rat): 161 mg/kg	
	Acute toxicity estimate: 161 mg/kg Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rat): 1.971 mg/kg	
	Acute toxicity estimate: 1.971 mg/kg Method: Calculation method	
1,2-Bis(triethoxysilyl)ether	e:	
Acute oral toxicity	: LD50 Oral (Rat): 161 mg/kg	
	Acute toxicity estimate: 161 mg/kg Method: Calculation method	
Acute inhalation toxicity	: Assessment: Corrosive to the respira	atory tract.
Acute dermal toxicity	: LD50 Dermal (Rat): 1.971 mg/kg	
	Acute toxicity estimate: 1.971 mg/kg Method: Calculation method	
Silicic acid (H4SiO4), tetra Acute oral toxicity	ethyl ester, reaction products with bis(ad : LD50 Oral (Rat): 1.000 mg/kg	cetyloxy)dibutylstannane:
	Acute toxicity estimate: 1.000 mg/kg Method: Calculation method	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye ir Causes serious eye damage		
Respiratory or skin sensiti	sation	
<b>Skin sensitisation</b> May cause an allergic skin re	eaction.	
Respiratory sensitisation Not classified due to lack of	data.	
Germ cell mutagenicity Not classified due to lack of		



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024
<b>Carcinogenicity</b> Not classified due to lack of data.		
<b>Reproductive toxicity</b> Not classified due to lack of data.		
STOT - single exposure		
Not classified due to lack of data.		

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

Not classified due to lack of data.

### **11.2 Information on other hazards**

#### **Endocrine disrupting properties**

#### Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

#### Components:

## N-[3-(triethoxysilyl)propyl]ethylenediamine:

Toxicity to fish (Chronic toxicity) : LC50: 597 mg/l Exposure time: 96 h Species: Danio rerio (zebra fish)

1

#### 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment

: This substance/mixture contains no components considered



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.2024
	to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	
12.6 Endocrine disrupting properti	es	
Product:		
Assessment :	The substance/mixture does not contain compor ered to have endocrine disrupting properties acc REACH Article 57(f) or Commission Delegated r (EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	cording to regulation
12.7 Other adverse effects		
<u>Product:</u> Additional ecological infor- : mation	An environmental hazard cannot be excluded in unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.	the event of

# **SECTION 13: Disposal considerations**

13.1 Waste treatmer	nt methods	
Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste	e Catalogue :	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated pa	ackaging :	15 01 10* packaging containing residues of or contaminated by dangerous substances

# **SECTION 14: Transport information**

### 14.1 UN number or ID number



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0	Print Date 10.09.202
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.2 UN proper shipping nar	ne	
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class	(es)	
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards		
Not regulated as a dange	rous good	
14.6 Special precautions for Not applicable	user	
14.7 Maritime transport in but Not applicable for product	ulk according to IMO instruments t as supplied.	

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Version 9.0		Print Date 10.09.2024	
International Chemical Weapons Schedules of Toxic Chemicals ar		Not applicable		
Regulation (EC) No 1005/2009 o plete the ozone layer	n substances that de- :	Not applicable		
UK REACH List of substances so (Annex XIV)	ubject to authorisation :	Not applicable		
GB Export and import of hazardous chemicals - Prior : Not applicable Informed Consent (PIC) Regulation				
Control of Major Accident Hazard 2015 (COMAH)	ds Regulations No	t applicable		
Volatile organic compounds :	<ul> <li>Law on the incentive tax for volatile organic compounds (VOCV)</li> <li>Volatile organic compounds (VOC) content: &lt; 0% w/w no VOC duties</li> </ul>			
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0% w/w			
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.				
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	<ul> <li>Environmental Protection Act 1990 &amp; Subsidiary Regulations Health and Safety at Work Act 1974 &amp; Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.</li> </ul>			

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

## Full text of H-Statements

H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.



Date of last issue: 12.12.2023
Revision Date: 17.01.2024

Version 9.0

Print Date 10.09.2024

evision Date: 17.01.2024		
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H341	:	Suspected of causing genetic defects.
H360FD	:	May damage fertility. May damage the unborn child.
H370	:	Causes damage to organs.
H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
H372		Causes damage to organs through prolonged or repeated
11372	•	exposure if swallowed.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Muta.	:	Germ cell mutagenicity
Repr.	÷	Reproductive toxicity
Skin Irrit.		Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a
2017/104/20	•	fourth list of indicative occupational exposure limit values
GB EH40		UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / TWA	:	Limit Value - eight hours
	÷	
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
ADR	·	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
LD30	•	once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
Country GB 00000603036		16 / 17



Date of last issue: 12.12.2023 Revision Date: 17.01.2024	Vers	Version 9.0			
REACH	and of the Council istration, Evaluatio	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency			
SVHC		Substances of Very High Concern			
vPvB		Very persistent and very bioaccumulative			
Further information Classification of the mixt	ure:	Classification proce	dure:		
Acute Tox. 4	H302	Calculation method			
Skin Irrit. 2	H315	Calculation method			
Eye Dam. 1	H318	Calculation method			
Skin Sens. 1	H317	Calculation method			
STOT RE 1	H372	Calculation method			
Aquatic Chronic 3	H412	Calculation method			

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN