

DECLARATION OF CONFORMITY

Nr: 844026-0001

According To



1. Identification Code : SikaShield®P65 MG 4mm 1,00/8m2

2. Intended use:

EN 13707:2004+A2:2009	Reinforced flexible bitumen sheets for roof waterproofing
-----------------------	---

3. Manufacturer: INDEX S.p.A. Via G.Rossini, 22 37060 Castel d'Azzano (Verona) Italia

4. Authorised represent NA

5. System or systems of assesment and verification of constancy of performance of the construction product as set out in annex V:

EN 13707:2004+A2:2009	AVCP 2+
-----------------------	---------

6. Identification number of the approved body and related harmonised standard:

Concerning AVCP system 2+, the following approved body performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control:
EN 13707 UK 0836-CPR-21/F530

7. Declared performances:


Standard:	Test	Standard	Performance
EN 13707:2004+A2:2009	External Fire Performance	UNI EN 13501-5	Roof
	Reaction To Fire	UNI EN 13501-1	E
	Watertightness	UNI EN 1928 (B)	60 kPa >=
	Tensile properties	UNI EN 12311-1	L/T 850/700 N/5cm - 20 % (50-15)%/(50 -15)%
	Resistance to root penetration	UNI EN 13948	NPD
	Resistance to static loading Meth A	UNI EN 12730 Met A	20 kg >=
	Resistance to impact	UNI EN 12691	1250 mm >=
	Resistance to tearing (nail shank)	UNI EN 12310-1	L/T 200/200 N - 30 %
	Peel resistance of joints	UNI EN 12316-1	50 N/5cm -30
	Shear resistance of joints	UNI EN 12317-1	L/T 750/600 N/5cm -20% or out
	Flexibility at low temperature after ageing	EN 1296 e EN 1109	-20 °C ± 5°
	Flow resistance at elevated temperature after ageing	EN 1296 e EN 1110	140 °C -10°C
	Artificial ageing by long term exposure to UV ray	EN 1297 e EN 1850-1	Si
	Flexibility at low temperature	UNI EN 1109	-20 °C <=
	Flow resistance at elevated temperature	UNI EN 1110	140 °C >=
	Adhesion of granules	UNI EN 12039	NPD
	Dangerous Substances	Sostanze pericolose	Nota A

Nota A This Product does not contain asbestos or tar constituents. In the absence of a uniform test method throughout Europe, any verifications and declarations on release/content must be performed considering the national regulations of the place of use.

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with EU Exit Regulation 2020, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Salvatore Schirinzi (GM)



Castel d'Azzano 30/01/2025