





Attestation

LEED v4 and v4.1 BETA

Sika AnchorFix®-2+

supplied by

Sika Services AG

The sample of sealant was supplied to Eurofins Product Testing A/S on the 22nd of December 2023 (VOC Emission) and the 5th of October 2022 (VOC Content). The sample was supplied as being representative of the manufactured product, and it has been tested in accordance with the relevant ISO 16000, EN 16516, and ASTM D2369 testing standards (See test report no. 392-2023-00603409_A_EN and no. 392-2022-00438610_XG_EN).

The test results of the tested sample indicate that the product qualifies for LEED v4 and LEED v4.1 BETA (February 2024) projects outside the US by showing compliance with the specifications for VOC emissions and VOC content by complying with:

VOC emissions specifications in LEED EQ credit "Low-Emitting Materials" for LEED projects outside the US:

- The requirements of LEED v4.1 BETA (February 2024) by not exceeding the LCI values mentioned in the German AgBB Testing and Evaluation Scheme (2018), showing an overall R-value below or equal to 1 and having a TVOC according to EN 16516 below or equal to 1,000 μg/m³, a sum of VOC without LCI less than 100 μg/m³ and a formaldehyde emission below or equal to 10 μg/m³; all after 28 days.
- The requirements of LEED v4 by complying with:
 - o The requirements of Indoor Air Comfort Gold version 9.0 (June 2023).

VOC content specifications in LEED EQ credit "Low-Emitting Materials" for LEED projects globally:

• The requirements of LEED v4 and LEED v4.1 BETA (February 2024): South Coast Air Quality Management District (SCAQMD) Rule 1168 (2017) for 'Multi-Purpose Construction Adhesive' having a VOC content below 70 g/L.

22 May 2025

Rasmus Verdier
Analytical Service Manager

LEED® is the preeminent program for the design, construction, maintenance and operations of high-performance green buildings. USGBC® and the related logo are trademarks owned by the U.S. Green Building Council and are used with permission.