





## PRODUCT DATA SHEET

# **EVERBUILD®** American Duct Tape

100 % Waterproof Multi-use Duct Tape with double strength adhesive

## PRODUCT DESCRIPTION

EVERBUILD® American Duct Tape is a remarkable tape which is not only thick, strong and 100 % waterproof; it also has the most amazing adhesive quality. It will stick to most surfaces and substrates and can be used internally as well as externally.

## **USES**

EVERBUILD® American Duct Tape has a multitude of uses including waterproofing and windproofing scaffolding, windows, doors and exposed roofing – it can also be used on vertical and overhead applications due to its unique hold strength. You can also use EVERBUILD® American Duct Tape to temporarily hold DPM, timber, guttering, sheet material or any other building material that needs to be held in place without the need to clamp.

## **CHARACTERISTICS / ADVANTAGES**

- Will stick to most common surfaces including polythene.
- Stronger than standard Gaffa tapes.
- Waterproof.

## **PRODUCT INFORMATION**

Chemical Base	PVC tape
Packaging	50 mm x 25 m rolls
Appearance / Colour	Silver, Orange
Shelf Life	36 months from date of manufacture.
Storage Conditions	Store in cool dry conditions between +5 °C and +25 °C. Safe in normal use however as a precaution keep polythene outer packaging away from children.
Thickness	0.26 mm
TECHNICAL INFORMATION	
Tensile Strength	42 N/cm

8.76 N/cm Steel

-10 °C to +93 °C

#### Product Data Sheet

Adhesion in peel

Service Temperature

**EVERBUILD®** American Duct Tape August 2022, Version 02.01 020514080000000024

## **VALUE BASE**

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### **LIMITATIONS**

- Do not use on surfaces that bleed oils or plasticisers
- It is the user's responsibility to determine suitability for use. If in doubt contact technical services for advice

## **ECOLOGY, HEALTH AND SAFETY**

## APPLICATION INSTRUCTIONS

#### SUBSTRATE PREPARATION

Ensure surfaces to which tape is to be applied are clean sound and dry.

#### **APPLICATION METHOD / TOOLS**

Remove outer packaging from roll of tape. Peel required amount of tape from roll pressing firmly into place while unrolling. Tear off or cut with a knife when finished.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### **EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds, LS9 0SW Tel: 0113 240 3456 Web: www.everbuild.co.uk Twitter: @everbuild

#### SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet EVERBUILD® American Duct Tape August 2022, Version 02.01 020514080000000024



