

SikaCeram[®]-282 Fibre Reinforced

DECLARATION OF PERFORMANCE No. 14100322

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	14100322
2	INTENDED USE/S	Fast setting, highly Deformable cementitious adhesive for internal & external tiling
3	MANUFACTURER:	Sika Limited, Watchmead, Welwyn Garden City, AL7 1BQ, UK
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	3
6a	DESIGNATED STANDARD:	BS EN 12004:2007 + A1:2012
	Approved body/ies:	1289

Declaration of Performance

SikaCeram[®]-282 Fibre Reinforced

14100322

2023/01, ver. 02

1008

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Initial tensile adhesion strength	>1.0 N/mm ²		BS EN 12004: 2007 + A1:2012
Tensile strength after 30 minutes open time	> 0.5 N/mm ²		
Tensile adhesion strength after heat aging	>1.0 N/mm ²		
Tensile adhesion strength after freeze thaw cycles	>1.0 N/mm ²		
Tensile adhesion strength after water immersion	>1.0 N/mm ²		
Reaction to fire	NPD		
Early tensile adhesion strength	> 0.5 N/mm ²		
Deformable	>5.0 mm		
Release of dangerous substances	See sds		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 30 January 2023

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 30 January 2023

End of information as required by UKNI

Declaration of Performance

SikaCeram®-282 Fibre Reinforced
14100322
2023/01, ver. 02
1008



Sika Limited, Welwyn Garden City, UK

DoP No. 14100322

BS EN 12004:2007 + A1:2012

Approved Body 1289

Fast setting, highly Deformable cementitious adhesive for internal & external tiling

Initial tensile adhesion strength	>1.0 N/mm ²
Tensile strength after 30 minutes open time	> 0.5 N/mm ²
Tensile adhesion strength after heat aging	>1.0 N/mm ²
Tensile adhesion strength after freeze thaw cycles	>1.0 N/mm ²
Tensile adhesion strength after water immersion	>1.0 N/mm ²
Reaction to fire	NPD
Early tensile adhesion strength	> 0.5 N/mm ²
Deformable	>5.0 mm
Release of dangerous substances	See sds

everbuild.co.uk

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaCeram®-282 Fibre Reinforced
14100322
2023/01, ver. 02
1008

Declaration of Performance

SikaCeram®-282 Fibre Reinforced
14100322
2023/01 , ver. 02
1008

