

Date of last issue: 24.01.2023	Version 3.2	Print Date 29.02.2024
Revision Date: 29.01.2024		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD FIX & FILL Expanding Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person	:	EHS@uk.sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.



Date of last issue: 24.01.2023 Revision Date: 29.01.2024		Version 3.2	Print Date 29.02.2024
Specific target organ toxicity - r exposure, Category 2	epeated	H373: May cause damage to longed or repeated exposure	
Long-term (chronic) aquatic ha: egory 4	zard, Cat-	H413: May cause long lasting aquatic life.	harmful effects to
2.2 Label elements			
Labelling (REGULATION (EC) Hazard pictograms :	No 1272/200		
Signal word :	Danger		
Hazard statements :	H222 H229 H315 H317 H319 H334 H351 H362 H373 H413	Extremely flammable and Pressurised container: Causes skin irritation. May cause an allergic s Causes serious eye irrit May cause allergy or as breathing difficulties if in May cause respiratory i Suspected of causing c May cause harm to brea May cause damage to or longed or repeated exp May cause long lasting aquatic life.	May burst if heated. skin reaction. tation. sthma symptoms or hhaled. rritation. ancer. ast-fed children. organs through pro- osure if inhaled.
Precautionary statements :	P101 P102	If medical advice is nee container or label at ha Keep out of reach of ch	nd.
	Prevention		
	P202 P210	Do not handle until all s have been read and un Keep away from heat, h open flames and other	derstood. not surfaces, sparks,
	P211	smoking. Do not spray on an ope tion source.	n flame or other igni-
	P251	Do not pierce or burn, e	even after use.
	P260	Do not breathe dust or	
	P263	Avoid contact during pro nursing.	
	P271	Use only outdoors or in ea.	a well-ventilated ar-
	P280	Wear protective gloves/	/ protective clothing/



Date of last issue: 24.01.2023 Revision Date: 29.01.2024	V	ersion 3.2	Print Date 29.02.2024
		eye protection/ face protection.	
	Response:		
	P304 + P340 +	P312 IF INHALED: Remove pe air and keep comfortable for bre POISON CENTER/ doctor if you	eathing. Call a
	P342 + P311	If experiencing respiratory symp POISON CENTER/ doctor.	otoms: Call a
	Storage:		
	P405 P410 + P412	Store locked up. Protect from sunlight. Do not ex peratures exceeding 50 °C/ 122	
	Disposal:		
	P501	Dispose of contents/container in with local regulation.	n accordance

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues alkanes, C14-17, chloro

Additional Labelling

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 24.01.2023	
Revision Date: 29.01.2024	

Version 3.2

Print Date 29.02.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 10 - < 20
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1A; H220	>= 10 - < 20



Date of last issue: 24.01.2023 Revision Date: 29.01.2024 Version 3.2

Print Date 29.02.2024

alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33- XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066	>= 5 - < 10
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1A; H220	>= 2,5 - < 5
Reaction products of phosphoryl trichloride and methyloxirane	1244733-77-4 807-935-0 01-2119486772-26- XXXX	Acute Tox. 4; H302 Aquatic Chronic 3; H412	>= 1 - < 2,5
		Acute toxicity esti- mate	
		Acute oral toxicity: 630 mg/kg	
Substances with a workplace expo	osure limit :		
dimethyl ether	115-10-6 204-065-8 01-2119472128-37- XXXX	Flam. Gas 1A; H220	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.



Date of last issue: 24.01.2023 Revision Date: 29.01.2024	Version 3.2	Print Date 29.02.2024
If swallowed	 Do not induce vomiting without medical advice Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscio 	
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms	 Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information of and symptoms. 	on health effects
Risks	 irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breaties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through prolong exposure if inhaled. 	-
4.3 Indication of any immediate m	edical attention and special treatment needed	
Treatment	Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Water spray jet Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : Carbon dioxide (CO2)



Date of last issue: 24.01.2023 Revision Date: 29.01.2024	Version 3.2	Print Date 29.02.2024
ucts	Carbon monoxide Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Chlorine compounds	
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-contained brea	athing apparatus.
Further information	: Use water spray to cool unopened contained	ers.
SECTION 6: Accidental releas	e measures ive equipment and emergency procedures	
6.1 Personal precautions, protect Personal precautions	ive equipment and emergency procedures : Use personal protective equipment.	
6.1 Personal precautions, protect	ive equipment and emergency procedures : Use personal protective equipment.	
 6.1 Personal precautions, protect Personal precautions 6.2 Environmental precautions 	 ive equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary s If the product contaminates rivers and lakes respective authorities. 	
 6.1 Personal precautions, protect Personal precautions 6.2 Environmental precautions Environmental precautions 	 ive equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary s If the product contaminates rivers and lakes respective authorities. 	s or drains inform
 6.1 Personal precautions, protect Personal precautions 6.2 Environmental precautions Environmental precautions 6.3 Methods and material for con 	 ive equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary s If the product contaminates rivers and lakes respective authorities. tainment and cleaning up Allow to solidify, use mechanical handling e 	s or drains inform

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
		Do not get in eyes, on skin, or on clothing.
		For personal protection see section 8.
		Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
		Smoking, eating and drinking should be prohibited in the application area.
		Take precautionary measures against static discharge.
		Open drum carefully as content may be under pressure.
		Follow standard hygiene measures when handling chemical



_

Date of last issue: 24.01.2023 Revision Date: 29.01.2024	Version 3.2	Print Date 29.02.2024
	products	
Advice on protection against fire and explosion	Keep away from heat/ sparks/ open flames smoking. Do not spray on a naked flame or material. Take precautionary measures aga discharges.	r any incandescent
Hygiene measures	 Handle in accordance with good industrial l practice. When using do not eat or drink. W smoke. Wash hands before breaks and at t 	/hen using do not
7.2 Conditions for safe storage, ir	cluding any incompatibilities	
Requirements for storage areas and containers	 BEWARE: Aerosol is pressurized. Keep aw exposure and temperatures over 50 °C. Do or throw into fire even after use. Do not spr red-hot objects. Store in original container. tightly closed in a dry and well-ventilated pl precautions. Store in accordance with local 	o not open by force ay on flames or Keep container ace. Observe label
Further information on stor- age stability	No decomposition if stored and applied as	directed.
7.3 Specific end use(s)		
Specific use(s)	 Cleaning with aprotic polar solvents must b Consult most current local Product Data Sh use. 	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	GB EH40
	Further information	ation: Capable of ca	ausing occupation	al asthma.
		STEL	0,07 mg/m3 (NCO)	GB EH40
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further informa	ation: Indicative		
		TWA	400 ppm 766 mg/m3	GB EH40
		STEL	500 ppm 958 mg/m3	GB EH40



Date of last issue: 24.01.2023	Version 3.2	Print Date 29.02.2024
Revision Date: 29.01.2024		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Environmental exposure cont	ols
General advice	Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform



Date of last issue: 24.01.2023	
Revision Date: 29.01.2024	

Version 3.2

Print Date 29.02.2024

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	aerosol various
Odour	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	Extremely flammable aerosol.
		le cive limite
Upper/lower flammability or e Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture reacts with water
Viscosity Viscosity, kinematic	:	Not applicable
Salubilitu/iaa)		

Solubility(ies)

Water solubility : No data available

:

No data available

10/20



Date of last issue: 24.01.2023 Revision Date: 29.01.2024	Version 3.2	Print Date 29.02.2024
octanol/water		
Vapour pressure	: 5100 hPa	
Density	: ca. 0,95 g/cm3 (23 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information No data available		

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.



of last issue: 24.01.2023 sion Date: 29.01.2024		Version 3.2	Print Date 29.02.20
Components:			
Diphenylmethanediisocyan	ate, iso	meres and homologues:	
Acute oral toxicity	: LC	050 Oral (Rat): > 10.000 mg/kg	
Acute inhalation toxicity	Ex Te Me As	250: 1,5 mg/l posure time: 4 h est atmosphere: dust/mist ethod: Expert judgement sessment: The component/mixture is ort term inhalation.	s moderately toxic after
Acute dermal toxicity	: LC	950 Dermal (Rabbit): > 9.400 mg/kg	
Reaction products of phos	phoryl t	richloride and methyloxirane:	
Acute oral toxicity		050 Oral (Rat): > 630 mg/kg	
		ute toxicity estimate: 630 mg/kg ethod: Calculation method	
Acute inhalation toxicity	Ex	50 (Rat): > 7 mg/l posure time: 4 h st atmosphere: dust/mist	
Acute dermal toxicity	: LC	050 Dermal (Rabbit): > 5.000 mg/kg	
Skin corrosion/irritation			
Causes skin irritation.			
Components:			
alkanes, C14-17, chloro:			
Assessment	: Re	epeated exposure may cause skin dr	yness or cracking.
Serious eye damage/eye iri			
Causes serious eye irritation.			
Respiratory or skin sensitis	sation		
Skin sensitisation May cause an allergic skin re	action.		
Respiratory sensitisation			
May cause allergy or asthma	sympto	ms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified based on availa	able info	rmation.	
Carcinogenicity			
Suspected of causing cancer			



Date of last issue: 24.01.2023	
Revision Date: 29.01.2024	

Version 3.2

Print Date 29.02.2024

Reproductive toxicity

May cause harm to breast-fed children.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
	G ()

SECTION 12: Ecological information

12.1 Toxicity

Product:		
Ecotoxicology Assessment		Man anna la stins hannful affacta ta sociatia lifa
Chronic aquatic toxicity	:	May cause long lasting harmful effects to aquatic life.
Components:		
Diphenylmethanediisocyana	ate,	isomeres and homologues:
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
		Exposure time: 72 h
alkanes, C14-17, chloro:		
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	10



Date of last issue: 24.01.2023 Revision Date: 29.01.2024	Version 3.2	Print Date 29.02.2024
Reaction products of phosphere	oryl trichloride and methyloxirane:	
Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (gr Exposure time: 72 h Method: OECD Test Guideline 201	een algae)): 82 mg/l
	NOEC (Pseudokirchneriella subcapitata (g mg/l Exposure time: 72 h Method: OECD Test Guideline 201	reen algae)): 13
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	NOEC: 32 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202	
12.2 Persistence and degradability No data available	,	
12.3 Bioaccumulative potential No data available		
12.4 Mobility in soil No data available		
12.5 Results of PBT and vPvB ass	essment	
Product: Assessment :	This substance/mixture contains componen be either persistent, bioaccumulative and to persistent and very bioaccumulative (vPvB	oxic (PBT), or very
12.6 Endocrine disrupting propert	es	
Product:		
Assessment	The substance/mixture does not contain co ered to have endocrine disrupting propertie REACH Article 57(f) or Commission Delega (EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.	es according to according to
12.7 Other adverse effects		
Product: Additional ecological infor- mation	An environmental hazard cannot be exclud unprofessional handling or disposal. May cause long lasting harmful effects to a	



Date of last issue: 24.01.2023	Version 3.2	Print Date 29.02.2024
Revision Date: 29.01.2024		

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0,072 100-year global warming potential: 0,02 500-year global warming potential: 0,006 Atmospheric lifetime: 0,036 yr Radiative efficiency: 0 Wm2ppb Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	16 05 04* gases in pressure containers (including halons) containing dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1950
IMDG	:	UN 1950
ΙΑΤΑ	:	UN 1950

14.2 UN proper shipping name



evision Date: 29.01.2023		Version 3.2	Print Date 29.02.2024
ADR	: AEROSO	LS	
IMDG	: AEROSO		
ΙΑΤΑ		flammable	
14.3 Transport hazard class(es)			
	Class	Subsidiary risks	
ADR	: 2	2.1	
IMDG	: 2.1		
ΙΑΤΑ	: 2.1		
14.4 Packing group			
ADR Packing group Classification Code Labels Tunnel restriction code	: Not assign : 5F : 2.1 : (D)	ned by regulation	
IMDG Packing group Labels EmS Code	: Not assign : 2.1 : F-D, S-U	ned by regulation	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 203 : Y203 : Not assigi : Flammabl	ned by regulation e Gas	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 203 : Y203 : Not assigi : Flammabl	ned by regulation e Gas	
14.5 Environmental hazards			
ADR Environmentally hazardous	: no		
IMDG Marine pollutant	: no		
IATA (Passenger) Environmentally hazardous	: no		
IATA (Cargo) Environmentally hazardous	: no		



Date of last issue: 24.01.2023	Version 3.2	Print Date 29.02.2024
Revision Date: 29.01.2024		

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the fol- lowing entries should be considered: Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 56)	
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable	
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable	
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	: Not applicable	
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable	
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable	
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	: Not applicable	
Control of Major Accident Hazards Regulations P3a	FLAMMABLE AEROSOLS	
(VOCV)	ax for volatile organic compounds ounds (VOC) content: 23,9% w/w	



Date of last issue: 24.01.2023	Version 3.2	Print Date 29.02.2024
Revision Date: 29.01.2024		

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 23,9% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation
 specific for the substance or mixture:
 Environmental Protection Act 1990 & Subsidiary Regulations
 Control of Substances Hazardous to Health Regulations
 (COSHH)
 May be subject to the Control of Major Accident Hazards
 Regulations (COMAH), and amendments.

Other regulations:

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H362	:	May cause harm to breast-fed children.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	
Flam. Gas	:	
Lact.	:	Effects on or via lactation



Date of last issue: 24.01.2023
Revision Date: 29.01.2024

Version 3.2

Print Date 29.02.2024

Deen Orne	Description equilibrium
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first
	list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)
ADR	: European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative
··· · ·	

Further information

Classification of the mixture:		Classification procedure:	
Aerosol 1	H222, H229	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Carc. 2	H351	Calculation method	
Lact.	H362	Calculation method	



Date of last issue: 24.01.2023 Revision Date: 29.01.2024		Version 3.2	Print Date 29.02.2024
STOT SE 3	H335	Calculation method	
STOT RE 2	H373	Calculation method	
Aquatic Chronic 4	H413	Based on product da	ata or assessment

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN