

Sika MonoTop®-4052

Declaration of Performance No 79593779

1	Unique identification code of the product-type:	79593779
2	Intended use/es:	All other uses — Cementitious screed material For internal uses subject to reaction to fire regulations — Cementitious screed material
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 4 (All other uses) System 3 (For internal uses subject to reaction to fire regulations)
6a	Harmonised standard:	EN 13813:2002
	Notified body/ies:	1139

Declaration of Performance

Sika MonoTop®-4052

79593779

07/02/2024 2

1029

7 Declared performance/s:			
Essential Characteristics	Performance		AVCP
			Harmonised Technical Specification
Chemical resistance	NPD		System 4
Mechanical resistance	Wear resistance (Boehme)	A15	System 4
	Flexural strength	F10	
	Compressive strength	C60	
Reaction to fire	Class A1 _{fl}		System 3
Release of corrosive substances	NPD		System 4
Sound absorption	NPD		System 4
Sound insulation	NPD		System 4
Thermal resistance	NPD		System 4
Water permeability	NPD		System 4
Water vapour permeability	NPD		System 4

EN 13813:2002

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski	Name: Wiktor Karpala
Function: Corporate Product Certification Manager	Function: Data Processing Specialist CTD
At Warsaw on 2024-02-07	At Warsaw on 2024-02-07
	

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sika MonoTop®-4052

79593779

07/02/2024 2

1029

CE		
23		
Sika Services AG, Zürich, Switzerland		
79593779		
Mechanical resistance	Wear resistance (Boehme)	A15
	Flexural strength	F10
	Compressive strength	C60
Reaction to fire	Class A1 _{fi}	
EN 13813:2002		
1139		
All other uses — Cementitious screed material		
For internal uses subject to reaction to fire regulations — Cementitious screed material		

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sika MonoTop®-4052

79593779

07/02/2024 2

1029