



**BUILDING TRUST** 

# PRODUCT DATA SHEET EVERBUILD OIL AWAY®

High performance cleaner for drives, patio & Paths.

## **PRODUCT DESCRIPTION**

EVERBUILD OIL AWAY<sup>®</sup> is the quick and easy solution for removing oil, petrol, diesel and grease stains from driveways and garage floors. EVERBUILD OIL AWAY<sup>®</sup> works on most common surface types including concrete, stone, tarmac, most common paving materials and BBQ areas. EVERBUILD OIL AWAY<sup>®</sup> can also be used as a general cleaner to revive the look of pathways and patio areas.

## USES

- Removing oil stains from driveways including concrete, stone, tarmac, block paving etc.
- As a general cleaner for paths, patios and driveways.

## **PRODUCT INFORMATION**

# CHARACTERISTICS / ADVANTAGES

- Ready to use, no diluting required.
- Available in a handy ready to use spray.
- Water clean up.

Odour	Slight
Coverage	Approx. 5-8m <sup>2</sup> per litre de-
	pending on porosity of
	substrate.

1Ltr Trigger Spray Bottle.
Clear pale green / yellow liquid
24 months form date of manufacture.
KEEP AWAY FROM CHILDREN. Store away from alkaline products and bleach between 5 - 30°C.
1.02g/cm <sup>3</sup>
6.0-8.0

## **APPLICATION INSTRUCTIONS**

#### SUBSTRATE PREPARATION

Remove any surface debris using a stiff brush. Large deposits of organic growth should be first treated with Everbuild Patio Wizard prior to application of Oil Away.

#### APPLICATION

#### Stain Removal

EVERBUILD OIL AWAY<sup>®</sup> is supplied ready to use and does not require diluting. Spray EVERBUILD OIL AWAY<sup>®</sup> directly onto the stain, work in well with a stiff bristled brush and leave for 5 minutes. Do not allow EVERBUILD OIL AWAY<sup>®</sup> to dry on the surface. Wash down the area with clean fresh water whilst scrubbing with a stiff brush. Further applications may be re-

Product Data Sheet EVERBUILD OIL AWAY® March 2018, Version 01.01 02189015000000038 quired depending on level of soiling. Should this be necessary, repeat procedure until stains are removed. *General Cleaning of Paths Patios etc.* 

Dampen surface to be treated with water. Apply EVER-BUILD OIL AWAY<sup>®</sup> liberally over the area and work in well with a stiff brush. Wash down the area with clean fresh water whilst brushing.

# LIMITATIONS

- Always test a small inconspicuous area prior to full application
- Do not leave on Tarmac for longer than 5 minutes.
  As quality/condition of Tarmac can vary significantly, always test a small area prior to full application.
- Do not allow EVERBUILD OIL AWAY<sup>®</sup> to dry on the surface.
- Do not apply to hot surfaces or in strong direct sunlight.
- If EVERBUILD OIL AWAY<sup>®</sup> comes into contact with plants or lawn edges, rinse thoroughly with clean water.
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for advice.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

# ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

# **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recom-Read ation of a burg fraguess of the sady in the fored. The use 4.0 kither product must test the product's suitability forstheeintended application and any pase Sika resurvessboewright to change the preopersties of itso products of the proprietary rights of the base must ble biserved All orders are accepted subject to our clwifeneterms of sale and delivery to seise himise always refer to the most recent issue of the local Product



Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILDOILAWAY-en-GBEVER-(03-2018)-1-1.pdf



**BUILDING TRUST**