





PRODUCT DATA SHEET

Sika MaxMix® Mortar Plasticiser

highly concentrated air entraining liquid plasticising admixture

PRODUCT DESCRIPTION

Sika MaxMix® Mortar Plasticiser is an liquid air entraining agent for brick laying mortars, renders, pointing and screeds. It can be used in all situations where improved workability is required. 1L treats up to 5 tons of cement.

USES

- Pointing mortars
- Renders
- Screeds
- Bricklaying mortars

CHARACTERISTICS / ADVANTAGES

- Concentrated formula. 1 L is equivalent to 25 L of standard mortar plasticiser.
- Easy to use gauged bottle.
- Superior plasticising action
- Improves workability of mortars.

APPROVALS / STANDARDS

Tested to BSEN934-3:2009

PRODUCT INFORMATION

1ltr bottle
Dark brown liquid with characteristic odour
24 months from date of manufacture in unopened containers.
Store in original unopened containers between 5 and 30°C.
1.02 - 1.06 g/cm ³
7.2 - 9.2
25.2 - 27.9%
<0.1% w/w
5-10ml per 50kg of cement

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Shake bottle well before use. Push the lid downwards and twist anti-clockwise to remove. Squeeze the sides of the bottle to fill the measuring cup to the required

dose (5-10ml per 50kg of cement).

Add Sika MaxMix® Mortar Plasticiser to a bucket of water and stir/mix well (use up to a maximum 10ltrs of water). Dry mix all other ingredients and add sufficient quantities of water/Sika MaxMix® Mortar Plasticiser solution until the desired consistency is achieved. Never add Sika MaxMix® Mortar Plasticiser directly to

Product Data Sheet Sika MaxMix® Mortar Plasticiser May 2018, Version 01.01 021405061000000011 the dry mix, always let down into a portion of gauging water. Replace cap after use.

LIMITATIONS

- Do not use in structural concrete.
- Do not exceed the recommended dosage rate range.
- Do not mix with other additives in same gauging water.
- Do not use in lime based mixes.
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services Department for further advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds, LS9 0SW Tel: 0113 240 3456 Web: www.everbuild.co.uk Twitter: @everbuild

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited

SikaMaxMixMortarPlasticiser-en-GBEVER-(05-2018)-1-1.pdf





